

DESCRIPTION

The Verifact Model K is a dynamic microphone with a modified omni-directional pattern, and is especially designed for areas with excessive background noise, or where the ambient sound level is high. The modified pattern is one in which the audio pickup is more from the front of microphone and less from the sides and back. Model K is compatible with all Louroe Base Stations.

APPLICATION

When part of a Louroe Audio System, the Model K Microphone can be used in situations such as:

- Convenience Stores
- Fast Food Restaurants
- Mall Shops
- Reception Areas
- Public Transportation Vehicles
- Casino soft count rooms

...Any area where ambient sound level is high

IMPORTANT NOTICE

When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.



Federal Law References:
Federal Regulations, US Code, Title 18. Crime and Criminal Procedure, Sec 2510.



WIRING REQUIREMENTS

2 Conductor shielded cable, 22 gauge with a 24 gauge drain wire.
West Penn 452 or equivalent

NOTE: Unshielded cable is not satisfactory for audio systems.



MODEL K MICROPHONE

COMING
NEXT

FEATURES

- Microphone can pick up normal sounds 12' away
- May be located up to 1,000' from the base station
- Pre-amp with line level output
- Sensitivity switch for lowering gain
- Mounts to a ceiling or flat surface
- Phantom powered from Louroe Base Station

SPECIFICATIONS

Frequency response	40 Hz to 15 kHz \pm 1 dB
Line level output	0 dB @ 1000 Ω
Current drain	4 mA
Supply voltage	12 Vdc
Output impedance (mic only)	600 Ω unbalanced
Dimensions	5 7/8"L x 3 1/8 "W