

USA VISION SYSTEMS
Enterprise Class Series
3U Rackmount DVR Server



System Models		800			1120		1240		1480
Hot Swap Bays		0/ 2							
CPU		Intel i3 Ivy Bridge (3rd Gen.)							
Memory (RAM)		8 GB DDR3							
Video	Codec	MPEG4, MJPEG, H.264							
	Input	4	8	16	8	16	8	16	16
Video Loop (optional)		4	8	16	8	16	8	16	16
Audio	Compression	ADPCM , G.723, AAC (16 kHz / 16 bit)							
	Input	4	4	4	8	16	8	16	16
Display Frames (total)	NTSC	120			480		480		480
	PAL	100			400		400		400
Recording Frames (total) at (CIF)	NTSC	120			120		240		480
	PAL	100			100		200		400
Video Resolution	NTSC	320 x 240, 360 x 240, 640 x 480, 640x 480 De-interlace, 720 x 480, 720 x 480 De-interlace							
	PAL	320 x 240, 360 x 288, 640 x 480, 640 x 480 De-interlace, 720 x 576, 720 x 576 De-interlace							
Backup Type		DVD±R, DVD±RW, CD-R/RW							
Recovery DVD		Automatic System Rebuild							
Alarm Inputs	Sensor Input	4*							
	Alarm Output	4*							
Connector	Ethernet	1 x RJ-45, 10/100/1000 Mbps							
	VGA Output	2 (DVI, VGA, or HDMI)							
	USB 2.0 (F + R)	2 Front + 4 Rear							
	USB 3.0	2 Rear							
Remote Access		TCP/IP, LAN, WAN, Internet, ISDN							
Operating Temperature		0 to 45 °C (32 to 133 °F)							
Humidity		0 to 80% RH (non condensing)							
Dimensions (W x D x H)		19 x 21 x 5.25 inch							
Optional Products		GV-IO 12-In Card / GV-IO 12-Out Card / GV-IO Box 4 / GV-IO Box 8 / GV-IO Box 16 / GV-Data Capture Box Series / GV-Hub Box / GV-COM Box/ GV-DOM / GV-Joystick / GV-Remote / GV - Keyboard							
Languages		English/ Spanish							