



Temperature Screening Solution

Flexible Product Choice for a Multitude of Scenarios

WEC Temperature Screening Solution, with multiple product types and wide range of applications, is designed for the detection of skin-surface temperatures so as to achieve rapid and safe preliminary screening in public areas with high efficiency in a multitude of scenarios.

Thermographic
Cameras



Pain Points of Conventional Methods



Conventional methods – such as using an ear thermometer or mercury thermometer – have obvious deficiencies in detecting people with abnormal temperature in public places:

Close Contact, High Risk

Close contact among the users leads to potential risks.

High Cost, Low Efficiency

Increased manpower required, but 1-by-1 inspection is inefficient.

Lack of Intelligent Analysis

Manual registration is required, which may lead to human error and not so timely feedback.

We Offer a Better Approach



An approach that incorporates competent technologies, instead of manpower alone, can be a much better choice in many ways. Such an approach is:



Safer

Non-contact measurement to avoid physical contact



Faster

One second per person for skin-surface temperature detection



Smarter

AI detection, greatly reducing false alarms

Advantages of Thermal Technology

- AI technology ensures thermographic cameras only detect human skin-surface temperature to reduce false alarms of other heat sources.
- Compensation algorithm ensures the temperature is compensated with ambient temperature and the distance of the measured target for better accuracy.
- Thermal technology has been applied widely in temperature screening scenarios as it offers more flexibility and efficiency in preliminary screening of elevated skin-surface temperatures.



Workflow

Entering detection area

1

Human skin-surface temperature measurement
Fast preliminary temperature screening without contact



Locating potential abnormal temperatures

3

Second check with mercury or ear thermometers

4

Solution Overview

OPERATION TIPS

- Install the devices in a windless indoor environment
- Set up a specific temperature measurement zone
- Double-check with a thermometer upon detection of elevated skin-surface temperatures

Temperature Screening with Fast Deployment

Thermographic Cameras

Visualized bi-spectrum live view

Wireless Devices

Easy connection, cable free



Thermographic Bullet/Turret Camera

Thermographic Handheld Camera

Flexible product choice for temperature screening of building entrances, elevator halls, airport security checks, etc.

Group Temperature Screening

Group Screening with High Efficiency



Thermographic Bullet Camera

Supports simultaneous temperature screening of multiple people, greatly enhancing efficiency

Temperature Screening on Patrol

Anytime, Anywhere, Just One Click



Thermographic Handheld Camera

Supports preliminary on-spot temperature screening without disturbing a person

Temperature Screening & Mask Detection

Intuitive Demonstration



Thermographic Camera & DeepinMind NVR

The special interface of DeepinMind NVR visually displaying temperature and mask status

Product Showcase

Thermographic Cameras

Thermographic Bullet Camera

DS-2TD2617B-3/6PA

- Thermal resolution: 160 × 120
- Thermal lens: 3 mm / 6 mm
- Optical: 2688 × 1520
- Optical lens: 4 mm / 8 mm
- Bi-spectrum image fusion
- Accuracy: ±0.5°C (±0.3°C with blackbody)
- Measurement range: 30-45°C
- Supports audio alarms
- Working temperature: 10-35°C
- AI human detection, false alarms reduction
- Simultaneous temperature screening for multiple people (Up to 30 people)



Thermographic Turret Camera

DS-2TD1217B-3/6PA

- Thermal resolution: 160 × 120
- Thermal lens: 3 mm / 6 mm
- Optical: 2688 × 1520
- Optical lens: 4 mm / 8 mm
- Bi-spectrum image fusion
- Accuracy: ±0.5°C (±0.3°C with blackbody)
- Measurement range: 30-45°C
- Supports audio alarms
- Working temperature: 10-35°C
- AI human detection, false alarms reduction
- Simultaneous temperature screening for multiple people (Up to 30 people)



Thermographic Bullet Camera

DS-2TD2636B-15/P

DS-2TD2636B-13/P

DS-2TD2637B-10/P

- Thermal resolution: 384 × 288
- Thermal lens: 15 mm / 13 mm / 10 mm
- Optical: 2688 × 1520
- Optical lens: 6 mm / 6 mm / 4 mm
- Accuracy: ±0.5°C (±0.3°C with blackbody)
- Measurement range: 30-45°C
- Working temperature: 10-35°C
- AI human detection, false alarms reduction
- Simultaneous temperature screening for multiple people (Up to 30 people)



Thermographic Handheld Camera

DS-2TP21B-6AVF/W

- Thermal resolution: 160 × 120
- Optical resolution: 640 × 480
- Measurement range: 30-45°C
- Touch screen
- Accuracy: ±0.5°C
- Bi-spectrum image fusion
- Supports Wi-Fi
- Supports audio alarms
- Automatic screenshots & uploading



*WEC Temperature Screening Thermographic Cameras are designed for the detection of skin-surface temperatures so as to achieve rapid preliminary screening in public areas. Actual core body temperatures should be further confirmed using clinical measurement devices. Under any circumstances, it is highly recommended to use Hikvision's Thermographic Cameras in accordance with local laws and regulations.