

# WECHNC3V241E-IRS-S2/28

## 4MP IR Mini Dome Network Camera



- 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- Outputs 4MP (2560 × 1440)@25/30 fps, max. supports 4MP (2688 × 1520) @ 20 fps
- H.265 coding, high compression ration, low bit rate
- Built-in IR LED, max IR distance: 30 m
- ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire
- Abnormality detection: Motion detection, video tempering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection
- Max. 256 GB SD card
- 12V DC/POE power support
- IP67, IK10 protection grade



### System Overview

With upgraded H.265 encoding technology, Dahua Lite series camera has efficient video encoding capacity, which saves bandwidth and storage space. This camera adopts the latest starlight technology and displays better colorful image in the environment of low illumination. It supports SD card storage, waterproof function, dust-proof function and tamper-proof function, complying to the standards of IP67 and IK10.

### Functions

#### Smart (H.265+ & H.264+)

Adopting advanced algorithm of auto stream control according to the environment, Dahua smart encoding technology realizes the higher efficiency than (H.265 & H.264), providing high-quality video, and reducing the cost of storage and transmission.

#### Wide dynamic range (WDR)

Dahua adopts advanced Wide Dynamic Range (WDR) technology. You can get clear details in the environment of strong brightness contrast. In high brightness and back-light environment, bright region and dark region with strong light source, you can also get clear images.

#### Starlight

Dahua Starlight technology mainly applies to the environment of low illumination, and it can provide clear colorful video. Even in the environment of min. illumination, the technology can guarantee the good image effect.

#### Intelligent Video Analysis (IVS)

With advanced video algorithm, Dahua camera supports intelligent detection, such as tripwire and intrusion and so on.

#### Protection (IP67, IK10, wide voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can works normal after soaking in 1 m deep water for 30 minutes.

IK10: The enclosure can stand the punch more than 5 times from a 5 kg hammer falling from a height of 40 m (Impact energy is 20J).

Wide voltage: The camera allows  $\pm 30\%$  input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

Technical Specification					
<b>Camera</b>					
Image Sensor	1/3" CMOS				
Effective Pixels	2688 (H) × 1520 (V)				
ROM	128 MB				
RAM	128 MB				
Scanning System	Progressive				
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100000 s				
Min. Illumination	0.008 Lux @ F1.6				
IR Distance	30 m (98.43 ft) (IR)				
IR On/Off Control	Auto/Manual				
IR LEDs Number	3 (IR LED)				
Pan/Tilt/Rotation Range	Horizontal: 0°–355° Vertical: 0°–65° Rotation: 0°–355°				
<b>Lens</b>					
Lens Type	Fix focal				
Mount Type	M12				
Focal Length	2.8 mm 3.6 mm				
Max. Aperture	F1.6				
Field of View	2.8 mm: Horizontal: 102.0° Vertical: 55.0° Diagonal: 121.0° 3.6 mm: Horizontal: 84.0° Vertical: 45.0° Diagonal: 100.0°				
Iris Type	Fixed				
Close Focus Distance	2.8 mm: 0.9 m (2.95 ft) 3.6 mm: 1.6 m (5.25 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8mm	56 m (183.73 ft)	22.4 m (73.49 ft)	11.2 m (36.75 ft)	5.6 m (19.37 ft)
	3.6mm	80 m (262.47 ft)	32 m (104.99 ft)	16 m (52.49 ft)	8 m (26.25 ft)
<b>Smart Event</b>					
General IVS Analytics	Intrusion; tripwire				
<b>Video</b>					
Video Compression	H.265; H.264; H.264B; MJPEG				
Smart Codec	H.264: Yes H.265: Yes				
Video Frame Rate	50Hz Main stream (2560 × 1440@25 fps); sub stream (704 × 576@25 fps) Main stream (2688 × 1520@20 fps); sub stream (704 × 576@20 fps) 60Hz Main stream (2560 × 1440@30 fps); sub stream (704 × 480@30 fps) Main stream (2688 × 1520@20 fps); sub stream (704 × 480@20 fps)				
Stream Capability	Main stream; sub stream				
Resolution	2688 × 1520 (2688 × 1520); 2560 × 1440 (2560 × 1440); 2304 × 1296 (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)				
Bit Rate Control	CBR/VBR				
Video Bit Rate	H.264: 32 kbps–6144 kbps H.265: 12 kbps–6144 kbps				
Day/Night	ICR switch				
BLC	Yes				
WDR	120 dB				
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom				
Gain Control	Auto/Manual				
Noise Reduction	3D DNR				
Motion Detection	Disable/Enable (4 areas, rectangle)				
Region of Interest(Rol)	Yes (4 areas)				
Smart IR	Yes				
Image Rotation	0°/90°/180°/270° (Supports 90°/270° with 2688 × 1520 resolution.)				
Mirror	Yes				
Privacy Masking	4 areas				
<b>Network</b>					
Network	RJ-45 (10/100 Base-T)				
Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; RTMP; Multicast; HTTPS; SFTP; 802.1x; ICMP; IGMP				
Interoperability	ONVIF (Profile S/Profile G); CGI; Milestone; Genetec				
Scene self-adaptation	20				
User/Host	20				
Edge Storage	Dahua Cloud; FTP; Micro SD card (max. 256 GB); NFS				
Browser	IE Google Firefox				
Management Software	Smart PSS; DSS; DMSS				
Mobile Phone	IOS; Android				
<b>Certification</b>					
Certifications	CE-LVD: EN60950-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL: UL60950-1 CAN				
<b>Power</b>					
Power Supply	12V DC/POE				
Power Consumption	Basic power consumption: 1.9W (12V DC); 2.3W (POE) Max power consumption (H.265 + WDR + Intelligent function + IR): 4.5W (12V DC), 5.2W (POE)				

Environment

Operating Temperature	-40°C to +60°C (-40°F to +140°F)
Operating Humidity	≤95%
Storage Temperature	-40°C to +60°C (-40°F to +140°F)
Storage Humidity	≤95%
Protection Grade	IP67, IK10

Structure

Casing	Metal
Dimensions	81 mm × Φ109.9 mm (3.19" × Φ4.33")
Net Weight	0.350 kg (0.77 lb)
Gross Weight	0.491 kg (1.08 lb)

Ordering Information

Type	Part Number	Description
4MP Camera	HNC3V241E-IRS-S2/28	4MP IR Mini Dome Network Camera,PAL
	HNC3V241E-IRS-S2/28	4MP IR Mini Dome Network Camera,NTSC
Accessories (optional)	PFA136	Junction Box
	PFA200W	Rain Shade
	PFB203W	Wall Mount
	PFA152-E	Pole Mount
	PFA106	Mount Adapter
	PFB220C	Ceiling Mount
	PFM321D	DC12V1A Power Adapter
	LR1002-1ET/1EC	Single-port Long Reach Ethernet Over Coax Extender
	PFM900-E	Integrated Mount Tester
	PFM114	TLC SD Card



PFM321D  
DC12V1A Power Adapter



LR1002-1ET/1EC  
Single-port long reach ethernet over coax extender




PFM900-E  
Integrated Mount tester



PFM114  
TLC SD card

Junction Mount	Wall Mount	Wall Mount	Pole Mount
PFA136	PFA136+PFA200W	PFB203W	PFB203W+PFA152-E
Ceiling Mount			
PFA106+PFB220C			

Dimensions (mm[inch])



Accessories

Optional:



PFA136  
Junction Box



PFA200W  
Rain Shade



PFA106  
Wall Mount



PFA152-E  
Pole Mount



PFA106  
Mount Adapter



PFB220C  
Ceiling Mount