# Product Data Sheet | Anixter Catalog Page



## RUS/REA PE-39 Design



## **Product Description**

For use in exchange and campus areas, direct buried or installed in-duct. Suitable for voice frequency use on all pairs and carrier frequency, both analog and digital, on a selected pair assignment basis. For full utilization at carrier frequencies, a core-dividing screen is required.

## **Specifications**

- Solid, annealed, bare copper conductors
- Solid polyolefin insulation, color-coded to telephone industry standards
- Insulated conductors are twisted into pairs of varying lengths of lay to minimize crosstalk
- Pairs are stranded into units (and super units, if required by pair count)
- The cable core is filled with a waterproofing compound and wrapped with a non-hygroscopic core tape
- A flooding compound is applied over the core and to all surfaces of the shield/armor to resist moisture entry and to inhibit corrosion
- The cable is finished with a black polyethylene jacket which is sequentially printed with footage marker at regular intervals

#### Tech. Info & Standards

Cables with AFC suffix conform to ANSI ICEA 7CFR-1755-390

#### Standard Cables - SEALPIC-F

A 0.008 in. coated aluminum black polyethylene (part suffix AFC)

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • Fasteners

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com

Anixter is a leading global supplier of communications and security products, electrical and electronic wire and cable, fasteners and other small components. We help our customers specify solutions and make informed purchasing decisions around technology, applications and relevant standards. Throughout the world, we provide innovative supply chain management solutions to reduce our customers' total cost of production and implementation.



| Part No.    | No. of Pairs | AWG | Approx. Wt.<br>lb./1,000 ft. | Nom. O.D.<br>(in.) |
|-------------|--------------|-----|------------------------------|--------------------|
| E-000624AFC | 6            | 24  | 67                           | 0.390              |
| E-001224AFC | 12           | 24  | 102                          | 0.470              |
| E-002524AFC | 25           | 24  | 175                          | 0.590              |
| E-005024AFC | 50           | 24  | 304                          | 0.750              |
| E-010024AFC | 100          | 24  | 561                          | 1.010              |
| E-020024AFC | 200          | 24  | 1,029                        | 1.330              |
| E-030024AFC | 300          | 24  | 1,532                        | 1.680              |
| E-040024AFC | 400          | 24  | 1,997                        | 1.900              |
| E-000622AFC | 6            | 22  | 91                           | 0.450              |
| E-001222AFC | 12           | 22  | 143                          | 0.550              |
| E-002522AFC | 25           | 22  | 255                          | 0.700              |
| E-005022AFC | 50           | 22  | 468                          | 0.940              |
| E-010022AFC | 100          | 22  | 853                          | 1.240              |
| E-040022AFC | 400          | 22  | 3,125                        | 2.370              |

## Sales Tips

If stock not available, suggest substitution of part number suffix DFC for foam/skin insulated product.

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • Fasteners

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com