

## 6000 / 7000-SERIES 3MP IP DOME CAMERA

**OE-C6413-AWR**

**OE-C7413-AWR**



The OpenEye OE-C6413-AWR and OE-C7413-AWR are compact 3MP mini-dome cameras with big camera features like a 3x motorized, autofocus lens. Perfect for users who require an unobtrusive camera but do not wish to sacrifice functionality for a smaller footprint. A crystal clear image and ease of installation are guaranteed, thanks to true WDR, adaptive IR technology, a 3-axis gimbal, and PoE.

All OpenEye IP cameras are fully ONVIF™ compliant and are compatible with the OpenEye Web Services platform, allowing advanced operation, configuration and viewing of high definition video remotely from any Web browser.

### FEATURES

- 3MP maximum resolution
- 2.8-8mm autofocus lens
- Adaptive IR LEDs
- True Wide Dynamic Range @ 2MP
- 3-Axis Gimbal Positioning
- IP66 Outdoor rating (OE-C7413-AWR only)
- ONVIF™ Profile S compliant



## SPECIFICATIONS


CAMERA		
Part Number	OE-C6413-AWR	OE-C7413-AWR
Maximum Resolution	3MP	
Image Sensor	1/3" Progressive CMOS	
Video Compression	H.264 / MJPEG	
Frame Rate	30FPS @ 3MP H.264	
ONVIF	Profile S compliant	
Streaming	Up to 4 simultaneous streams	
Browser Support	Internet Explorer (6+) / Chrome / Firefox / Safari	
Day / Night	True Day / Night	
Wide Dynamic Range	Shutter on / off @ 2MP	
Lens	2.8~8mm autofocus	
Field of View	99° (Wide), 51° (Tele)	
White Balance	Auto / Manual / ATW / One Push	
Auto White Balance Range	2700~7800K	
Backlight Compensation	2500~10000K	
Auto Gain Control	Yes	

ENVIRONMENTAL		
Operating Temperature	-14 ~ 122 °F (-20 ~ 50 °C)	
IP Rating	N/A	IP66 Outdoor
UL Listed Product	Yes	

POWER	
Power Consumption	5W
Input Voltage	PoE
PoE Class	3

PHYSICAL	
IR Range	Up to 25M
IR LED	4 IR LEDs
microSD Card Slot	SDXC 64GB support
Camera Weight	1.13lb (512g)
Dimensions	ø 4.6 x 3.36in (117 x 83.5mm)
Housing / Dome Cover	Plastic / metal housing

## CONNECTIONS




microSD Card Slot	1	Insert the microSD card into the card slot to store video and snapshots
Reset Button	2	Press the reset button with a proper tool for at least 20 seconds to return the camera to factory defaults
RJ-45 Dongle*	3	For network and PoE connections


RJ-45 Dongle is for the OE-C7413-AWR only.

## DIMENSIONS


### FRONT VIEW



### BOTTOM VIEW



## ACCESSORIES



## ACCESSORIES



OE-C7413-AWR



OE-CA75APM  
(Pendant Mount Adapter)



OE-CA75PM  
(Pendant Mount)



OE-CA510W  
(7.25" Wall Mount)



OE-CA510WL  
(13.5" Wall Mount)



OE-CA510PA25  
(1.25" Threaded  
Pipe Adapter)



OE-CA510PA50  
(1.5" Threaded  
Pipe Adapter)



OE-CA510P25  
(10" Ceiling Pole  
Mount)



OE-CA510P50  
(20" Ceiling Pole  
Mount)



Kit: OE-CA97CMS  
(Short Arm Corner  
Mount Kit)



Kit: OE-CA97CML  
(Long Arm Corner  
Mount Kit)



Kit: OE-CA97PLMS  
(Short Arm Pole  
Mount Kit)



Kit: OE-CA97PLML  
(Long Arm Pole  
Mount Kit)



Kit: OE-CA97WMS  
(Short Arm Pen-  
dant Mount Kit)



Kit: OE-CA97WML  
(Long Arm Pen-  
dant Mount Kit)