





LED-2364HD

This LED-backlit monitor features the latest technology with enhanced picture clarity and sharpness which is ideal for broadcast production and video surveillance applications.

Benefits

LED backlight: brighter picture using less power Full HD (1080i/p) with no downscaling Great picture quality with motion adaptive 3D De-interlace noise reduction USB and SD Card ports for displaying multi-media files (video, pictures, music, and text) RS-232 Control (looping)

IR Remote Control

| Specifications | |
|--------------------------|---|
| Mount | VESA 100 x 100mm |
| HD Compatible | Yes |
| Anti Glare Coating | Yes |
| Case | Durable ABS Plastic |
| IR Remote Control | Yes |
| Native Aspect Ratio | 16:9 |
| Visible Screen Size (WH) | 20.5" x 11.54" / 521.28 x 293.22mm |
| Resolution | 1920 x 1080 (Full HD) |
| Brightness Rating | 250 cd/m² (Nit) |
| Contrast Ratio | 3000:1 |
| Back Light | LED |
| Color Depth | 16.7 million |
| Number of Pixels | 2,073,600 |
| Response Time | 5ms (Rising/Falling) |
| Audio Power / Speakers | 2 Speakers x 2.5 Watts |
| Viewing Angle (L/R/T/B) | 85/85/85/85 degrees |
| Digital Signal Processor | 3D Comb Filter |
| Operating Temp | 32 ~ 104°F / 0 ~ 40°C |
| Humidity | 10% ~ 90% |
| HDMI | x2 Input |
| VGA | x1 Input |
| Composite | x2 BNC Inputs / Outputs |
| RS-232 | x1 Input; x1 Output (loop-through) |
| USB 2.0 | x1 Input |
| SD Card | x1 Input |
| Audio | x2 Inputs |
| Power | x1 DC12V Input |
| Power Requirements | 100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included |
| Power Consumption | <35 Watts (Active) / 0.5 Watts (Stand-by) |
| Dimensions | 22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm |
| Weight | Net: 9.04 lbs / 4.1 kg; Gross: 12.57 lbs / 5.7 kg |

Specifications subject to change.