

**ICONA SERIES HANDS-FREE COLOUR MONITOR. SBTOP SYSTEM**

Flush-mounted (in box Art. 6117) or wall-mounted (with bracket Art. 6620) colour monitor with 4.3" 16/9 screen, Full-Duplex hands-free audio and touch-sensitive controls. Allows adjustment of brightness level, contrast, audio volume and ringtone volume. Ringtones can be customised by selecting from the various melodies provided. Fitted as standard with a key button, enable/disable audio button with corresponding indicator LEDs and a further 7 programmable buttons for self-ignition, privacy service and other programmable functions. It is normally used for floor door call and call repetition management, and comes complete with 2 x 8-position DIP SWITCHES for user code programming and button programming. Equipped with riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire SimplebusTop Colour systems. Dimensions 142.5x147x23 mm.

**General specifications**

Audio system:	No
Audio/video system:	Yes
Flush-mounted:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Induction loop function:	No
Type of display:	LCD
Display size (inches):	4.3", 16:9
Touch screen display:	No
OSD display:	No
Display resolution (H x V):	480x272pixel
B/W or colour display:	Colori
Product colour:	Bianco RAL9003
Sensitive Touch technology:	Yes
Total buttons:	15
Backlighting color:	Bianco

**Functions**

Actuator control function:	Yes
Self-ignition:	Yes
Switchboard call function:	Yes
Panic call:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes

## DATA SHEET

Privacy function:	Yes
Doctor:	Yes
Redial:	Yes
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	Yes
Alarm function:	Yes
Privacy conversation function:	Yes
Key button function:	Yes
Full Duplex hands-free function:	Yes

### Hardware specifications

Customisable housing:	No
Removable terminals:	Yes

### Settings

Loudspeaker volume control:	Yes
Microphone volume control:	Yes
Ringtone volume control:	Yes
Display brightness control:	Yes
Display contrast control:	Yes
Display colour control:	No

### General info

Product height (mm):	147
Product width (mm):	142,5
Product depth (mm):	23

### Compatibility

Video door entry family:	Yes
Simplebus Top system:	S2
Simplebus Color system:	Yes

### Technical specifications

Power supply voltage:	22÷28Vdc
Maximum current absorption (mA):	400
Support SD card (card not in equipment):	No
IP Rating:	30
Operating temperature (°C):	-5÷40
Relative humidity for operation:	25 - 75 %
Video encoding:	MPEG
Product weight (g):	0,7
Clamps:	L L - + CFP1 CFP2 S+ S- IN1 IN2