



LED-1003HDX

This 9.7" free standing monitor features the latest screen imaging technology for enhanced clarity and sharpness. Both analog and digital video will benefit by being viewed on this monitor, and it is the best match for displaying higher resolution.

Benefits		
LED backlight: brighter picture using less power		
Wide viewing angle		
Excellent contrast ratio		
Very fast response time		
Image enhancing: 3D Interlace comb filter, DNR, 4H filter		
Durable metal case		
No front controls		

Accessories

DC-1500: Factory approved car cord HM-400: Under-cabinet hinge mount WM-31: Wall mount bracket (fixed) WM-302: Wall mount with swing arm & 4-way adjustable

Related Products

LED-1003HD: Free standing LED-1003HDL: Flush mount LED-1003HDLX: Flush mount with no front controls

SpecificationsMountDeskstand; VESA 75x75mm and 100x100mm; ¼ - 20 pad on topHD CompatibleYesAnti Glare CoatingYesCaseMetalNative Aspect Ratio4:3Visible Screen Size (WH)7.8" x 5.9" / 197.6 x 148.8mmResolution1024(H) x 768(V)Brightness Rating400 cd/m² (Nit)Contrast Ratio1000:1Back LightLED (30K)PC CompatibilityYesDot Pitch0.192(H) x 0.192(V)mmColor Depth262,144Number of Pixels786,432Response Time2ms / 2ms (Rising/Falling)Viewing Angle (L/R/T/B)89/89/89 degrees3D Comb Filter3D interlace & DNR, 4H filterDimensions8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mmOperating Temp32 ~ 104°F / 0 ~ 40°CPower Requirements12VDC; 2A; Negative GroundPower Consumption30 Watts (Max)Compositex1 BNC Input; x1 BNC Output		
Mount100x100mm; ¼ - 20 pad on topHD CompatibleYesAnti Glare CoatingYesCaseMetalNative Aspect Ratio4:3Visible Screen Size (WH)7.8" x 5.9" / 197.6 x 148.8mmResolution1024(H) x 768(V)Brightness Rating400 cd/m² (Nit)Contrast Ratio1000:1Back LightLED (30K)PC CompatibilityYesDot Pitch0.192(H) x 0.192(V)mmColor Depth262,144Number of Pixels786,432Response Time2ms / 2ms (Rising/Falling)Viewing Angle (L/R/T/B)89/89/89 degrees3D Comb Filter3D interlace & DNR, 4H filterDimensions8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mmOperating Temp32 ~ 104°F / 0 ~ 40°CPower Requirements12VDC; 2A; Negative GroundPower Consumption30 Watts (Max)	Specifications	
Anti Glare Coating Yes Case Metal Native Aspect Ratio 4:3 Visible Screen Size (WH) 7.8" x 5.9" / 197.6 x 148.8mm Resolution 1024(H) x 768(V) Brightness Rating 400 cd/m² (Nit) Contrast Ratio 1000:1 Back Light LED (30K) PC Compatibility Yes Dot Pitch 0.192(H) x 0.192(V)mm Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Mount	
Case Metal Native Aspect Ratio 4:3 Visible Screen Size (WH) 7.8" x 5.9" / 197.6 x 148.8mm Resolution 1024(H) x 768(V) Brightness Rating 400 cd/m² (Nit) Contrast Ratio 1000:1 Back Light LED (30K) PC Compatibility Yes Dot Pitch 0.192(H) x 0.192(V)mm Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	HD Compatible	Yes
Native Aspect Ratio 4:3 Visible Screen Size (WH) 7.8" x 5.9" / 197.6 x 148.8mm Resolution 1024(H) x 768(V) Brightness Rating 400 cd/m² (Nit) Contrast Ratio 1000:1 Back Light LED (30K) PC Compatibility Yes Dot Pitch 0.192(H) x 0.192(V)mm Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Anti Glare Coating	Yes
Visible Screen Size (WH) 7.8" x 5.9" / 197.6 x 148.8mm Resolution 1024(H) x 768(V) Brightness Rating 400 cd/m² (Nit) Contrast Ratio 1000:1 Back Light LED (30K) PC Compatibility Yes Dot Pitch 0.192(H) x 0.192(V)mm Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Case	Metal
Resolution 1024(H) x 768(V) Brightness Rating 400 cd/m² (Nit) Contrast Ratio 1000:1 Back Light LED (30K) PC Compatibility Yes Dot Pitch 0.192(H) x 0.192(V)mm Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7." x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Native Aspect Ratio	4:3
Brightness Rating 400 cd/m² (Nit) Contrast Ratio 1000:1 Back Light LED (30K) PC Compatibility Yes Dot Pitch 0.192(H) x 0.192(V)mm Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Visible Screen Size (WH)	7.8" x 5.9" / 197.6 x 148.8mm
Contrast Ratio 1000:1 Back Light LED (30K) PC Compatibility Yes Dot Pitch 0.192(H) x 0.192(V)mm Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Resolution	1024(H) x 768(V)
Back Light LED (30K) PC Compatibility Yes Dot Pitch 0.192(H) x 0.192(V)mm Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Brightness Rating	400 cd/m ² (Nit)
PC Compatibility Yes Dot Pitch 0.192(H) x 0.192(V)mm Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Contrast Ratio	1000:1
Dot Pitch 0.192(H) x 0.192(V)mm Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Back Light	LED (30K)
Color Depth 262,144 Number of Pixels 786,432 Response Time 2ms / 2ms (Rising/Falling) Viewing Angle (L/R/T/B) 89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104° F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	PC Compatibility	Yes
Number of Pixels786,432Response Time2ms / 2ms (Rising/Falling)Viewing Angle (L/R/T/B)89/89/89/89 degrees3D Comb Filter3D interlace & DNR, 4H filterDimensions8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mmOperating Temp32 ~ 104°F / 0 ~ 40°CPower Requirements12VDC; 2A; Negative GroundPower Consumption30 Watts (Max)	Dot Pitch	0.192(H) x 0.192(V)mm
Response Time2ms / 2ms (Rising/Falling)Viewing Angle (L/R/T/B)89/89/89/89 degrees3D Comb Filter3D interlace & DNR, 4H filterDimensions8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mmOperating Temp32 ~ 104°F / 0 ~ 40°CPower Requirements12VDC; 2A; Negative GroundPower Consumption30 Watts (Max)	Color Depth	262,144
Viewing Angle (L/R/T/B) 89/89/89/89/89 degrees 3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Number of Pixels	786,432
3D Comb Filter 3D interlace & DNR, 4H filter Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Response Time	2ms / 2ms (Rising/Falling)
Dimensions 8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm Operating Temp 32 ~ 104°F / 0 ~ 40°C Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Viewing Angle (L/R/T/B)	89/89/89/89 degrees
Operating Temp32 ~ 104°F / 0 ~ 40°CPower Requirements12VDC; 2A; Negative GroundPower Consumption30 Watts (Max)	3D Comb Filter	3D interlace & DNR, 4H filter
Power Requirements 12VDC; 2A; Negative Ground Power Consumption 30 Watts (Max)	Dimensions	8.8" x 7.7" x 1.85" / 223 x 196.4 x 47mm
Power Consumption 30 Watts (Max)	Operating Temp	32 ~ 104°F / 0 ~ 40°C
• • • • •	Power Requirements	12VDC; 2A; Negative Ground
Composite x1 BNC Input; x1 BNC Output	Power Consumption	30 Watts (Max)
	Composite	x1 BNC Input; x1 BNC Output
VGA x1 15-pin mini D-sub Input	VGA	x1 15-pin mini D-sub Input
HDMI x2 Inputs	HDMI	x2 Inputs
Power x1 2.1mm DC Input	Power	x1 2.1mm DC Input
Weight Net: 3.75 lbs / 1.7 kg; Gross: 5.5 lbs / 2.5 kg	Weight	Net: 3.75 lbs / 1.7 kg; Gross: 5.5 lbs / 2.5 kg

Specifications subject to change.