Non UL Listed Electric Strikes for light use with narrowline aluminum (excluding 11BS model) cylindrical locks up to 5/8" latch projection.

00

11BS

For Centerline Latch Entry

1-3/8" x 3-1/2" 34.9mm x 88.9mm

- (5/8" Latch Projection)
- Fail Locked
- 26D Brushed Chrome (Shown) / S4 Sprayed Brass Enamel
- For hollow metal or wood frames



15CA

For Centerline Latch Entry

1-1/4" x 5-7/8" 31.8mm x 149.2mm

- (5/8" Latch Projection)
- Fail Locked
- 28 Brushed Anodized Aluminum
- For hollow metal, aluminum or wood frames



15BS

For Special Offset Latch Entry

1-1/4" x 5-7/8" 31.8mm x 149.2mm

- (5/8" Latch Projection)
- Fail Locked
- 26D Brushed Chrome (Shown) / S4 Sprayed Brass Enamel
- For hollow metal, aluminum or wood frames
- Non-handed

Model	Description	Dimensions	Mode	Voltage	Finish	
11BS for Cente	rline Latch Entry (5/8" Latch P	rojection)				
11BS-01	HM/Wood Frames	1-3/8" x 3-1/2"	Fail Locked	11-16VAC	26D/S4	
11BS-05D	HM/Wood Frames	1-3/8" x 3-1/2"	Fail Locked	12VDC	26D/S4	
11BS-08D	HM/Wood Frames	1-3/8" x 3-1/2"	Fail Locked	24VDC	26D/S4	
11BS Strike Acc	essories:					
BXES1	Weldable Box (3-1/2"D x 1	Weldable Box (3-1/2"D x 1-9/16"W x 3-3/4"H)				
15BS for Specia	al Offset Latch Entry (5/8" Lato	th Projection)				
15BS-01	HM/Wood/Alum Frames	1-1/4" x 5-7/8"	Fail Locked	11-16VAC	26D/S4	
15CA for Cente	rline Latch Entry (5/8" Latch P	rojection)				
15CA-01	HM/Wood/Alum Frames	1-1/4" x 5-7/8"	Fail Locked	11-16VAC	28	