

Exit Devices

8800 Series Device with Trim



Program	Options	Functions	Rails	Escutcheon	Lever	Finishes
24-Hour	12, 43, 55, 56, KD	8813	F	ET, PSB, PTB	B, J, L, P, MD, ME, MG, MI, MJ, MV, ND, NJ, REM, 88CLL	32D
1-Week	12, 16, 43, 55, 56, 60, 70, HC, KD, LC, SC, WS*	8804, 8810, 8813, 8815, 8863, 8873*, 8874*, 8875*, 8876*	F, G, J			10B, 10BE, 32D
2-Week						03, 10, 10B, 10BE, 32D

Cylinder Options

- 60 Disposable Construction Core
- 70 Interchangeable Core Disposable Plug
- KD Keyed Different
- LC Less Cylinder
- SC Schlage "C" Keyway

Mechanical Options

- 12 Fire Rated
- 16 Cylinder Dogging
- 43 Flush End Cap
- 55 Request-to-Exit
- 56 Electric Latch Retraction (ELR)
- HC Hurricane Code
- WS** Windstorm

Finishes

- 03 Bright Brass
- 10 Dull Bronze
- 10B Oxidized Dull Bronze
- 10BE Dark Oxidized Satin Bronze - Equivalent
- 32D Dull Stainless

Functions

- 8804 (ANSI 03) Key Retracts Latch with PSB or ET Trim
- 8810 (ANSI 01) Exit Only, No Outside Trim
- 8810 (ANSI 02) Exit Only, with PTB or ET Trim
- 8813 (ANSI 08) Key Locks/Unlocks ET Trim
- 8815 (ANSI 14) Passage Only with ET Trim
- 8863 (ANSI 05) Key Locks/Unlocks PTB Thumb Piece
- 8973 Electrified ET Trim - Fail Safe, Power off, Unlocks Lever (No Cylinder)
- 8974 Electrified ET Trim - Fail Secure, Power off, Unlocks Lever (No Cylinder)
- 8975 Electrified ET Trim - Fail Safe. Power off, Unlocks Lever, Key retracts Latch
- 8976 Electrified ET Trim - Fail Secure. Power off, Unlocks Lever, Key retracts Latch

Rail

- F 33" - 36" (84cm - 91cm)
(No cutting required for 36" (91 cm) door)
- G 43" - 48" (110cm - 122cm)
(No cutting required for 48" (122 cm) door)
- J 37" - 42" (94cm - 107cm)
(No cutting required for 42" (107cm) door)

Hand

- LHR Left Hand Reverse
- RHR Right Hand Reverse

* Specify 12V or 24V when ordering solenoid operated ET Trim

** WS is available for single hollow metal door applications for 1-3/4" thick doors, 3'0" x 7'0" max doors.

