Description

The **IPPWR1** is a single channel, in-line, 10/100/1000 Ethernet surge protector for IP cameras. In addition to the network protection the IPPWR1 provides independent protection for 12 or 24 volt power which can be used with heaters, blowers or PTZ. The IPPWR1 is designed to provide surge protection for one 10/100/1000 Ethernet port. The unit has standard RJ45 jacks for easy connection and is ideal for small or restricted spaces. The IPPWR1 provides a heavy duty, single point ground connection and is easy to install in minutes.

Specifications

Size
Connection Network
Connection Power
Clamping
12/24VAC/DC
Data/PoE+ Ethernet
Transient Response Time
Peak Pulse Power Dissipation

Impedance

Temperature


Shipping Weight


0.9" H x 2.5" W x 1.8" D Standard RJ45 Push-in terminals - rate @ 5 amps

30 Vrms 58 Vp-p 1 picosecond typ. 3,000 W/pair (10/100us) 50 or 75 Ohms -40C to +85C 1 lb


Features

- Heavy duty single point ground
- 1 picosecond clamping time
- Lifetime warranty
- Separate power protection for 12 or 24 VAC/VDC
- Will pass PoE+ power

















5410 Newport Drive, # 24 Rolling Meadows, IL 60008 Phone: (847) 259-8900 Fax: (847) 259-1300 E-mail: info@nitek.net WWW.NITEK.NET EUROPE

De Schans 19-21 2a 8231 KA Lelystad Tel: +31(0)320-230005 E-mail: info@nitek.nl WWW NITEK NI