

Strobe Light & Wall Mount Kit

ELK-SL1

The ELK-SL1 is a weatherproof strobe light designed for easy attachment to ELK's stainless steel speaker and siren units. An optional wall kit (ELK-WK1) allows the strobe to be mounted to a wall or to single or double gang electrical boxes. The attractive SL1 features simple two-wire hookup, low current draw, and compatibility with virtually all 12 volt control panels (including pulsing alarm outputs). The ELK-SL1 is molded from virtually indestructible polycarbonate, such as Lexan, and is available in clear, amber, blue, and red.

Features

- Indoor / Outdoor.
- Durable Polycarbonate.
- Easy to Install: Simple 2 Wire Hookup.
- Works with pulsing alarm outputs.
- Lifetime Limited Warranty.

Specifications

- Operating Voltage: 12 Volts D.C.
- Current Draw: 210mA.
- Flash Rate: Approximately 1 Flash per second.
- Size: 4.875" x 3.875" x 1.125".
- Color: Clear, Red, Blue, Amber.
- Not Designed for Continuous Duty Applications



ELK-SL1 Strobe mounted to optional ELK-1RT

ELK-WK1

The ELK-WK1 is an optional wall mount kit for use with the ELK-SL1 Strobe Light. The kit features a decorative snap-on trim cover with all hardware for mounting the strobe to any flat surface or directly to a single or double gang electrical box.

Features

- Indoor / Outdoor.
- Durable ABS Plastic.
- Easy to Install.
- Size: 5.125" x 2.625" x 1.375".
- Color: White.



ELK-WK1 Trim Cover mounted on optional ELK-SL1