



8501HIM

SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP H264 SYST.



The kit consists of 1 colour audio/video unit art. 4682HKC, 1 module with 1 button art. 33411M, 1 flush-mounted box art. 3110/1, 1 frame complete with finishing frame art. 3311/1S, 1 power supply unit art. 1595 and 1 PC Intercom software art. 1454K. The kit is pre-programmed and ready to use. The kit can be expanded with other products from the ViP catalogue. Compatible with H.264 video format.

AWARDS

DESIGN
MILANO



8501HIM

**SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM ViP
H264 SYST.**



4894HIM External unit for ViP kit - Ikall Metal H264

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/15, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKD. The external unit is coded with ViP address 100 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H264 video format

GENERAL DATA

Flush-mounted

Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°F) (°C)

-13 ÷ 131



8501HIM

**SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP
H264 SYST.**

1454K LOCAL PC DOOR ENTRY MONITOR SOFTWARE VIP



Software on USB stick that allows a PC to be used for answering calls like a door entry monitor. Pre-set for operation with the single-family VIP KIT Art. 8501. For installation and use on a PC wired directly to the system.

MAIN FUNCTIONS	
Self Activation	Yes
GENERAL FEATURES	
Switchboard call function	Yes
Privacy function	Yes
MAIN FEATURES	
Height (inch) (pc)	9.45
Width (inch) (pc)	20.55
Depth (inch) (pc)	13.46
Product weight (oz) (oz)	0.88
SOFTWARE/FIRMWARE SPECIFICATIONS	
IP assignment	AUTO IP, DHCP, STATIC
GENERAL DATA	
ViP	Yes
Door opener	Yes
FUNCTIONS	
Alarm function	Yes
Actuator control function	Yes
Intercom function	Yes
Key button function	Yes



8501HIM

**SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP
H264 SYST.**

Vip system	Yes
AUDIO/VIDEO FEATURES	
Audio/video system	Yes
CONNECTIVITY	
Type of connections/ports	1xUSB 2.0



8501HIM

**SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP
H264 SYST.**



1595 120-230VAC / 33VDC POWER SUPPLY UNIT

Power supply unit with input of 120÷230VAC, 33VDC output with 500mA continuous and 1.2A inrush current for video door entry panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).

MAIN FEATURES	
Supply voltage	120÷230 VAC
Output supply voltage	33VDC
Max. current delivered (A)	0.5
Maximum inrush current (A)	1.2
Applicable to DIN rail	Yes
Number of DIN modules (n°)	4

GENERAL DATA	
Height (inch) (pc)	14.65
Width (inch) (pc)	16.94
Depth (inch) (pc)	21.26
Type of finishing materials	Plastic
Product color	White
Operating temperature (°F) (°F)	-4 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 95

COMPATIBILITY	
Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes



8501HIM

**SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP
H264 SYST.**

Maximum power delivered (W)

60

**8501HIM**

SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP H264 SYST.



4682HKDE HD A/V UNIT FOR ADDITIONAL KIT ENTRANCE PANEL. VIP

ViP system audio/video unit complete with colour video camera. Maximum resolution 1280x720 pixels. Recording angle 110° (H) - 80° (V). LED camera lighting. Complete with terminal block and digital audio management system with Echo-cancellation, watertight loudspeaker and electret microphone; loudspeaker volume can be adjusted via software programming. Programmable audiovisual functions for users with disabilities. Standard POE audio/video unit but if necessary 33 Vdc power supply can be used via Art. 1595. Compatible with H.264 video format. Audio/video unit pre-programmed with ViP address 101 and call button with ViP address 1. Dimensions (W x H x D): 102x55x38 mm.



4682HKD HD COLOR A/V UNIT FOR IKALL KIT. VIP

ViP system audio/video unit complete with colour video camera. Maximum resolution 1280x720 pixels. Recording angle 110° (H) - 80° (V). LED camera lighting. Complete with terminal block and digital audio management system with Echo-cancellation, watertight loudspeaker and electret microphone; loudspeaker volume can be adjusted via software programming. Programmable audiovisual functions for users with disabilities. Standard POE audio/video unit but if necessary 33 Vdc power supply can be used via Art. 1595. Compatible with H.264 video format. Audio/video unit pre-programmed with ViP address 100 and call button with ViP address 1. Dimensions (W x H x D): 102x55x38 mm.



8501HIM

**SING.-FAMILY KIT W/ IKALL METAL & PC INTERCOM VIP
H264 SYST.**



4895HIM

ADDIT. EXT. UNIT FOR VIP KIT - IKALL METAL. H264

Single-family video door entry external unit for ViP system with Icall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKE. The external unit is coded with ViP address 101 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H.264 video format.