

**KVV8111****VISTO VIP KIT WITH POWER SUPPLY UNIT**

Single-family kit with smart Wi-Fi doorbell complete with power supply unit. After connecting to the Wi-Fi network, you will be able to receive calls straight to your smartphone and tablet using the Comelit app. With the Comelit app you will always be in touch with what's happening at home, whether you are out and about in town or even in another country. The Kit consists of 1 Visto ViP Wi-Fi external unit art. VS8111 and 1 power supply unit art. 1595.



**KVV8111**

## VISTO VIP KIT WITH POWER SUPPLY UNIT

### PRODUCTS IN THE KIT



#### **VS8111 VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM**

Wi-Fi video entry external unit for use in Comelit ViP systems, complete with adapter allowing use of the power supply for the existing bell (12-20 VAC or 12-33 VDC) and allowing interfacing with the existing bell. Depending on the system configuration, you can receive video entry phone calls on ViP monitors or directly on smartphones and tablets via the Comelit app. With the Comelit app, you are always in touch with what is going on at your home, whether you are in town or even in another country.

GENERAL DATA	
Type	Monoblock
Height (mm)	136
Width (mm)	47
Depth (mm)	32
Product color	Dark Graphite RAL9011
Wall-mounted	Yes
COMPATIBLE SYSTEMS	
ViP	Yes
AUDIO FEATURES	
Technologies implemented	Full-Duplex, Echo canceling, Noise reduction
CAMERA FEATURES	
Camera	Colours
Sensor type	1/4" CMOS
Lens optical dimensions (mm)	1.6
Angle of view (H x V - °)	170 (diagonal)
Sensitivity	2
Video compression	H.264



**KVV8111**

## VISTO VIP KIT WITH POWER SUPPLY UNIT

### ELECTRICAL CHARACTERISTICS

Type of power supply	External power supply
Supply voltage	12 ÷ 33 VDC
Maximum absorption (W)	6

### HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	1
Clamps	+ - NO C
Removable terminals	Yes
Number of outputs (n°)	1
Type of outputs	Relay (C-NO, 1A@30VDC)

### NETWORK AND COMMUNICATION PROTOCOLS

Type of Wi-Fi connection	2.4 GHz
IP address assignment	DHCP, AUTO IP, static IP

### PROGRAMMING MODE

ViP Manager software	Yes
----------------------	-----

### ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	0 ÷ 75
Environmental class	III
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), RED 2014/53/UE (EN 62311:2008, EN 62368-1:2014, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)

### MAIN FUNCTIONS



**KVV8111**

## VISTO VIP KIT WITH POWER SUPPLY UNIT

Visual indications of system status

Yes



**KVV8111**

## VISTO VIP KIT WITH POWER SUPPLY UNIT



### **1595 100-240VAC / 33VDC POWER SUPPLY UNIT**

Power supply unit with input of 100÷240VAC/50÷60Hz, 33VDC output with 500mA continuous and 1.2A inrush current for video door entry panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).

MAIN FEATURES	
Supply voltage	100÷240
Output supply voltage	33VDC
Max. current delivered (A)	0.5
Maximum inrush current (A)	1.2
Input connector	Terminal block
Applicable to DIN rail	Yes
Number of DIN modules (n°)	4

HARDWARE SPECIFICATIONS	
Product weight (g)	220

GENERAL DATA	
Height (mm)	62
Width (mm)	72
Depth (mm)	90
Type of finishing materials	Plastic
Product color	White RAL9010
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95

COMPATIBILITY	
Simplebus 2 audio/video system	Yes
Simplebus 2 audio system	Yes



**KVV8111**

## VISTO VIP KIT WITH POWER SUPPLY UNIT

### COMPATIBILITY

Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes

### ELECTRICAL SPECIFICATIONS

Maximum power delivered (W)	14
-----------------------------	----