

AXIS TU6007-E Cable

Indoor and outdoor rated cable for 2nd generation AXIS F-series modular cameras

Designed for use with 2nd generation AXIS F Series modular cameras, this flexible indoor/outdoor cable has a bending radius of 30 mm (1.2 in). Compatible with AXIS F91 main units and AXIS F21, AXIS F72, and AXIS F41 sensor units. It's available in 2 different lengths: 1 m (3 ft) and 8 m (26 ft).

- > **Only compatible with 2nd generation main units and sensors**
- > **Indoor and outdoor rated**
- > **30 mm (1.2 in) bending radius**
- > **IP66-, IP67-rated (SMA side)**
- > **1 m (3 ft), 8 m (26 ft)**



AXIS TU6007-E Cable

General	
Environment	SMA connector: IP66- and IP67-rated
Power	Impedance: 50 Ohms
Frequency	0-3 GHz
Connectors	SMA FAKRA
Operating conditions	-40 °C to 75 °C (-40 °F to 167 °F) Humidity 10-100% RH (condensing)
Approvals	UL CM E164469-F5, UN ECE R118

Dimensions	Color: black Length: 1 m (3 ft) and 8 m (26 ft) ø 3 ±0.2 mm (0.1 in) Bend radius: 30 mm (1.2 in)
Weight	1 m (3 ft): 22 g (0.05 lb) 8 m (26 ft): 124 g (0.27 lb)
Compatible products	AXIS F91 main units, AXIS F21 sensor units, AXIS F4105-LRE Dome Sensor, AXIS F7225-RE Pinhole Sensor
Warranty	3-year warranty, see axis.com/warranty