

PAGE 1 OF 14

Camera - Network	QND-8020R	5MP Indoor IR Dome		Wienernet Q network indoor dome camera, 5MP @ 30fps, 4.0mm fixed focal lens (7°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8030R	5MP Indoor IR Dome		Wienernet Q network indoor dome camera, 5MP @ 30fps, 6.0mm fixed focal lens (48°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8060R	5MP Indoor IR Dome		Wienernet Q network indoor dome camera, 5MP @ 30fps, motorized varifocal lens 3.1x (3.2 – 10.0mm) (109°-33.2°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, SD card, video analytics, CVBS, open platform, PoE, white color
Camera - Network	QND-8011	5MP Indoor Dome		Wienernet Q mini network indoor dome camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color
Camera - Network	QND-8021	5MP Indoor Dome		Wienernet Q mini network indoor dome camera, 5MP @ 30fps, 4.0mm fixed focal lens (80°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, IK08, PoE, white color
Camera - Network	QNE-8011R	5MP IR Outdoor Flat-Eye		Wienernet Q mini network outdoor flat-eye camera, 5MP @ 30fps, 2.8mm fixed focal lens (104°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, open platform, IP67, IK10, PoE, white color
Camera - Network	QNE-8021R	5MP IR Outdoor Flat-Eye	Limited Stock Comparable Model QNE-8011R	Wienernet Q mini network outdoor flat-eye camera, 5MP @ 30fps, 4.0mm fixed focal lens (80°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, SD card, video analytics, open platform, IP67, IK10, PoE, white color
Camera - Network	QNF-8010	6MP Indoor fisheye		Wienernet Q series network indoor fisheye dome camera, 6MP CMOS sensor, max resolution 2048x2048 @ 30fps, triple code: H.265H.264MPEG with WiStream II technology, WDR 120dB, business analytics (heatmap and people counting), built-in SD card slot, PoE
Camera - Network	TNW-8011C	5MP Compact corner mount camera		Compact corner mount camera, 5MP @ 30fps, triple code: WDR 120dB, 2.3mm fixed, USB and CVBS, true DNR, SD cards slots, hallway view, HLC, defog detection, PoE, Auto-Infrared-out, Wiener net platform IP68, IP69K, IK10, Video analytics, Defocus, Detection, Motion, Enter/Exit, Tampering, Virtual line, Audio
4MP Cameras				
Camera - Network	QND-7012R	4MP IR Dome		Wienernet Q network indoor dome camera, 4MP @ 30fps, 2.8mm fixed focal lens (107°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB) PoE/12VDC, white color
Camera - Network	QND-7022R	4MP IR Dome		Wienernet Q network indoor dome camera, 4MP @ 30fps, 4mm fixed focal lens (78°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB) PoE/12VDC, white color
Camera - Network	QND-7032R	4MP IR Dome		Wienernet Q network indoor dome camera, 4MP @ 30fps, 6mm fixed focal lens (48°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB) PoE/12VDC, white color
Camera - Network	QND-7082R	4MP IR Dome		Wienernet Q network indoor dome camera, 4MP @ 30fps, motorized varifocal lens 3.1x (3.2 – 10.0mm) (109°-33.2°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 20m (65.62'), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, Built-in Line in, Micro SD/SDHC/SDXC card 1 slot (Max. 128GB), PoE/12VDC (White color)
Camera - Network	QNV-7012R	4MP IR Vandal Dome		Wienernet Q network outdoor vandal dome camera, 4MP @ 30fps, 2.8mm fixed focal lens (107°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB), IP68, IK10, PoE/12VDC, white color
Camera - Network	QNV-7022R	4MP IR Vandal Dome		Wienernet Q network outdoor vandal dome camera, 4MP @ 30fps, 4mm fixed focal lens (78°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB), IP68, IK10, PoE/12VDC, white color
Camera - Network	QNV-7032R	4MP IR Vandal Dome		Wienernet Q network outdoor vandal dome camera, 4MP @ 30fps, 6mm fixed focal lens (48°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB), IP68, IK10, PoE/12VDC, white color
Camera - Network	QNV-7082R	4MP IR Vandal Dome		Wienernet Q network outdoor vandal dome camera, 4MP @ 30fps, motorized varifocal lens 3.1x (3.2 – 10.0mm) (109°-33.2°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 30m (98.42'), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, One way audio - Line in, Micro SD/SDHC/SDXC card 1 slot (Max. 128GB), IP68, IK10, PoE/12VDC (White color)
Camera - Network	QNO-7012R	4MP IR Bullet		Wienernet Q network outdoor vandal bullet camera, 4MP @ 30fps, 2.8mm fixed focal lens (107°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB), IP68, IK10, PoE/12VDC
Camera - Network	QNO-7022R	4MP IR Bullet		Wienernet Q network outdoor vandal bullet camera, 4MP @ 30fps, 4mm fixed focal lens (78°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 65', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB), IP68, IK10, PoE/12VDC
Camera - Network	QNO-7032R	4MP IR Bullet		Wienernet Q network outdoor vandal bullet camera, 4MP @ 30fps, 6mm fixed focal lens (48°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 98', motion detection, tampering, defocus detection, hallway View, one way audio and SD card (max. 128GB), IP68, IK10, PoE/12VDC
Camera - Network	QNO-7082R	4MP IR Bullet		Wienernet Q network outdoor vandal bullet camera, 4MP @ 30fps, motorized varifocal lens 3.1x (3.2 – 10.0mm) (109°-33.2°), triple code: H.265H.264MPEG with WiStream II, 120dB WDR, IR LEDs range 30m (98.42'), Motion detection, Tampering, Defocus detection, Hallway view, LDC support, One way audio - Line in, Micro SD/SDHC/SDXC card 1 slot (Max. 128GB), IP68, IK10, PoE/12VDC (White color)
Camera - Network	XND-C7089RV	4MP IR Indoor Vandal Dome AI Camera		Powered by WIN7, Indoor Network AI IR Dome Camera, 4MP resolution @ 60FPS (WDR off)/30FPS (WDR on), 2.8-12mm(4.3x) (109°-33.2°) motorized varifocal lens, Triple code (H.265H.264MPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coded dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events - Defocus detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP68, IK08, Operating temperature: -10 °C ~ 50 °C(14°F ~ +122°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNV-C7089R	4MP IR Outdoor Vandal Dome AI Camera		Powered by WIN7, Outdoor Network AI IR Vandal Dome Camera, 4MP resolution @ 60FPS (WDR off)/30FPS (WDR on), 2.8-12mm(4.3x) (109°-33.2°) motorized varifocal lens, Triple code (H.265H.264MPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coded dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events - Defocus detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP68, IP67, NEMAX, IK10, Operating temperature: -40°C~+50°C(4°F ~ +131°F), Power: PoE+12VDC, Metal shielded RJ-45
3MP Cameras				
Camera - Network	TNW-7011RC	3MP IR Vandal Corner Camera		Powered by Wienernet 3 network indoor corner mount camera, 3MP, 2048*1536 @ 30fps, 2.8mm fixed lens (102°-75°), 540mm IR 32', built-in mic, triple code: H.265H.264MPEG with WiStream II technology, 120dB WDR, advanced video analytics and business analytics, single SD card, HLC, defog detection, DIS, PoE, IP68 Nema 4X, IK10
2MP Cameras				
Camera - Network	PND-A00819F	2MP IR Indoor Flush Mount Dome AI Camera		2MP Network AI IR Dome Camera, Max. 2MP resolution, Up to 120fps, 0.00/Lux@F1.3 (Color), Lux@ (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wide IR, Day & Night (ICR), WDR (120dB), WienerNet (Using AI engine), H.265, H.264, MPPEG, WiStreamII, Face mask detection, Social distancing detection, Attribute, BestShot/People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 Iweel, Secure boot, Verify firmware loggery, Hard-coated dome bubble, IP52, IK10, Modular structure for easy install, PoE+
Camera - Network	PND-A00819V	2MP IR Indoor Vandal Dome AI Camera		2MP Network AI IR Dome Camera, Max. 2MP resolution, Up to 120fps, 0.00/Lux@F1.3 (Color), Lux@ (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wide IR, Day & Night (ICR), WDR (120dB), WienerNet (Using AI engine), H.265, H.264, MPPEG, WiStreamII, Face mask detection, Social distancing detection, Attribute, BestShot/People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 Iweel, Secure boot, Verify firmware loggery, Hard-coated dome bubble, IP52, IK10, Modular structure for easy install, PoE+
Camera - Network	PNV-A00819R	2MP IR Outdoor Vandal Dome AI Camera		2MP Network AI IR Vandal Dome Camera, Max. 2MP resolution, Up to 120fps, 0.00/Lux@F1.3 (Color), Lux@ (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wide IR, Day & Night (ICR), WDR (120dB), WienerNet (Using AI engine), H.265, H.264, MPPEG, WiStreamII, Face mask detection, Social distancing detection, Attribute, BestShot/People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 Iweel, Secure boot, Verify firmware loggery, Hard-coated dome bubble, IP68, IP67, IP69K, IK10+, NEMAX, Modular structure for easy install, PoE+
Camera - Network	PND-A00819B	2MP IR Bullet AI camera		2MP Network AI IR Bullet Camera, Max. 2MP resolution, Up to 120fps, 0.00/Lux@F1.3 (Color), Lux@ (B/W, IR LED on), IR Viewable Length 40m(131.23ft), Wide IR, Day & Night (ICR), WDR (120dB), WienerNet (Using AI engine), H.265, H.264, MPPEG, WiStreamII, Face mask detection, Social distancing detection, Attribute, BestShot/People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 Iweel, Secure boot, Verify firmware loggery, Hard-coated dome bubble, IP68, IP67, IK10, NEMAX, PoE+
Camera - Network	PNB-A0001	2MP Box AI camera		2MP Network AI Box Camera, Max. 2MP resolution, Up to 120fps, 0.00/Lux@F1.2 (Color), Lux@ (B/W, IR LED on), Day & Night (ICR), WienerNet (Using AI engine), Video Analytics based on AI (Object detection and classification (Person, Face, Vehicle, License Plate), Face mask detection, Social distancing detection, Attribute, BestShot/People counting, Heatmap, Queue management based on AI, TPM with FPS 140-2 Iweel, Secure boot, Verify firmware loggery, Hard-coated dome bubble, IP68, IP67, NEMAX, IK10, Operating temperature: -40°C~+50°C(4°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XND-C0083RV	2MP IR Indoor Vandal Dome AI Camera		Powered by WIN7, Indoor Network AI IR Dome Camera, 2MP resolution @ 60FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple code (H.265H.264MPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coded dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events - Defocus detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP68, IK08, Operating temperature: -10 °C ~ 50 °C(14°F ~ +122°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XNV-C0083R	2MP IR Outdoor Vandal Dome AI Camera		Powered by WIN7, Outdoor Network AI IR Vandal Dome Camera, 2MP resolution @ 60FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple code (H.265H.264MPEG), IR viewable length 40m (131.2ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coded dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events - Defocus detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, IP68, IP67, NEMAX, IK10, Operating temperature: -40°C~+50°C(4°F ~ +131°F), Power: PoE/12VDC, Metal shielded RJ-45
Camera - Network	XND-0083RV	2MP IR Indoor Vandal Dome AI Camera		Powered by WIN7, X-Plus series, Indoor Network AI IR Dome Camera, 2MP resolution @ 120FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple code (H.265H.264MPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coded dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events - Defocus detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FPS 140-2, 2x micro SD card (512GB x2), IP68, IP67, NEMAX, IK10+, Operating temperature: -40°C~+50°C(4°F ~ +131°F), Power: PoE+12VDC, Metal shielded RJ-45
Camera - Network	XNV-0083R	2MP IR Outdoor Vandal Dome AI Camera		Powered by WIN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 2MP resolution @ 120FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple code (H.265H.264MPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coded dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events - Defocus detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FPS 140-2, 2x micro SD card (512GB x2), IP68, IP67, NEMAX, IK10+, Operating temperature: -40°C~+50°C(4°F ~ +131°F), Power: PoE+12VDC, Metal shielded RJ-45
Camera - Network	XNV-0083R	2MP IR Outdoor Vandal Dome AI Camera		Powered by WIN7, X-Plus series, Outdoor Network AI IR Vandal Dome Camera, 2MP resolution @ 120FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, Triple code (H.265H.264MPEG), IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Hard-coded dome bubble, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events - Defocus detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FPS 140-2, 2x micro SD card (512GB x2), IP68, IP67, NEMAX, IK10+, Operating temperature: -40°C~+50°C(4°F ~ +131°F), Power: PoE+12VDC, Metal shielded RJ-45
Camera - Network	XNB-0003	2MP Box AI Camera		Powered by WIN7, X-Plus series, Box Camera, 2MP resolution @ 120FPS, Triple code (H.265H.264MPEG), USB port for easy installation, Day & Night (ICR), extremeWDR (150dB), DIS with built-in Gyro sensor, Handover, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line/Area, Enter/Exit, Loitering, direction, intrusion), Analytics events - Defocus detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Appear/Disappear, FPS 140-2, 2x micro SD card (512GB x2), IP68, IP67, NEMAX, IK10+, Operating temperature: -40°C~+50°C(4°F ~ +131°F), Power: PoE+12VDC, Metal shielded RJ-45
Camera - Network	XNP-6400RW	2MP IR, Wiper PTZ		Powered by WIN7, 2MP @ 60FPS resolution, 4.25mm~170mm (40x) lens, Wide IR (200m), extreme WDR 150dB, Day & Night ICR, H.265, H.264, MPPEG code support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/now removal, IP68, IK10(Camera body only), NEMAX, HP-e injector included, Compatible with IO Box (SPM-4210)
Camera - Network	XNP-6400R	2MP, 40x, IR PTZ camera		Powered by WIN7, 2MP @ 60FPS resolution, 4.25mm~170mm (40x) lens, Wide IR (200m), extreme WDR 150dB, Day & Night ICR, H.265, H.264, MPPEG code support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/now removal, IP68, IK10, NEMAX, NEMA 7S (2.2/2.8/2.8), HP-e injector included, Compatible with IO Box (SPM-4210)
Camera - Network	XNP-6400	2MP, 40x PTZ camera		Powered by WIN7, 2MP @ 60FPS resolution, 4.25mm~170mm (40x) lens, extreme WDR 150dB, Day & Night ICR, H.265, H.264, MPPEG code support, Intelligent Analytics, Object auto tracking(Person/Vehicle), Target lock track, BLC, HLC, SSDR, lens heater for water/now removal, IP68, IK10, NEMAX, NEMA 7S (2.2/2.8/2.8), HP-e injector included, Compatible with IO Box (SPM-4210)
Camera - Network	XND-00819EV	2MP Indoor Dome, PoE extender camera	POE+ Required	Wienernet X powered by Wienernet 5 network indoor dome camera with PoE Extender, PoE+ @ 15W, 60FPS, Motorized Varifocal Lens (2.8mm~12mm), triple code H.265H.264MPEG with WiStream II technology WDR 150dB, USB port for easy installation, motion detection and sound classification, true DIN, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE+@15W, IP52, IK10, -25°C ~ +40°C (-13°F ~ +104°F)
Camera - Network	XNV-00819E	2MP Outdoor Dome, PoE extender camera	POE+ Required	Wienernet X powered by Wienernet 5 network outdoor vandal dome camera with PoE Extender, PoE+ @ 15W, 60FPS, Motorized Varifocal Lens (2.8mm~12mm), triple code H.265H.264MPEG with WiStream II technology WDR 150dB, USB port for easy installation, advanced video analytics and sound classification, true DIN, dual SD card, hallway view, HLC, defog detection, DIS(Gyro), PoE+@15W, IP52/IP68/IP69K, IK10+, NEMAX, -25°C ~ +40°C (-13°F ~ +104°F)
Camera - Network	XNV-0081R	2MP IR Outdoor Dome		Wienernet X series Plus powered by Wienernet 5 IR network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264MPEG with WiStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true DIN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP68/IP69K, IK10+, Nema 4X, -40°C ~ +40°C (-40°F ~ +104°F), white color, very skin included, optional blank skin cover
Camera - Network	XND-00819F	2MP IR Flush Mount Dome		Wienernet X series Plus powered by Wienernet 5 IR network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264MPEG with WiStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, true DIN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing
Camera - Network	XND-0081RV	2MP IR Indoor Dome		Wienernet X series Plus powered by Wienernet 5 IR network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264MPEG with WiStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, high powered IR LEDs range of 164', shock detection, audio playback, built-in mic, true DIN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, very skin included, optional blank skin cover
Camera - Network	XNV-0081	2MP Outdoor Dome		Wienernet X series Plus powered by Wienernet 5 network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264MPEG with WiStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DIN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP68/IP69K, IK10+, Nema 4X, -40°C ~ +40°C (-40°F ~ +104°F), white color, very skin included, optional blank skin cover
Camera - Network	XND-0081F	2MP Flush Mount Dome	Limited Stock	Wienernet X series Plus powered by Wienernet 5 network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264MPEG with WiStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DIN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, plenum housing
Camera - Network	XND-0081V	2MP Indoor Vandal Dome		Wienernet X series Plus powered by Wienernet 5 network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code: H.265H.264MPEG with WiStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true DIN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, very skin included, optional blank skin cover
Camera - Network	XNV-0081Z	2MP Outdoor PTRZ Dome		Wienernet X series Plus powered by Wienernet 5 network outdoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), PTRZ, triple code: H.265H.264MPEG with WiStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, true DIN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, optional 24VAC, IP67/IP68/IP69K, IK10+, Nema 4X, -40°C ~ +40°C (-40°F ~ +104°F), white color, very skin included, optional blank skin cover
Camera - Network	XND-0081VZ	2MP Indoor PTRZ Dome		Wienernet X series Plus powered by Wienernet 5 network indoor vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), PTRZ, triple code: H.265H.264MPEG with WiStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, sound classification and business analytics, shock detection, audio playback, built-in mic, true DIN, dual SD card, hallway view, HLC, defog detection, DIS (Gyro), 12VDC/PoE, IP52, IK10, white color, very skin included, optional blank skin cover

Camera - Network	XND-6081FZ	2MP Flush Mount PTIRZ Dome		Wiener X series Plus powered by Wisenet 5 network indoor flush mount vandal dome camera, modular structure, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119°-27.9°), PTIRZ, triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDCPoE, IP62, plenum housing
Camera - Network	XNP-6559RH	2MP IR 55x PTZ		Wiener X powered by Wiener 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.4mm ~ 142.6mm) (81.8° ~ 2.19°), Pan: 360° endless, Tilt: 0° ~ 180°, triple code H.265H.264/MP4EG with WiseStream II technology, 120dB WDR, built-in IR 160dB (500m), USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDCPoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F) W/24VAC power supply
Camera - Network	XNP-6305RH	2MP IR 32x PTZ	Limited Stock Comparable model XNP-6405R	Wiener X powered by Wiener 5 network IR PTZ camera, IR range up to 650', 2MP, Full HD(1080p) @ 60fps, triple code H.265H.264/MP4EG, 32x optical zoom lens (4.4mm ~ 142.6mm) (81.8° ~ 2.19°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, auto tracking, true DN, dual SD card, HLC, defog detection, DIS(Gym), IP66/IK10, 24VDCPoE
Camera - Network	XNP-6305HS	2MP 32x Stainless steel PTZ	Limited Stock	Wiener X powered by Wiener 5 network stainless steel PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.4mm ~ 142.6mm) (81.8° ~ 2.19°), Pan: 360° endless, Tilt: 0° ~ 180°, triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDCPoE, IP66/IK10, -58°F ~ +131°F W/24VAC power supply
Camera - Network	XNP-6320H	2MP 32X PTZ	Limited Stock	Wiener X powered by Wiener 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.4mm ~ 142.6mm) (81.8° ~ 2.19°), Pan: 360° endless, Tilt: 0° ~ 180°, triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDC24VACPoE, IP66/IK10, -58°F ~ +131°F W/24VAC power supply
Camera - Network	XNP-6320	2MP 32X PTZ	Limited Stock Comparable model XNP-6400	Wiener X powered by Wiener 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.4mm ~ 142.6mm) (81.8° ~ 2.19°), Pan: 360° endless, Tilt: 0° ~ 180°, triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDCPoE, IP66/IK10, -58°F ~ +131°F W/24VAC power supply
Camera - Network	XNP-6321H	2MP 32x PTZ Outdoor	Limited Stock Comparable model XNP-6400	Wiener X powered by Wiener 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.4mm ~ 142.6mm) (81.8° ~ 2.19°), Pan: 360° endless, Tilt: 0° ~ 180°, triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDC24VACPoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNP-6321	2MP 32x PTZ Indoor	Limited Stock Comparable model XNP-6400	Wiener X powered by Wiener 5 network indoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.4mm ~ 142.6mm) (81.8° ~ 2.19°), Pan: 360° endless, Tilt: 0° ~ 180°, triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, Auto Tracking, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDCPoE, IP66/IK10, -58°F ~ +131°F W/24VAC power supply
Camera - Network	XNP-6120H	2MP 12X PTZ		Wiener X powered by Wiener 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 12X optical zoom lens (5.2mm ~ 42.4mm) (54.58° ~ 5.30°), Pan: 360° endless, Tilt: 0° ~ 180°, triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDCPoE, IP66, IK10, 22°F ~ +131°F
Camera - Network	XNP-6040H	2MP 4.3X PTZ		Wiener X powered by Wiener 5 network outdoor PTZ camera, 2MP, Full HD(1080p) @ 60fps, 4.3X optical zoom lens (2.8mm ~ 12mm) (119.9° ~ 27.9°), Pan: 0°~360°, Tilt: 0°~90°, triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDCPoE, IP66, IK10, 22°F ~ +131°F
Camera - Network	XND-6085R	eXtraLUX IR Bullet		Wiener X powered by Wiener 5 network IR outdoor vandal bullet camera, eXtraLUX features 12" sensor with F0.94 Lens, PTIR, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.0x (4.1~16.4mm) (100°~26.2°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDC24VACPoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNV-6085	eXtraLUX Outdoor PTIRZ Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, eXtraLUX features 12" sensor with F0.94 Lens, PTIR, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.0x (4.1~16.4mm) (100°~26.2°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDC24VACPoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XND-6085V	eXtraLUX Indoor PTIRZ Dome	Limited Stock Comparable model XNV-6085	Wiener X powered by Wiener 5 network indoor vandal dome camera, eXtraLUX features 12" sensor with F0.94 Lens, PTIR, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.0x (4.1~16.4mm) (100°~26.2°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDCPoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNB-6005	eXtraLUX Box Camera		Wiener X powered by Wiener 5 network box camera, eXtraLUX features 12" sensor, 2MP, Full HD(1080p) @ 60fps, triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDC24VACPoE
Camera - Network	XNV-6120R	2M 12X IR outdoor Dome		Wiener X powered by Wiener 5 network IR outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 12X optical zoom lens (5.2mm ~ 42.4mm) (54.58° ~ 5.30°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDC24VACPoE, IP67, IK10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNV-6120RLPR	Low Speed LPR Outdoor IR Dome	1 week Lead time	Wiener X powered by Wiener 5 network IR outdoor Low Speed LPR bullet camera for Parking Lots, Drive-Thrus, and Entry Gates up to 35MPH, 2MP, Full HD(1080p) @ 60fps, 12X optical zoom lens (5.2mm ~ 42.4mm) (54.58° ~ 5.30°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, backbox included, 12VDC24VACPoE, IP67, K10, NEMAAX, -40°C ~ +55°C (40°F ~ +131°F)
CARE IS RECOMMENDED IN SELECTING MOUNTING LOCATION - See Quick Start Guide Step 1. DEALER TRAINING OR HANNA ENGINEERING CONSULT RECOMMENDED BEFORE INSTALLATION				
Camera - Network	XNV-6120	2M 12X Outdoor Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 12X optical zoom lens (5.2mm ~ 42.4mm) (54.58° ~ 5.30°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDC24VACPoE, IP67, K10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XND-6120R	2M 12X IR Bullet		Wiener X powered by Wiener 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @ 60fps, 12X optical zoom lens (5.2mm ~ 42.4mm) (54.58° ~ 5.30°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 229', true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDC24VACPoE, IP67, K10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XND-6120RLPR	Low Speed LPR IR Bullet	1 week Lead time	Wiener X powered by Wiener 5 network IR outdoor Low Speed LPR bullet camera for Parking Lots, Drive-Thrus, and Entry Gates up to 35MPH, 2MP, Full HD(1080p) @ 60fps, 12X optical zoom lens (5.2mm ~ 42.4mm) (54.58° ~ 5.30°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, backbox included, 12VDC24VACPoE, IP67, K10, NEMAAX, -40°C ~ +55°C (40°F ~ +131°F)
CARE IS RECOMMENDED IN SELECTING MOUNTING LOCATION - See Quick Start Guide Step 1. DEALER TRAINING OR HANNA ENGINEERING CONSULT RECOMMENDED BEFORE INSTALLATION				
Camera - Network	XND-6085RSA	2MP Stainless Steel IR Dome	POKOK	Wiener X powered by Wiener 5 network IR stainless steel outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true DN, dual SD card, HLC, defog detection, DIS, 12VDC24VACPoE, IP67, K10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNV-6080R	2MP IR Outdoor Dome		Wiener X powered by Wiener 5 network IR outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true DN, dual SD card, HLC, defog detection, DIS, 12VDC24VACPoE, IP67, K10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNV-6080	2MP Outdoor Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS, 12VDC24VACPoE, IP67, K10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNV-6010	2MP Outdoor Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 4mm fixed focal lens (139'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DN, dual SD card, HLC, defog detection, DIS, 12VDCPoE, IP67, K10
Camera - Network	XNV-6020R	2MP IR Outdoor Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 4mm fixed lens (88.6'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DN, dual SD card, HLC, defog detection, DIS, 12VDCPoE, IP67, K10
Camera - Network	XNV-6011	2MP Compact Vandal Dome		Wiener X powered by Wiener 5 network outdoor compact vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 2.8mm fixed lens (112'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and business analytics, single SD card, HLC, defog detection, DIS, PoE, IP66, Nema 4X, K10
Camera - Network	XNV-6011W	2MP Compact Vandal Dome (White Color)		Wiener X powered by Wiener 5 network outdoor compact vandal dome camera (white color), 2MP, Full HD(1080p) @ 60fps, 2.8mm fixed lens (112'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and business analytics, single SD card, HLC, defog detection, DIS, PoE, IP66, Nema 4X, K10, white color
Camera - Network	XND-6083R	2MP IR Bullet AI Camera		Powered by WINN X-Plus series, Outdoor Network AI IR Bullet Camera, 2MP @ 120FPS, 2.8-12mm(4.3x) (119.5°-27.9°) motorized varifocal lens, H.265H.264/MP4EG, IR viewable length 50m (164ft), USB port for easy installation, Day & Night (ICR), IntermittentWDR (150dB), DIS built-in Gyr sensor, Handover, Hard-coded window, Analytics events based on AI engine: Object detection(Person/Face/Vehicle/License plate), IVA (Virtual line Area, Enter/Exit, Loitering, direction, intrusion), Analytics events: Defocus detection, Motion detection, Tampering, Fog detection, Audio detection, Sound classification, Shock detection, Apparatus/Disappear, FPS H.265, 2 mms SD card (120GB), PoE, IP67, NEMA4, K10, Operating temperature: -30°C/(-58°F) ~ +40°F, Power: PoE/12VDC, Metal angled RJ45
Camera - Network	XND-6080R	2MP IR Bullet		Wiener X powered by Wiener 5 network IR outdoor vandal bullet camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 164', true DN, dual SD card, HLC, defog detection, DIS, 12VDC24VACPoE, IP67, K10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XND-6010R	2MP IR Bullet		Wiener X powered by Wiener 5 network outdoor vandal bullet camera, 2MP, Full HD(1080p) @ 60fps, 4mm fixed focal lens (139'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 65', true DN, dual SD card, HLC, defog detection, DIS, PoE, IP66, K10, Nema 4X
Camera - Network	XND-6020R	2MP IR Bullet		Wiener X powered by Wiener 5 network outdoor vandal bullet camera, 2MP, Full HD(1080p) @ 60fps, 4mm fixed focal lens (88.6'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 98', true DN, dual SD card, HLC, defog detection, DIS, PoE, IP66, K10, Nema 4X
Camera - Network	XND-6085RV	2MP Indoor IR Vandal Dome		Wiener X powered by Wiener 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, high powered IR LEDs range of 98', true DN, dual SD card, HLC, defog detection, DIS, 12VDCPoE, IP67, K10
Camera - Network	XND-6080V	2MP Indoor Vandal Dome		Wiener X powered by Wiener 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 4.3x (2.8-12mm) (119.5°-27.9°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS, 12VDCPoE, IP67, K10
Camera - Network	XND-6010	2MP Indoor Vandal Dome		Wiener X powered by Wiener 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 4mm fixed lens (139'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, single SD card, HLC, defog detection, DIS, 12VDCPoE, IP67, K10, Nema 4X
Camera - Network	XND-6020R	2MP Indoor IR Vandal Dome		Wiener X powered by Wiener 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 4mm fixed lens (88.6'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, high powered IR LEDs range of 65', true DN, dual SD card, HLC, defog detection, DIS, PoE, IP66, K10, Nema 4X
Camera - Network	XND-6011F	2MP Flush Mount		Wiener X powered by Wiener 5 network flush mount dome camera, 2MP, Full HD(1080p) @ 60fps, 2.8mm fixed lens (112'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, built-in Me, magnetic cover, electronic DN, SD card, HLC, defog detection, DIS, PoE only
Camera - Network	XNV-6013M	2MP Mobile Vandal Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 2.8mm fixed lens (107.4'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical DN, single SD card, HLC, defog detection, DIS, PoE, IP66, K10 NEMA 4X, -40°C ~ +60°C (40°F ~ +140°F)
This camera was designed to be mounted outside of the vehicle. M12 connector (M12 to RJ45 is not included)				
Camera - Network	XNV-6012	2MP Mobile Vandal Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 2.8mm fixed lens (138.4'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical DN, single SD card, HLC, defog detection, DIS, PoE, IP66, K10 NEMA 4X
Camera - Network	XNV-6012M	2MP Mobile Vandal Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 2.8mm fixed lens (138.4'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, electrical DN, single SD card, HLC, defog detection, DIS, PoE, IP66, K10 NEMA 4X, M12 connector (M12 to RJ45 is not included)
Camera - Network	XNV-6022R	2MP Mobile Vandal Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 3.8mm fixed lens (94.8'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, IR LEDs range of 49', true DN, single SD card, HLC, defog detection, DIS, PoE, IP66, K10 NEMA 4X
Camera - Network	XNV-6022RM	2MP Mobile Vandal Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, 3.8mm fixed lens (94.8'), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification, IR LEDs range of 49', true DN, single SD card, HLC, defog detection, DIS, PoE, IP66, K10 NEMA 4X, M12 connector (M12 to RJ45 is not included)
Camera - Network	XN2-6320	2MP 32x Zoom Box		Wiener X powered by Wiener 5 network zoom box camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.4mm ~ 142.6mm) (81.8° ~ 2.19°), triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, SFP slot, advanced video analytics and sound classification, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDCPoE
Camera - Network	XN2-16320	2MP 32x Zoom Box		Wiener X powered by Wiener 5 network zoom box camera, 2MP, Full HD(1080p) @ 60fps, 32X optical zoom lens (4.4mm ~ 142.6mm) (81.8° ~ 2.19°), triple code H.265H.264/MP4EG with WiseStream II technology, 120dB WDR, advanced video analytics and sound classification, true DN, built-in SD card slot, HLC, defog detection, 12VDCPoE
Camera - Network	XNB-6000	2MP Box		Wiener X powered by Wiener 5 network box camera, 2MP, Full HD(1080p) @ 60fps, simple focus, triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics and sound classification and business analytics, true DN, dual SD card, HLC, defog detection, DIS(Gym), 12VDC24VACPoE
Camera - Network	XNB-6001	2MP Cover Camera Main Module		Wiener X powered by Wiener 5 covert camera body, 2MP, full HD(1080p) 60fps, triple code H.265H.264/MP4EG with WiseStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, HLC, defog detection, DIS, 12VDCPoE, +14°F ~ 131°F, lens module is not included compatible lens modules (SLA-T486, SLA-T489V, SLA-T486S, SLA-T486V, SLA-T486F, SLA-T486D, SLA-T486DS, SLA-T486DSW)
Camera - Network	XNV-16080R	2MP IR Outdoor Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 3.1x (3.2-10mm) (109°~33.2°), triple code H.265H.264/MP4EG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 88.4', true DN, single SD card, HLC, defog detection, DIS, PoE, IP66, K10, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XNV-16080	2MP Outdoor Dome		Wiener X powered by Wiener 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 3.1x (3.2-10mm) (109°~33.2°), triple code H.265H.264/MP4EG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 88.4', true DN, single SD card, HLC, defog detection, DIS, PoE, IP66, K10, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XND-16080RV	2MP Indoor IR Vandal Dome		Wiener X powered by Wiener 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 3.1x (3.2-10mm) (109°~33.2°), triple code H.265H.264/MP4EG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 88.4', true DN, single SD card, HLC, defog detection, DIS, PoE, IP66, K10, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XND-16080V	2MP Indoor Vandal Dome		Wiener X powered by Wiener 5 network indoor vandal dome camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 3.1x (3.2-10mm) (109°~33.2°), triple code H.265H.264/MP4EG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 88.4', true DN, single SD card, HLC, defog detection, DIS, PoE, IP66, K10, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	XND-16080R	2MP IR Bullet		Wiener X powered by Wiener 5 network IR outdoor bullet camera, 2MP, Full HD(1080p) @ 60fps, motorized varifocal lens 3.1x (3.2-10mm) (109°~33.2°), triple code H.265H.264/MP4EG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 88.4', true DN, single SD card, HLC, defog detection, DIS, PoE, IP66, K10, -40°C ~ +55°C (40°F ~ +131°F)
Camera - Network	TNB-6030	PVM Camera	Special order Need Accessory SBP-300MM	PVM camera powered by Wiener X series (1600/1080i), micro HDMI output, 16:9 aspect ratio, face detection display for real distance, customizable text overlay, 4.6mm fixed lens(3.78"), 160dB WDR, H.265H.264/MP4EG, WiseStream II compression technology, micro SD/SDHC/SDXC, bi-directional audio, hallway view mode
Camera - Network	TND-6010M	Front Facing Mobile Camera	Special order	Wiener X network mobile front facing camera, 2MP @ 60FPS, 2.8mm fixed lens (113') triple code H.265H.264/MP4EG with WiseStream II technology, 150dB WDR, USB port for easy installation, advanced video analytics, true DN, SD card, hallway view, HLC, defog detection, DIS(Gym), 12VDCPoE, IP66, IK10, Nema 4X, -40°C ~ +55°C (40°F ~ +131°F)

Camera - Network	QNO-8012R	2MP IR Bullet	Special Order Limited Stock Comparable Model QNO-8012R1	Wieneer Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNO-8012R1	2MP IR Bullet	Available No Audio Invol	Wieneer Q network outdoor vandal bullet camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, no audio invol, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNO-8032R	2MP IR Bullet	Limited Stock	Wieneer Q network outdoor vandal bullet camera, 2MP @ 30fps, 4.5mm fixed focal lens (87°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNO-8032R	2MP IR Bullet	Limited Stock	Wieneer Q network outdoor vandal bullet camera, 2MP @ 30fps, 6.0mm fixed focal lens (82°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC
Camera - Network	QNO-8082R	2MP IR Bullet	Limited Stock	Wieneer Q network outdoor vandal bullet camera, 2MP @ 30fps, motorized var-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, R LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNO-8082R1	2MP IR Bullet	Available No Audio Invol	Wieneer Q network outdoor vandal bullet camera, 2MP @ 30fps, motorized var-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, R LEDs range 98', defocus detection, hallway View, no audio invol, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-8012R	2MP IR Outdoor Dome	Special Order Limited Stock Comparable Model QNV-8012R1	Wieneer Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-8012R1	2MP IR Outdoor Dome	Available No Audio Invol	Wieneer Q network outdoor vandal dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, no audio invol, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-8032R	2MP IR Outdoor Dome	Limited Stock	Wieneer Q network outdoor vandal dome camera, 2MP @ 30fps, 4.5mm fixed focal lens (87°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-8032R1	2MP IR Outdoor Dome	Available No Audio Invol	Wieneer Q network outdoor vandal dome camera, 2MP @ 30fps, 4.5mm fixed focal lens (87°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, no audio invol, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-8024RM	2M Mobile IR Flat Camera		Wieneer Q network mobile IR vandal dome camera, 2MP, Full HD(1080p) 30fps, triple code H.265H.264/MPEG with Wiestream technology, Fixed focal Lens 3.0mm, Built in Mi2 Network connectors (M12 connector to RJ-45 adaptor is not included), hallway View, 120dB WDR, built in IR camera, 65' defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10
Camera - Network	QNV-8032R	2MP IR Outdoor Dome		Wieneer Q network outdoor vandal dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (82°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-8082R	2MP IR Outdoor Dome	Special Order Limited Stock Comparable Model QNV-8082R1	Wieneer Q network outdoor vandal dome camera, 2MP @ 30fps, motorized var-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, R LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QNV-8082R1	2MP IR Outdoor Dome	Available No Audio Invol	Wieneer Q network outdoor vandal dome camera, 2MP @ 30fps, motorized var-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, R LEDs range 98', defocus detection, hallway View, no audio invol, SD card, video analytics, CVBS, open platform, IP66, IK10, PoE/12VDC, white color
Camera - Network	QND-8022R	2MP IR Vandal Dome		Wieneer Q network outdoor vandal dome camera, 2MP @ 30fps, 3.5mm fixed focal lens (94.8°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66, IK10, PoE
Camera - Network	QND-8012R	2MP IR Indoor Dome	Special Order Limited Stock Comparable Model QND-8012R1	Wieneer Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66/12VDC, white color
Camera - Network	QND-8012R1	2MP IR Indoor Dome	Available No Audio Invol	Wieneer Q network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66/12VDC, white color
Camera - Network	QND-8022R	2MP IR Indoor Dome	Limited Stock	Wieneer Q network indoor dome camera, 2MP @ 30fps, 4.5mm fixed focal lens (87°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66/12VDC, white color
Camera - Network	QND-8032R	2MP IR Indoor Dome		Wieneer Q network indoor dome camera, 2MP @ 30fps, 6.0mm fixed focal lens (82°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, IR LEDs range 65', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, IP66/12VDC, white color
Camera - Network	QND-8082R	2MP IR Indoor Dome	Special Order Limited Stock Comparable Model QND-8082R1	Wieneer Q network indoor dome camera, 2MP @ 30fps, motorized var-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, R LEDs range 98', defocus detection, hallway View, one way audio and SD card, video analytics, CVBS, open platform, PoE/12VDC, white color
Camera - Network	QND-8082R1	2MP IR Indoor Dome	Available No Audio Invol	Wieneer Q network indoor dome camera, 2MP @ 30fps, motorized var-focal lens 3.1x (3.2 ~ 10.0mm) (109°~33°), triple code H.265H.264/MPEG with Wiestream II, 120dB WDR, R LEDs range 98', defocus detection, hallway View, no audio invol, SD card, video analytics, CVBS, open platform, PoE/12VDC, white color
Camera - Network	QND-8011	2MP Indoor Dome		Wieneer Q mini network indoor dome camera, 2MP @ 30fps, 2.8mm fixed focal lens (113°), triple code H.265H.264/MPEG with Wiestream I, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, K08, PoE, white color
Camera - Network	QND-8021	2MP Indoor Dome		Wieneer Q mini network indoor dome camera, 2MP @ 30fps, 4.0mm fixed focal lens (87°), triple code H.265H.264/MPEG with Wiestream I, 120dB WDR, defocus detection, hallway View, SD card, people counting, open platform, IP42, K08, PoE, white color
Camera - Network	LNV-6012R	2MP IR Vandal Dome		L series outdoor vandal dome camera, 2MP @ 30fps, var-focal lens 3.1x (3.2 ~ 10.0mm) (101.6° ~ 31.3°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	LVN-6012R	2MP IR Vandal Dome		L series outdoor vandal dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	LVN-6022R	2MP IR Vandal Dome		L series outdoor vandal dome camera, 2MP @ 30fps, 4.5mm fixed focal lens (81°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	LVN-6032R	2MP IR Vandal Dome		L series outdoor vandal dome camera, 2MP @ 30fps, 6mm fixed focal lens (81°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, IP66, IK10, PoE, White
Camera - Network	LND-6012R	2MP IR Dome		L series indoor dome camera, 2MP @ 30fps, var-focal lens 3.1x (3.2 ~ 10.0mm) (101.6° ~ 31.3°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	LND-6022R	2MP IR Dome		L series indoor dome camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	LND-6032R	2MP IR Dome		L series indoor dome camera, 2MP @ 30fps, 4.5mm fixed focal lens (81°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	LNO-8012R	2MP IR Bullet		L series outdoor bullet camera, 2MP @ 30fps, var-focal lens 3.1x (3.2 ~ 10.0mm) (101.6° ~ 31.3°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	LNO-8012R	2MP IR Bullet		L series outdoor bullet camera, 2MP @ 30fps, 3mm fixed focal lens (102°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	LNO-8022R	2MP IR Bullet		L series outdoor bullet camera, 2MP @ 30fps, 4mm fixed focal lens (80°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	LNO-8032R	2MP IR Bullet		L series outdoor bullet camera, 2MP @ 30fps, 6mm fixed focal lens (81°), Double code H.264/MPEG, Wiestream II, 120dB WDR, IR LEDs, hallway view, SD card, PoE, White
Camera - Network	XNB-H421A	2MP Network ATM Camera Kit		Wieneer X powered by Wieneer 5 network ATM camera, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138°), triple code H.265H.264/MPEG with WiStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defocus detection, DIS, 12VDC/PoE, +14V ~ 131V, cable length is 8m (26 feet)
Camera - Network	XNB-H424Q	2MP Network ATM Camera Kit		Wieneer X powered by Wieneer 5 network ATM camera, 2MP, Full HD(1080p) 60fps, 2.4mm fixed lens (138°), triple code H.265H.264/MPEG with WiStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defocus detection, DIS, 12VDC/PoE, +14V ~ 131V, cable length is 1.5m (4.9 feet)
Camera - Network	XNB-H424H	2MP Pinhole Height Strip Camera Kit		Wieneer X powered by Wieneer 1 network pinhole camera with Height Strip Housing, 2MP, Full HD(1080p) 60fps, 4.4mm fixed lens (73°), triple code H.265H.264/MPEG with WiStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defocus detection, DIS, 12VDC/PoE, +14V ~ 131V, cable length is 8m (26 feet)
Camera - Network	XNB-H428B	2MP Bandit Barrier		Wieneer X powered by Wieneer 1 network Bandit Barrier camera, 2MP, Full HD(1080p) 60fps, 2.8mm fixed lens (107.4°), triple code H.265H.264/MPEG with WiStream II technology, 120dB WDR, micro SD/SDHC/SDXC, USB port for easy installation, advanced video analytics and sound classification and business analytics, hallway view, H.LC, defocus detection, DIS, 12VDC/PoE, +14V ~ 131V, cable length is 1.5m (4.9 feet)
Camera - Network	QNP-6230	2MP 23x PTZ	Limited Stock Comparable Model QNP-6230H	Wieneer Q network outdoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265H.264/MPEG, Optical Zoom Lens 23x (4.4-102.1mm), 120dB WDR, true DN, 500' true Pan, SD/SDHC/SDXC, 24VAC/PoE
Camera - Network	QNP-6230H	2MP 23x PTZ	Limited Stock Comparable Model QNP-6230H1	Wieneer Q network outdoor PTZ camera, 2MP, Full HD(1080p) 30fps, H.265H.264/MPEG, Optical Zoom Lens 23x (4.4-102.1mm), 120dB WDR, true DN, 500' true Pan, SD/SDHC/SDXC, 24VAC/PoE, Analytics, IP66, IK10, Heater on -58°F 24VAC
Camera - Network	QNP-6230H1	2MP 23x PTZ	Limited Stock Comparable Model QNP-6230H2	Wieneer Q network outdoor IR PTZ camera, IR range up to 328F, 2MP, Full HD(1080p) 30fps, triple code H.265H.264/MPEG with WiStream II technology, 4.4~11.1mm (25x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC, 16x 256GB, Focus Save, white color
Camera - Network	QNP-6250	2MP 25x PTZ	3 Week Lead Time (Updated Mar'22)	Wieneer Q network outdoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple code H.265H.264/MPEG with WiStream II technology, 4.4~11.1mm (25x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC, 16x 256GB, Focus Save, white color
Camera - Network	QNP-6250H	2MP 25x PTZ	3 Week Lead Time (Updated Mar'22)	Wieneer Q network outdoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple code H.265H.264/MPEG with WiStream II technology, 4.4~11.1mm (25x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC, 16x 256GB, Focus Save, white color
Camera - Network	QNP-6250R	2MP 25x PTZ	3 Week Lead Time (Updated Mar'22)	Wieneer Q network IR PTZ camera, IR range up to 328F, 2MP, Full HD(1080p) 60fps, triple code H.265H.264/MPEG with WiStream II technology, 4.4~11.1mm (25x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC, 16x 256GB, Focus Save, IP66, IK10, NEMA4, white color
Camera - Network	QNP-6320	2MP 32x PTZ	3 Week Lead Time (Updated Mar'22)	Wieneer Q network outdoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple code H.265H.264/MPEG with WiStream II technology, 4.4~14.2mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC, 16x 256GB, Focus Save, white color
Camera - Network	QNP-6320H	2MP 32x PTZ	3 Week Lead Time (Updated Mar'22)	Wieneer Q network IR PTZ camera, IR range up to 328F, 2MP, Full HD(1080p) 60fps, triple code H.265H.264/MPEG with WiStream II technology, 4.4~14.2mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC, 16x 256GB, Focus Save, IP66, IK10, NEMA4, white color
Camera - Network	QNP-6320R	2MP IR 32x PTZ	3 Week Lead Time (Updated Mar'22)	Wieneer Q network outdoor PTZ camera, 2MP, Full HD(1080p) 60fps, triple code H.265H.264/MPEG with WiStream II technology, 4.4~14.2mm (32x) lens, 120dB WDR, Day & Night (ICR), DIS (Built-in gyro sensor), Intelligent Analytics, Micro SD/SDHC/SDXC, 16x 256GB, Focus Save, white color
Camera - Network	TNJ-6321	2MP 32x Positioning Camera	Special Order Only	2MP Network Positioning Camera (1920 x 1080) resolution, 4.4 ~ 142.6mm (32x) varifocal lens, 60fps@2MP (11.264), 30fps@2MP (MP66), H.265, H.264, MP66 code support, 300 Endless, 16~90° 40° Day & Night (ICR), WDR (120dB), Defocus, Tampering, Virtual line, Enter/Exit, On/Off, Audio detection, Face detection, Motion detection, micro SD / SDHC / SDXC slot, Power 24VAC (Optional IR Illuminators, SPL90)

Thermal Cameras

Camera - Network	TNO-4041T	VGA Thermal Camera for PT Unit	Special order	Wieneer I network outdoor thermal camera (uncooled), 640x480 @ 30fps, 18mm fixed focal lens (32°), triple code H.265H.264/MPEG with WiStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), IP66, IK10, PoE/12VDC/24VAC, white color RS484922, built to go on PT head unit
Camera - Network	TNO-4040T	VGA Thermal Bullet	Special order	Wieneer I network outdoor thermal bullet camera (uncooled), 640x480 @ 30fps, 18mm fixed focal lens (32°), triple code H.265H.264/MPEG with WiStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4030T	VGA Thermal Bullet		Wieneer I network outdoor thermal bullet camera (uncooled), 640x480 @ 30fps, 13mm fixed focal lens (48°), triple code H.265H.264/MPEG with WiStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4051T	VGA Thermal Camera for PT Unit	Special order	Wieneer I network outdoor thermal bullet camera (uncooled), 640x480 @ 30fps, 20mm fixed focal lens (17.2°), triple code H.265H.264/MPEG with WiStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), IP66, IK10, PoE/12VDC/24VAC, white color RS484922, built to go on PT head unit
Camera - Network	TNO-4050T	VGA Thermal Bullet	Special order	Wieneer I network outdoor thermal bullet camera (uncooled), 640x480 @ 30fps, 25mm fixed focal lens (17.2°), triple code H.265H.264/MPEG with WiStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNJ-4041T	VGA Thermal Positioning	Special order	Wieneer I network outdoor thermal positioning camera (uncooled), 640x480 @ 30fps, 18mm fixed focal lens (32°), pan: 360° endless, tilt: 90° ~ 40° - triple code H.265H.264/MPEG with WiStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, 24VAC, white color
Camera - Network	TNJ-4051T	VGA Thermal Positioning	Special order	Wieneer I network outdoor thermal positioning camera (uncooled), 640x480 @ 30fps, 35mm fixed focal lens (17.2°), pan: 360° endless, tilt: 90° ~ 40° - triple code H.265H.264/MPEG with WiStream II, SD card, advanced video analytics and sound classification, PTZ handover, open platform, DIS(Gyro), integrated back box, IP66, IK10, 24VAC, white color
Camera - Network	TNO-4030TR	VGA Radiometric Bullet	Special order	Wieneer I network outdoor thermal Radiometric bullet camera (uncooled), 640x480 @ 30fps, 13mm fixed focal lens (48°), triple code H.265H.264/MPEG with WiStream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F ~ 266°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4040TR	VGA Radiometric Bullet	Special order	Wieneer I network outdoor thermal Radiometric bullet camera (uncooled), 640x480 @ 30fps, 18mm fixed focal lens (32°), triple code H.265H.264/MPEG with WiStream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F ~ 266°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color
Camera - Network	TNO-4041TR	VGA Radiometric Camera for PT Unit	Special order	Wieneer I network outdoor thermal Radiometric bullet camera (uncooled), 640x480 @ 30fps, 18mm fixed focal lens (32°), triple code H.265H.264/MPEG with WiStream II, SD card, advanced video analytics and sound classification, PTZ handover, up to 3 user programmable temperature detection areas, temperature detection range is from (-4°F ~ 266°F), open platform, DIS(Gyro), integrated back box, IP66, IK10, PoE/12VDC/24VAC, white color RS484922, built to go on PT head unit
Camera - Network	TNM-3027DY	EBT camera	Special order	Wieneer I network indoor body temperature detection camera (uncooled), dual sensor camera with OVGA thermal (320x240) & 2MP (1920x1080) visible video output, built-in 4.7mm fixed lens (90°) thermal, 4mm fixed lens (87°) visible, AI Face & temperature detection, Estimated Body Temperature, -10°C ~ 45°C (-14°F ~ 113°F), accuracy ±0.3°C (±0.5°F) with standard ±0.2°C (±0.4°F), normal radiometric mode temperature detection range from (4°F ~ 266°F), triple code H.265H.264/MPEG with WiStream II, 160dB WDR, USB and CVBS port for easy installation, advanced video analytics, micro SD, SD PoE/12VDC
Camera - Network	TNO-3010T	OVGA Thermal Bullet	Special order only (4-6 week lead time)	OVGA Thermal camera, Max. 320 x 240 resolution support, built-in 4.7mm fixed lens, H.265, H.264, MP66 code, Max. 30fps@gal resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4, IK10
Camera - Network	TNO-3030T	OVGA Thermal Bullet	Special order only (4-6 week lead time)	OVGA Thermal camera, Max. 320 x 240 resolution support, built-in 4.3mm fixed lens, H.265, H.264, MP66 code, Max. 30fps@gal resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4, IK10
Camera - Network	TNO-3030T	OVGA Thermal Bullet	Special order only (4-6 week lead time)	OVGA Thermal camera, Max. 320 x 240 resolution support, built-in 13.7mm fixed lens, H.265, H.264, MP66 code, Max. 30fps@gal resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4, IK10
Camera - Network	TNO-3040T	OVGA Thermal Bullet	Special order only (4-6 week lead time)	OVGA Thermal camera, Max. 320 x 240 resolution support, built-in 13mm fixed lens, H.265, H.264, MP66 code, Max. 30fps@gal resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4, IK10
Camera - Network	TNO-3050T	OVGA Thermal Bullet	Special order only (4-6 week lead time)	OVGA Thermal camera, Max. 320 x 240 resolution support, built-in 35mm fixed lens, H.265, H.264, MP66 code, Max. 30fps@gal resolutions, full video and audio analytics, temperature detection, shock detection, micro SD Max. 256GB, Hallway View, WiStreamII, PoE, 24VAC, 12VDC / IP66, NEMA4, IK10

Explosion Proof

Camera - Network	TNO-M302EPTD-Z	Explosion Proof Zoom Camera	Special order only (16 weeks lead time)	Explosion proof housing using the XNZ-6320 PoE Only (No Wiper), cULus C101 certification, -10°C ~ +50°C (+14°F ~ -131°F), IP69/P67, IP68, -2" for cULus C101
Camera - Network	TNO-M302EPTD-C	Explosion Proof Zoom Camera	Special order only (16 weeks lead time)	Explosion proof housing using the XNZ-6320 PoE Only (No Wiper), cULus C101 certification, -10°C ~ +50°C (+14°F ~ -131°F), IP69/P67, IP68, -2" for cULus C101
Camera - Network	TNO-M302EPTD-M	Explosion Proof Zoom Camera	Special order only (16 weeks lead time)	Explosion proof housing using the XNZ-6320 PoE Only (No Wiper), cULus C101 certification, -10°C ~ +50°C (+14°F ~ -131°F), IP69/P67, IP68, -4" for NEMA10
Camera - Network	TNO-M302ETWT1-Z	Explosion Proof Zoom Camera	Special order only (16 weeks lead time)	Explosion proof housing using the XNZ-6320 24VAC, with wiper, cULus C101 certification, -40°C ~ +60°C (-40°F ~ +140°F), IP69/P67, IP68, -2" for cULus C101

[illegible]

Recording - Hybrid	HDX-1632	16CH AHD, TVI, CVI, C.VBS, IP Recorder	Weenet HD-Pentastar DVR/AIO up to 8MP*, TVI up to 8MP*, CVI up to 4(MP), C.VBS and IP up to 8(BMP). Max Analog 16CH + NW 10CH, up to BMP; 15/12(9+6)MP recording (frame rate at higher resolutions will vary); triple code H.265(H.264/MPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 30Mbps; 16Ch audio input/output 1CH audio output and 4 relay output, coaxial control, HDMI/VGA video output, 1 x S.pd monitor output, QR Code. Up to 4 SATA HDDs ((ETH/HDD))
Recording - Hybrid	HDX-1632S-4TB	16CH AHD, TVI, CVI, C.VBS, IP Recorder	Weenet HD-Pentastar DVR/AIO up to 8MP*, 4TB Raw Storage(TV I up to 8MP*, CVI up to 4(MP), C.VBS and IP up to 8(BMP). Max Analog 16CH + NW 8CH, up to BMP; 15/12(9+6)MP recording (frame rate at higher resolutions will vary); triple code H.265(H.264/MPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 30Mbps; 16Ch audio input/output 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 x S.pd monitor output, QR code. Up to 4 SATA HDDs ((ETH/HDD))
Recording - Hybrid	HDX-1632S-8TB	16CH AHD, TVI, CVI, C.VBS, IP Recorder	Weenet HD-Pentastar DVR/AIO up to 8MP*, 8TB Raw Storage(TV I up to 8MP*, CVI up to 4(MP), C.VBS and IP up to 8(BMP). Max Analog 16CH + NW 8CH, up to BMP; 15/12(9+6)MP recording (frame rate at higher resolutions will vary); triple code H.265(H.264/MPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 30Mbps; 16Ch audio input/output 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 x S.pd monitor output, QR code. Up to 4 SATA HDDs ((ETH/HDD))
Recording - Hybrid	HDX-1632S-8TB	16CH AHD, TVI, CVI, C.VBS, IP Recorder	Weenet HD-Pentastar DVR/AIO up to 8MP*, 8TB Raw Storage(TV I up to 8MP*, CVI up to 4(MP), C.VBS and IP up to 8(BMP). Max Analog 16CH + NW 8CH, up to BMP; 15/12(9+6)MP recording (frame rate at higher resolutions will vary); triple code H.265(H.264/MPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 30Mbps; 16Ch audio input/output 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 x S.pd monitor output, QR code. Up to 4 SATA HDDs ((ETH/HDD))
Recording - Hybrid	HDX-1632S-12TB	16CH AHD, TVI, CVI, C.VBS, IP Recorder	Weenet HD-Pentastar DVR/AIO up to 8MP*, 12TB Raw Storage(TV I up to 8MP*, CVI up to 4(MP), C.VBS and IP up to 8(BMP). Max Analog 16CH + NW 8CH, up to BMP; 15/12(9+6)MP recording (frame rate at higher resolutions will vary); triple code H.265(H.264/MPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 30Mbps; 16Ch audio input/output 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 x S.pd monitor output, QR code. Up to 4 SATA HDDs ((ETH/HDD))
Recording - Hybrid	HDX-1632S-16TB	16CH AHD, TVI, CVI, C.VBS, IP Recorder	Weenet HD-Pentastar DVR/AIO up to 8MP*, 16TB Raw Storage(TV I up to 8MP*, CVI up to 4(MP), C.VBS and IP up to 8(BMP). Max Analog 16CH + NW 8CH, up to BMP; 15/12(9+6)MP recording (frame rate at higher resolutions will vary); triple code H.265(H.264/MPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 30Mbps; 16Ch audio input/output 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 x S.pd monitor output, QR code. Up to 4 SATA HDDs ((ETH/HDD))
Recording - Hybrid	HDX-1632S-24TB	16CH AHD, TVI, CVI, C.VBS, IP Recorder	Weenet HD-Pentastar DVR/AIO up to 8MP*, 24TB Raw Storage(TV I up to 8MP*, CVI up to 4(MP), C.VBS and IP up to 8(BMP). Max Analog 16CH + NW 8CH, up to BMP; 15/12(9+6)MP recording (frame rate at higher resolutions will vary); triple code H.265(H.264/MPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 30Mbps; 16Ch audio input/output 1CH audio output, 16 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 x S.pd monitor output, QR code. Up to 4 SATA HDDs ((ETH/HDD))
Recording - Hybrid	HDX-835	8CH AHD, TVI, CVI, C.VBS, IP Recorder	Weenet HD-Pentastar DVR/AIO up to 8MP*, TVI up to 8MP*, CVI up to 5(MP), C.VBS and IP up to 8(BMP). Max Analog 8CH + NW 10CH, up to BMP; 8(B)/5(S)+GMP, 12/12(9+6)MP recording (frame rate at higher resolutions will vary); triple code H.265(H.264/MPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 30Mbps; 8Ch audio input/output 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 x S.pd monitor output, QR code. Up to 4 SATA HDDs ((ETH/HDD))
Recording - Hybrid	HDX-835-4TB	8CH AHD, TVI, CVI, C.VBS, IP Recorder	Weenet HD-Pentastar DVR/AIO up to 8MP*, 4TB Raw Storage(TV I up to 8MP*, CVI up to 5(MP), C.VBS and IP up to 8(BMP). Max Analog 8CH + NW 10CH, up to BMP; 8(B)/5(S)+GMP, 12/12(9+6)MP recording (frame rate at higher resolutions will vary); triple code H.265(H.264/MPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 30Mbps; 8Ch audio input/output 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 x S.pd monitor output, QR code. Up to 4 SATA HDDs ((ETH/HDD))
Recording - Hybrid	HDX-835-8TB	8CH AHD, TVI, CVI, C.VBS, IP Recorder	Weenet HD-Pentastar DVR/AIO up to 8MP*, 8TB Raw Storage(TV I up to 8MP*, CVI up to 5(MP), C.VBS and IP up to 8(BMP). Max Analog 8CH + NW 10CH, up to BMP; 8(B)/5(S)+GMP, 12/12(9+6)MP recording (frame rate at higher resolutions will vary); triple code H.265(H.264/MPEG, Recording Bandwidth Max. 50Mbps, Playback Bandwidth 30Mbps; 8Ch audio input/output 1CH audio output, 8 alarm input and 4 relay output, coaxial control, HDMI/VGA video output, 1 x S.pd monitor output, QR code. Up to 4 SATA HDDs ((ETH/HDD))

Recording - Hybrid	HRX-835-8TB	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 8TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 8CH + NW 10CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 8CH audio input/ 1CH audio output, 4 alarm input and 4 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-835-12TB	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 12TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 8CH + NW 10CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 8CH audio input/ 1CH audio output, 4 alarm input and 4 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-835-16TB	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 16TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 8CH + NW 10CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 8CH audio input/ 1CH audio output, 4 alarm input and 4 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-835-24TB	8CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 24TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 8CH + NW 10CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 8CH audio input/ 1CH audio output, 4 alarm input and 4 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 4 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 4CH + NW 8CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435-2TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 2TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 4CH + NW 8CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435-4TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 4TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 4CH + NW 8CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435-6TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 6TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 4CH + NW 8CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435-8TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 8TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 4CH + NW 8CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-435-12TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 12TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 4CH + NW 8CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 2 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-434	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 4CH + NW 8CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 1 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-434-2TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 2TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 4CH + NW 8CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 1 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-434-4TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 4TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 4CH + NW 8CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 1 SATA HDDs (6TB/HDD)
Recording - Hybrid	HRX-434-6TB	4CH AHD, TVI, CVI, CVBS, IP Recorder		Wiener HD+ Pentabrid DVR AHD (up to BMP), - 6TB Raw Storage.TVI (up to BMP), CVI (up to SMP), CVBS and IP (up to BMP). Max Analog 4CH + NW 8CH, up to BMP, 8192ps@6MP, 12/12ps@8MP recording (frame rate at higher resolutions will vary), triple codecs: H.265H1.264MPEG, Recording Bandwidth Max 30Mbps, Playback Bandwidth 32Mbps, 4CH audio input/ 1CH audio output, 4 alarm input and 2 relay output, coaxial control, HDMI/ VGA video output, 1 X spot monitor output, QR code . Up to 1 SATA HDDs (6TB/HDD)

DVR's Accessories

Recording - Adapter	SRU-X121	Audio Adapter for DVR		Optional 5-Sub adapter with 12 RCA audio connector for SRD-100X series
Lenses				
Lens	SLA-C-E24	Canon EF 24mm f/1.4L II USM		Canon 24mm f1.4L, Auto-Iris (EF 24mm f1.4L II USM) : Horizontal field of view: 8K 62.1° CarePak 4 Years warranty
Lens	SLA-C-E30	Canon EF 30mm f/1.2L USM		Canon 30mm f1.2, Auto-Iris (EF 30mm f1.2 USM) : Horizontal field of view: 8K 31.6° CarePak 4 Years Warranty
Lens	SLA-C-E85	Canon EF 85mm f/1.2L II USM	Limited Stock	Canon 85mm f1.2L, Auto-Iris (EF 85mm f1.2L II USM) : Horizontal field of view: 8K 19.2° CarePak 4 Years Warranty
Lens	SLA-C-E2470	Canon EF 24-70mm f2.8L II USM		Canon 24-70mm f2.8L II USM (EF 24-70mm f2.8L USM) : Horizontal field of view 8K 62.1° ~ 23.2° CarePak 4 Years Warranty
Lens	SLA-C-E70200	Canon EF 70-200mm f2.8L IS III USM		Canon 70-200mm f2.8L, Auto-Iris, Vari Focal (EF 70-200mm f2.8L USM) : Horizontal field of view: 8K 23.2° ~ 8.3° , CarePak 4 Years Warranty
Lens	SLA-C-0910	1/1.8" 3.9-10mm (i-CS Mount)	4 weeks lead time	1/1.8" 3.9-10mm F1.5 Varifocal, HD Series Pairs (i-CS Mount) Day/Night IR (12 MP capable) for i-Box Camera (PNB-A8001)
Lens	SLA-C-02885	12.7" 2.8-8.5mm (i-CS Mount)	4 weeks lead time	12.7" 2.8-8.5mm F1.2 Varifocal, HD Series Pairs (i-CS Mount) Day/Night R (8 MP capable) for WIN7 Box Camera (XNB-9002 and XNB-8002)
Lens	SLA-T1080F	1.6mm Lens/Imager straight body for XNB-6001 (8.0m cable)		1.6mm fixed lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.03 Lux, 120dB WDR, 187° horizontal field of view, 8 meters cable (26 feet cable)
Lens	SLA-T2480	2.4mm Lens/Imager straight body for XNB-6001 (8.0m cable)		2.4mm fixed lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.45 Lux, 120dB WDR, 138° horizontal field of view, 8 meters (26 feet cable)
Lens	SLA-T2480V	2.4mm Lens/Imager right angle body for XNB-6001 (8.0m cable)		2.4mm fixed lens module, compatible with the XNB-6001, right angle body style, 2MP @ 60fps, 0.45 Lux, 120dB WDR, 138° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680	4.6mm Lens/Imager straight body for XNB-6001 (8.0m cable)		4.6mm pinhole lens module, compatible with the XNB-6001, straight body style, 2MP @ 60fps, 0.06 Lux, 120dB WDR, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680V	4.6mm Lens/Imager right angle body for XNB-6001 (8.0m cable)		4.6mm pinhole lens module, compatible with the XNB-6001, right angle body style, 2MP @ 60fps, 0.06 Lux, 120dB WDR, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680A	4.6mm Lens/Imager straight body for PNM-9000GB (8.0m cable)		4.6mm pinhole lens module, compatible with PNM-9000GB, straight body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680VA	4.6mm Lens/Imager right angle body for PNM-9000GB (8.0m cable)		4.6mm pinhole lens module, compatible with PNM-9000GB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T2480A	2.4mm Lens/Imager straight body for PNM-9000GB (8.0m cable)		2.4mm fixed lens module, compatible with PNM-9000GB, straight body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T2480VA	2.4mm Lens/Imager right angle body for PNM-9000GB (8.0m cable)		2.4mm fixed lens module, compatible with PNM-9000GB, right angle body style, 2MP @ 30fps, 0.45 Lux, 138° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T1080FA	1.6mm Lens/Imager straight body for PNB-9000GB (8.0m cable)		1.6mm fixed lens module, compatible with PNM-9000GB, straight body style, 2MP @ 30fps, 0.03 Lux, 187° horizontal field of view, 8 meters cable / 26 feet cable
Lens	SLA-H-4680VA	Height strip with 2MP pinhole lens	Camera not included	Height strip with 4.6mm pinhole lens module, compatible with PNM-9000GB, right angle body style, 2MP @ 30fps, 0.06 Lux, 73° horizontal field of view, 8 meters/ 26 feet cable
Lens	SLA-T4680D	Door Jamb Lens (black)		Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, black color
Lens	SLA-T4680DS	Door Jamb Lens (silver)		Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, silver color
Lens	SLA-T4680DW	Door Jamb Lens (white) Special order ONLY	Special order only	Door Jamb head with a 4.6mm lens, compatible with XNB-6001 (not included) 8m (26 feet) cable, white color
Lens	SLA-T40410CN	Megapixel DC-Iris Lens		Megapixel Lens, image sensor from 1/2.3" up to 1/1.7", Up to 12MP resolution, Vari-focal (4-10mm), DC auto iris, CS-Mount, Compatible with XNB-6005/8000, PNB-A8001
Lens	SLA-T41250CN	Megapixel DC-Iris Lens		Megapixel Lens, image sensor from 1/2.3" up to 1/1.7", Up to 12MP resolution, Vari-focal (12-50mm), DC auto iris, CS-Mount, Compatible with XNB-6005/8000, PNB-A8001
Lens	SLA-T4946CN	Megapixel DC-Iris Lens		Lens, 1/2.3", Up to 4K Vari-focal(9-40mm), Auto DC Iris, CS-Mount, compatible with: XNB-6000, HCB-6000/6017/7000/7000A
Lens	SLA-2M820VP	PNM-9322VQP Lens module	For the PNM-9320VQP, PNM-9321VQP, PNM-9322VQP	12.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2° for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M820P	PNM-9322VQP Lens module	For the PNM-9320VQP, PNM-9321VQP, PNM-9322VQP	12.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M900VP	PNM-9322VQP Lens module	For the PNM-9320VQP, PNM-9321VQP, PNM-9322VQP	12.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M800P	PNM-9322VQP Lens module	For the PNM-9320VQP, PNM-9321VQP, PNM-9322VQP	12.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M1200P	PNM-9322VQP Lens module	For the PNM-9320VQP, PNM-9321VQP, PNM-9322VQP	12.8" 2MP CMOS with a 12.0mm fixed focal lens, FoV: H: 26.3°, V: 14.9°, for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-5M700P	PNM-9322VQP Lens module	For the PNM-9320VQP, PNM-9321VQP, PNM-9322VQP	11.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9° for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-5M600P	PNM-9322VQP Lens module	For the PNM-9320VQP, PNM-9321VQP, PNM-9322VQP	11.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9° for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-5M700P	PNM-9322VQP Lens module	For the PNM-9320VQP, PNM-9321VQP, PNM-9322VQP	11.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8° for the PNM-9320VQP and PNM-9322VQP
Lens	SLA-2M400Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	12.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2° for the PNM-9000VQ
Lens	SLA-2M800Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	12.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-9000VQ
Lens	SLA-2M900Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	12.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-9000VQ
Lens	SLA-2M800Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	12.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-9000VQ
Lens	SLA-5M700Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	11.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9° for the PNM-9000VQ
Lens	SLA-5M600Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	11.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9° for the PNM-9000VQ
Lens	SLA-5M700Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	11.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8° for the PNM-9000VQ
Lens	SLA-5M700Q	PNM-9000VQ Lens module	For the PNM-9000VQ, PNM-9002VQ	11.8" 5MP CMOS with a 3.7mm fixed focal lens, FoV: H: 97.5°, V: 71.9° for the PNM-9000VQ
Lens	SLA-5M600Q	PNM-9000VQ Lens module	For the PNM-9000VQ	11.8" 5MP CMOS with a 4.6mm fixed focal lens, FoV: H: 77.9°, V: 57.9° for the PNM-9000VQ
Lens	SLA-5M700Q	PNM-9000VQ Lens module	For the PNM-9000VQ	11.8" 5MP CMOS with a 7.0mm fixed focal lens, FoV: H: 50.7°, V: 37.8° for the PNM-9000VQ
Lens	SLA-2M400Q	PNM-7000VQ Lens module	Limited Stock For the PNM-7000VQ	12.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-7000VQ
Lens	SLA-2M800Q	PNM-7000VQ Lens module	Limited Stock For the PNM-7000VQ	12.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-7000VQ
Lens	SLA-2M900Q	PNM-7000VQ Lens module	Limited Stock For the PNM-7000VQ	12.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-7000VQ
Lens	SLA-2M800Q	PNM-7000VQ Lens module	Limited Stock For the PNM-7000VQ	12.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-7000VQ
Lens	SLA-2M400Q	PNM-7000VQ Lens module	Limited Stock For the PNM-7000VQ	12.8" 2MP CMOS with a 2.4mm fixed focal lens, FoV: H: 135.4°, V: 71.2°, for the PNM-7000VQ
Lens	SLA-2M800Q	PNM-7000VQ Lens module	For the PNM-7000VQ	12.8" 2MP CMOS with a 2.8mm fixed focal lens, FoV: H: 107.4°, V: 62.2°, for the PNM-7000VQ
Lens	SLA-2M900Q	PNM-7000VQ Lens module	For the PNM-7000VQ	12.8" 2MP CMOS with a 3.6mm fixed focal lens, FoV: H: 94.8°, V: 49.3°, for the PNM-7000VQ
Lens	SLA-2M800Q	PNM-7000VQ Lens module	For the PNM-7000VQ	12.8" 2MP CMOS with a 6.0mm fixed focal lens, FoV: H: 50.4°, V: 28.8°, for the PNM-7000VQ
Lens	SLA-M930CN	Megapixel DC-Iris Lens		Lens, 12.8", 3 MP, Vari-focal (2.8-8.0mm), Auto DC Iris, CS-Mount
Lens	SLA-M930PN	Megapixel Paris Lens		Lens, 12.8", 3 MP, Vari-focal (2.8-8.0mm), Auto P Iris, CS-Mount

[illegible]

[illegible]

Disclaimer

We put our best effort and knowledge to maintain the accuracy of specifications and price. Should there be any discrepancies we reserve the right to follow our specifications and price set. Thanks for your understanding.