

Features:

- 1/3" Sony Super HAD II CCD
- Effective Pixels: 811 (H) x 508 (V)
- **650 TV Lines**
- 2.8 ~ 12mm Vari-Focal Lens
- Heavy Duty Vandalproof & Weatherproof
- Super Low Lux, OSD Menu
- 12V DC



SUPER LOW LUX

OSD

Specifications:

C	Image Sensor	1/3" Sony Super HAD II CCD
	Pixel	NTSC: 811(H) x 508 (V)
D	Scanning System	2:1 Interlace
	Synchronization	Internal / Line-lock
E	OSD	Yes
	Resolution	650TV Lines
L	Dynamic Range	60dB (x128)
	S/N Ratio	60dB (AGC Off, Weight On)
E	Min. Illumination	Color Mode: 0.6Lux / 0.003Lux (Sense-up) B/W Mode: 0.1Lux / 0.0002Lux (Sense-up)
	Electronic Shutter	1/60 ~ 1/120,000 sec (NTSC)
C	Slow Shutter	Yes
	White Balance	ATW / AWC / Manual / Outdoor (1800K ~ 10500K) Indoor (4500K ~ 8500K)
R	Backlight Compensation	WDR / BLC / Off Selectable
	Gain Control	Low / Mid / High / Off Selectable
I	DNR	2D, 3D Double DNR
	Motion Detection	On / Off (4 Zone, Alarm Output)
C	Privacy Masking	On / Off (15 Zone)
	Mirror / Flip / Freeze	On / Off
A	Digital Zoom	On (x6) / Off
	Day & Night	Color / B&W / Auto / EXT
L	Sharpness	On / Off (Level Adjustable)
	Blemish Compensation	256 Point (Even 128 Point, ODD 128 Point)
O	Power	DC 12V
	Weatherproof	IP67
T	Iris Control	DC
	Built-In Lens	2.8 ~ 12mm Vari-Focal Lens
H	Operating Environment	14°F ~ 122°F RH 80% Max
	Dimension	5.4" (D) x 5" (H)
R	Weight	1.83 LBS