



### **■ World Leading Active Matrix TFT-LCD Panel**

Truly flat LCD screen delivers razor sharp images

# ■ Hi Performance Image Proceseeing Circuit

3D comb filter and deinterlace function realize perfect images

# ■ Real Industrial Mechanical Design

Rigid case comes with Heavy duty metal vessel, LCD protection glass

### ■ Versatile terminals for Security and Industrial Solution

Multiple input and output of Video(BNC Type), Audio, S-Video and RGB

# ■ Public View Monitor Ready

**Special Features** 

Ready to use for Public View Monitor with DC 12V outlet and mounting hole

3D comb Filter

USB Hub

Deinterlace Function

DC 12V Power Outlet

Yes

Yes

Yes

Yes

Video	
Screen Size	17"
Resolution	1280 x 1024@75Hz
Contrast Ratio	500:1
Brightness	300cd/m2
Aspect Ratio	4:3
Color Depth	16.2M
Viewing Angle(H/V)	150°/135°
Pixel Pitch	0.264mm
Response Time	13ms
Scanning Frequency(Horizontal)	30 ~ 80KHz
(Vertical)	56 ~ 75Hz
Video System	NTSC
Audio	
Built-in Speakers	Yes
Gradual Volume Increase	Yes
Terminals	
RGB In (15-pin)	1
Video In(BNC Jack)	2
Video Out(BNC Jack)	2
Audio In	2
Audio Out	2
S-Video In	1
S-Video Out	1
Component In	Not Available
DVI In	Not Available
PC stereo In	1

DO IZI I OTTO OUTION	
LCD Protection Glass	Yes
Rack Mountable Kit	Optional
Camera Mounting Hole	2(Upper/Bottom)
Multi-lingual Menus	English, Spanish, French,
	German, Italian
VESA™ Standard Compatible	Yes
Additional Information	
Cabinet Dimensions	
WxHxD	15.2"x15.7"x7.5"/386x398x190
Weight	13.7lbs/6.2kg
Dimensions with Packaging	
WxHxD	18.5"x16.9"x7.5"/470x430x191
Weight	17.2lbs/7.8kg
Power Consumption	40W
Power Source	AC110~230V(50/60Hz)
Cabinet	
Finish	Black
Tilt Stand	Yes
Warranty	
Warranty: Parts/Labor	1 Year/1 Year
MTBF (Approx.)	30K hrs.
Regulations	
TUV-NRTL(same as UL), CB,	FCC(B), CE-EMC(LVD)

<sup>\*</sup> Specification and Design are subject to change without prior notice.

Transmitter

Yes

**Remote Control**