ORION IMAGES CORPORATION



DR DN®





SPECIAL FEATURES_

The ORION LCD w/ LED BLU (backlight unit) high brightness displays are a truly professional experience in next generation technology using eco-friendly material (no mercury or halogen). This technology exceeds the NTSC color gamut standard of 100% with the LED BLU at 123% to provide a wider range of colours than ever before - you will see colors on screen as you see them in real world.

- 1920 x 1080p Full HD
- LED BLU (Back Light Unit) Display Monitor
- BNC 2 In / 2 Out, S-Video 1 In, VGA 1 In, HDMI 1 In, Audio 2 In, PC Stereo 1 In
- 5ms Response, 250 NITS
- 1000:1 Contrast Ratio
- VESA Mount Compatible
- Wall and Ceiling Mount








SPECIFICATIONS

		21REDE
Display	Screen Size	21.5 Inch
	Panel Type	LED BLU
	Max. Resolution	1920 x 1080 @ 60Hz
	Pixel Pitch	0.24825 x 0.24825mm
	Brightness	250cd/m ²
	Contrast Ratio	1000 : 1
	Aspect Ratio	16 : 9
	Viewing Angle (H/V)	170°/ 160°
	Display Color	16.7 Million
	Response Time	< 5ms
	Video System	NTSC / PAL
Interface	Video In / Out (BNC Type)	2/2
	S-Video In	1
	VGA In (15 PIn D-Sub)	1
	HDMI In	1
	Audio In (RCA Type)	2(L + R)
	PC Stereo In	1
Audio	Built-In Speaker	Yes (2W x 2)
Features Dimension (W x H x D) Cabinet	Filter Type	2.5D Comb Filter
	Multi Language	English, French, German, Spanish, Italian
	Outline Dimension (w/ stand)	21.17" x 15.93" x 5.90"
	Net. Weight	8.818 lbs
	Gross Weight	11.02 lbs
	Material / Color	ABS Plastic / Black
	Tilt Function	Front 5° / Back 10°
Warranty	Part / Labor	2year / 2year
	MTBF (Approx.)	30,000 Hours
Regulations		RoHS, TUV-NRTL, FCC(B), CE
Power	Consumption: < On	Max. <30W
		Min. <1W
	Electrical Ratings	AC110 ~ 230V(50/60Hz)
		DC 12V / 3.7A
Circumstance	Operating Temperature	0 ~ 50°C / 32 ~ 122°F
	Storage Temperature	-20 ~ 60°C / -4 ~ 140°F
Mounts	VESA™ Mount Size	75 x 75mm
	Wall	WB-5, WB-10, WB-30, WB-31
	Ceiling	CMK-01
*Design and specifications are subject to change without notice		

DIMENSIONS



OTHER VIEW





Side View



