

## UL Listed GSM Alarm Communicator for Commercial Security

UL Listed and bank-vault security rated, the Uplink 2550-CB alarm communicator delivers full-event reporting and complete end-to-end signal verification for backup to landline connections. Designed for commercial applications, the Uplink 2550-CB is compatible with virtually all security system panels and supports all common event reporting formats. Installation is remarkably easy, with no additional programming or central station equipment required. Instant onsite activation is available through the Uplink dealer website or live operator, and includes options for automatic, daily or weekly test signals. The Uplink 2550-CB offers unparalleled value, and is backed by Uplink's dealer support program.

### Uplink 2550-CB Key Features



- UL Listed
- Multiple central station event reporting formats: Contact ID, SIA, Pulse 4/2 (:10, :20, or :40 PPS), Modem IIe/IIIa/IIIa<sup>2</sup>
- Industry's only proprietary ISO certified network services
- Bank-vault rating for maximum compliance
- Low-profile, tamper-resistant case



- Installs in minutes
- Automatic, remote daily or weekly status and signal tests
- Daily or weekly testing options
- Full event reporting



- Compatible with all major control panels
- Dial-capture, two inputs, three outputs and trouble reporting for universal compatibility
- Telephone line monitor for backup or primary communications
- Redundant delivery methods and multiple carrier paths



- Flat-rate billing for improved dealer profitability
- Universal - works with any central station - no special receiver or programmer required
- Customized product marketing services through a simple e-commerce website



#### Uplink's dealer support :

- Instant activation by secure dealer website or live operator
- Email Notifications for instant alerts
- Website Control & Status 24/7
- Expert Support from a live technical specialist 8am-8pm Monday through Friday
- Dealer website for activation/deactivation, trouble-shooting, remote programming and on-demand status and signal strength testing, analysis tools and more



*\*16.5V AC required*

### Uplink 2550-CB

Alarm Communicator for Commercial Security

## A Trusted Partner

The Uplink 2550-CB is a member of the Uplink family of wireless alarm communicators. Our products deliver the unique combination of reliable technology and superior value that has made Uplink the security industry's most trusted source for alarm communicators since 1996. GSM or CDMA protocols, primary or back-up applications, summary or full data reporting, there is an Uplink wireless alarm communicator for virtually any security system on the market today. With hundreds of thousands of installed communicators throughout the United States and Canada, Uplink delivers on its promise as the security dealer's trusted partner.

Plus, Uplink wireless communicators are backed by the unique combination of the proprietary ISO-27001 certified network service offering and a robust dealer web management tool.

For more information, visit the Uplink website and sign up to become an Uplink dealer at [www.uplink.com](http://www.uplink.com).

## Uplink 2550-CB Product Specifications

### INPUTS

Alarm Dial Capture  
Tamper Switches  
Two Inputs

- Contact ID, SIA, Modem IIe/IIla/IIla<sup>2</sup>, and 4/2 (:10, :20, or :40 PPS)
- Single and Double
- Contact Closure

### UL STANDARDS

- UL 1610

### OUTPUTS & REPORTING

Central Station  
Three Relay Outputs  
Other Reporting  
Automated Testing  
Status LEDs

- Contact ID, SIA, Modem IIe/IIla/IIla<sup>2</sup>, Pulse 4/2 (:10, :20, or :40 PPS), Internet or Dial Up
- (2) configurable - normally open, (1) configurable - normally closed
- Low Battery, AC Loss
- Monthly, Weekly or Daily
- Programmable for backup or primary reporting
- GSM/GPRS Network
- Signal Strength
- Power
- Telco Line
- Trouble
- Heartbeat

### POWER REQUIREMENTS

AC Transformer  
Battery Backup  
Power Supply

- UL Listed 16.5V AC - 45 VA transformer - NOT INCLUDED
- UL Listed 5.0 Ampere 12V DC Battery PS-1250-F1 or equivalent
- Battery Size (max): L 3.5" x W 2.75" x H 4.00"
- Built-in 12V DC Power Supply with battery backup & charging circuit

### RADIO

GSM  
Transmit Power

- 850/900/1800/1900 MHz
- Maximum Allowable
  - 1.0W at 1800/1900 MHz
  - 2.0W at 850/900 MHz

### DIMENSIONS

Height  
Width  
Depth  
Antenna

- 12.2 inches
- 7.5 inches
- 3.9 inches
- 7.75 inches

### DEALER WEBSITE

- Activate & Deactivate units
- Adjust settings and reporting
- Request status and signal strength
- View signal history
- Control inputs and outputs and notifications

