

# TRIPLETT

**New!!!**



The Triplet CamView PTZ is a multi-function test tool designed for CCTV and Security electronics installers and maintenance technicians. A color LCD video monitor allows viewing of security camera images to verify their operation and setup. The CamView PTZ's keyboard allows control and setup of the camera's PTZ (Pan, Tilt, Zoom) functions (if so equipped) via a standard RS-485, RS-422, or RS-232 interface. A Color Bar Generator provides a standard test signal to check video cables, video recorders, and video monitors. LAN cable can also be tested using the CamView PTZ's built-in cable tester.

The rugged yet lightweight construction maximizes convenience and portability, and the 10 hour rechargeable Li-ion battery delivers extended runtime. Its multiple functions, simple operation via on-screen menus, and reliable performance makes the CamView PTZ an efficient time saving test tool that will enhance any professional tool kit.

## Specifications:

### Video Specs

Display: Full color 2.6" TFT-LCD, 960 x 240 pixels  
Display Adjustments: Brightness, Contrast, Color Saturation  
Display Video Format: NTSC or PAL (Auto Selection)  
Video Input and Output: 1 each, BNC, 75 Ohms, 1.0 Vpp

### PTZ Controller

Protocols Supported: Pelco D, Pelco P, YAAN, YAAN-O, Samsung, Panasonic, Lilin-FAST, Lilin-MLP2, Molynx, Minking A01, Minking B01, AD, Fastrax, CBC, LC-NEW, WV-CS850, SONY-EVI, LG-MULTIX, PEARMAIN, ALEC, DAT-SD, Vicon, Vcltp, DH-YTC06, Sanyo-SSP, Santachi  
Communication: RS-232, RS-485, RS-422 simplex (2 wire)  
Baud Rates: 150, 300, 600, 1200, 2400, 4800, 9600, 19200bps

### Data Monitor

Communication: RS-232, RS-485  
Baud Rates: 150, 300, 600, 1200, 2400, 4800, 9600, 19200bps

### Video Signal Generator

Pattern: 8 vertical color bars  
Formats Supported: NTSC-M (RS170A), NTSC M (Japan), NTSC M (CCIR601), PAL-N (non Arg.), PAL-N (Arg.), PAL-M, PAL-B, PAL-D, PAL-G, PAL-H, PAL-I  
Video: 75 Ohms, 1Vpp

### LAN Cable Test

Test for Opens, Shorts, and Miswires. Remote Terminator provided.

### Power

AC Adaptor / Charger: Input 100VAC to 240VAC, 50/60Hz. Output 5VDC 2.0A  
Battery: Rechargeable Lithium Ion Polymer  
Charge Time: 4 hours or less  
Run Time: 11 hours (full charge)

### Certifications: CE and FCC

Operating Environment: -30F to 160F (-30C to 70C), 0 to 90% RH  
Dimensions: 6" x 4" x 2"  
Weight: 10 oz

# CamView PTZ

## Multi-Function Test Tool for CCTV & Security Installation Professionals

## Features:

- ▲ Full Color 2.6" TFT-LCD Video Monitor
- ▲ OSD (On Screen Display) of all Modes, Functions, and Settings
- ▲ Adjustable LCD Brightness / Contrast / Color Saturation
- ▲ BNC connectors match professional CCTV equipment
- ▲ Full Loop Thru capability or simultaneous View / Gen mode
- ▲ Auto NTSC / PAL detection and video display
- ▲ PTZ Keyboard allows fast access to Pan, Tilt, Zoom, Focus, and Iris
- ▲ Keyboard allows adjustment of Groups, Tours, and Presets
- ▲ Measures video level (IRE)
- ▲ Auto Address Search quickly finds camera address
- ▲ Continuous Pan helps identify failing pan motors
- ▲ Supports more than 25 PTZ Protocols
- ▲ Supports RS-485, RS-422, and RS-232 PTZ interfaces
- ▲ Data Monitor mode verifies presence of PTZ signals
- ▲ PTZ Transmit / Receive LEDs
- ▲ Color Bar Generator produces NTSC and PAL video formats
- ▲ Rechargeable Lithium Ion Polymer Battery provides 10 hr work time
- ▲ On screen battery life indicator and LED charging indicator
- ▲ Operates from battery or AC power pak
- ▲ Auto-Power-Off extends battery life (can be defeated)
- ▲ One Year Warranty
- ▲ Includes: Carrying case with shoulder strap, Neck strap for CamView, BNC cable and RS-485 / RS-422 cable, LAN Remote Terminator, International AC power pak and charger included



**MSRP**  
**\$379<sup>00</sup>\***  
**Cat. No.: 8000**

**TRIPLETT**  
**Test Equipment & Tools**

Jewell Instruments, LLC  
850 Perimeter Road, Manchester, NH 03103  
PHONE: 800-TRIPLITT FAX: 603-622-2690

**www.triplett.com**

\* Suggested Resale Price.  
Price & Specifications subject  
to change without notice. 3/10