

GV-BX120D 1.3M H.264 Low Lux D/N Box IP Camera



- 1.3 megapixel progressive scan CMOS
- Dual video streams from two of H.264, MJPEG and MPEG4
- Up to 30 fps at 1280 x 1024
- Built-in / external microphone
- 2-way audio
- One sensor input and alarm output
- TV-out support
- Motion detection
- Tampering alarm
- Privacy mask
- IP address filtering
- 3GPP/ISMA
- DC 12V / PoE
- Day / Night function
- Varifocal megapixel lens
- 16 languages on Web interface

Active Tampering Alarm

Tampered



Focus Change



Camera Shift



SPECIFICATIONS

Camera		
Image Sensor		1/3" progressive scan CMOS
Picture Elements		1280 (H) x 1024 (V)
Minimum Illumination	Color	0.15 Lux (1/30 sec), 0.08 Lux (1/5 sec)
	B/W	0.08 Lux (1/30 sec), 0.04 Lux (1/5 sec)
	IR ON	0 Lux
Shutter Speed		Automatic, Manual (1/5 ~ 1/8000 sec)
White Balance		Automatic, Manual (2800K ~ 8500K)
Lens		
Megapixel		Yes
IR Support		Yes
Iris		DC Drive
Focal Length		2.8 ~ 12 mm
Max Aperture		F / 1.4
Mount		CS Mount
Image Format		1/3"
Angle of view	Diagonal	115° ~ 45.3°
	Horizontal	92° ~ 27.2°
	Vertical	69° ~ 20.4°
Operation	Focus	Manual (w / lock)
	Zoom	Manual (w / lock)
	Iris	DC
Operation		
Video Codec		H.264, MPEG4, MJPEG
Video Streaming		Dual Streams from two of H.264, MPEG4 and MJPEG
Frame Rate		30 fps at 1280 x 1024 * The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).

Image Setting		Brightness, Contrast, Sharpness, Gamma, White Balance, Flicker-less, Image Orientation	
Audio Codec		G.711	
Input		1 Input (Dry Contact)	
Output		1 Digital Output	
Network			
Interface		10/100 Ethernet	
Ethernet Protocol		HTTP, TCP, UDP, SMTP, FTP, DHCP, NTP, UPnP, DynDNS, 3GPP/ISMA RTSP	
Mechanical			
Lens Mounting		C / CS-Mount	
Connectors	Power	DC Jack	
	Ethernet	RJ-45	
	Audio	1 In (Using the built-in microphone or externally connecting a microphone) 1 Out (Stereo phone jack, 3.5 mm / 0.14 in)	
	Digital I/O	3-pin terminal block, pitch 2.5 mm / 0.1 in	
	Auto Iris	DC drive	
	Local Storage	Mini or micro SD/SDHC memory card slot	
	TV-Out	BNC connector	
LED Indicator		2 LEDs: Power, Status	
General			
Operating Temperature		0 °C ~ 50 °C / 32 °F ~ 122 °F	
Humidity		10% to 90% (no condensation)	
Power Source		12V DC / PoE	
Power Consumption		5 W (max. 416 mA at 12V DC)	
Regulatory		CE, FCC, C-Tick, RoHS compliant	
Dimensions (L X W X H)		76 x 74.9 x 54.3 mm / 2.99 x 2.95 x 2.14 in (without lens)	
Weight		321 g / 0.71 lb	
Power over Ethernet			
PoE Standard		IEEE 802.3af Power over Ethernet / PSE	
PoE Power Supply Type		End-Span	
PoE Power Output		Per Port 48V DC, 350mA. Max. 15.4 watts	
Web Interface			
Installation Management		Web-based configuration	
Maintenance		Firmware upgrade through Web Browser	
Access from Web Browser		Camera live view, video recording, change video quality, bandwidth control, image snapshot, digital I/O control, audio, Picture in Picture, Picture and Picture, Privacy Mask, Visual Automation, Tampering Alarm	
Language		Czech / Danish / English / French / German / Hebrew / Hungarian / Italian / Japanese / Polish / Portuguese / Russian / Serbian / Simplified Chinese / Spanish / Traditional Chinese	
Applications			
Network Storage		GV-NVR, GV-System	
3G Mobile Phone		Built-in player for 3GPP / ISMA	
Live Viewing		IE , GV-MultiView	
CMS Server support		GV-Control Center, GV-Center V2, GV-VSM, GV-GIS	

Note: Specifications are subject to change without notice.