A·EGIS 9000 PLUS SERIES
MULTI TENANT DEDICATED TELEPHONE ENTRY SYSTEM

- Up to 2000 tenants
- Up to 3500 cards and access codes
- Programming:
  - Local via Keypad or RS232
  - Remote via dial-up modem
- Programming and Data Management with AeGIS Management Software
- Event recording with 1200 events buffer.
- 2 x 16 Electronic Liquid Crystal Display (LCD)
- Two relays
- Non-Volatile Memory
- Auto Unlock Timer, Time Zones, and Holiday Time Zones
- Optional 26-Bit Wiegand Reader
- Indoor or outdoor, surface and full-flush mount
- Brushed Stainless Steel Face   *Warranty: 24 months*

SPECIFICATIONS

POWER INPUT: 12VAC/40VA (supplied) or 12-VDC/40VA with battery backup charging circuit.
CURRENT CONSUMPTION: 700mA idle, 900mA operating.
OPERATING ENVIRONMENT: 32°F to 140°F. Heater is required if the temperature is below 32°F.
NIGHT LIGHT: Super Bright Light Emitting Diode (LED).
COMMUNICATION: 1200 Baud Modem, RS-485 and RS-232.
CONSTRUCTION: 16 Gauge Cold Rolled Steel back box with enamel finished and Brushed Stainless Steel Faceplate

MOUNTING: Surface and full-flush.
DIMENSIONS:
Surface 13-9/16"(H) x 11-1/4"(W) x 3-3/4"(D)
Full-flush 13-7/8" (H) x 11-9/16"(W) x 3-3/4" (D)
MOUNTING RING FULL-FLUSH (FFM9 is included):
Inside 13-3/4" (H) x 12" (W) x 3-11/16" (D)
Outside 18" (H) x 15-5/8" (W)
SHIPPING WEIGHT: 16 lb - 21 lb

See quick guide or manual for further specifications

ORDERING PART

Surface Mount	Full-flush Mount
9600CR25P	**9600CR25FFP**
600 tenants 25000 cards/codes	600 tenants 2500 cards and/or codes
92KCR35P	**92KCR35FFP**
2000 tenants 3500 cards/codes	2000 tenants 3500 cards and/or codes

ACCESSORIES

26-Bit Wiegand Proximity Readers and cards
UWCR Wiegand Proximity Reader.
UISO credit card size (passive card)
UCLAM Clam Shell (passive card)
UFOB Key Fob (passive fob)
26-Bit Wiegand Radio Receiver and Transmitters
AWRR Radio Reader Receiver.
AFOBT Single Button Keyfob Transmitter.
AFOBT2 Two Button Keyfob Transmitter.
AHHT Single Button Handheld Transmitter.
AHHT2 Two Button Handheld Transmitter.
Satellite Systems
USCR RS-485 Satellite Card Reader
USKP RS-485 Satellite Keypad
UMCK RS-485 Master Card Reader/Keypad

UCRM 26 Bit Wiegand RS-485 Controller Module
Video Package
AVPC AeGIS Color Camera Package.
Pedestal Mounting Post, Adapter Plate and Mounting Ring
UPM1S Standard Single Arm (42"H, 5"x5" base)
UPM4S Standard Single Arm (47"H, 5"x5" base)
UPM1L Large Single Arm (47"H, 8"x8" base)
UPM6L Large Single Arm (64"H, 8"x8" base)
UPM8L Large Single Arm (84"H, 8"x8" base)
UPM2 Double Vertical Arm (44"/84"H, 8"x8" base)
UPM5 Double Horizontal Arm (47"H, 8"x8" base)
UPMDB64 Single Arm Direct Buriel (64"H)
UPMDB72 Single Arm Direct Buriel (72"H)

UAP09 Adapter Plate AeGIS 9000P Series
UPM12E 12" Expansion Arm use for all UPM
Miscellaneous Accessories
FFM9 Full-flush mounting ring, included w/ system
ASP1 AC and Telephone Surge Protector.
AHP5 Heater Pad with Thermostat.
ABAT1 12VDC 4.5 Ahr backup battery.
ARIGB9 Rough-in gang box.
ADIR Paper Directory with night light

Specifications subject to change without prior notice