# Common Wall Mount Dome Configurations with Canon Cameras

### DISCLAIMER:

- 1. All domes are compatible with all Canon cameras unless specified.
- 2. All required accessories for domes will be stated.
- 3. Optional accessories are listed for your convience but are not required.
- 4. For more technical support please contact Michael Kearns 516-328-4632 or Deighton Fern 516-327-2217.



#### WALL MOUNTED


MODEL

ITEM CODE

MODEL

ITEM CODE

5" A-ODW5C(OW) (1381V094) / 7" A-ODW7C(OW) (1381V094)



## DESCRIPTION:

- · Housing is made from durable ABS plastic
- · Capsule dome is made from polycarbonate
- 24V AC heater and blower to maintain operating environment (-4°F ~ 104°F)
- IPX4 or IP66 selectable IP rating

## **PENDANT MOUNTED**


MODEL

ITEM CODE

MODEL

ITEM CODE

5" A-ODW5C(OW) (1381V094) / 7" A-ODW7C(OW) (1381V094)



## REQUIRED ACCESSORIES:

- A-CM100NPT: 1.5" NPT Ceiling Mount
- A-CP100NPT: 1.5" NPT Coupling

### DESCRIPTION:

- · Housing is made from durable ABS plastic
- · Capsule dome is made from polycarbonate
- 24V AC heater and blower to maintain operating environment (-4°F ~ 104°F)
- IPX4 or IP66 selectable IP rating

### **POLE MOUNTED**


MODEL

ITEM CODE

MODEL

ITEM CODE

5" A-ODW5C(OW) (1381V094) / 7" A-ODW7C(OW) (1381V094)



## **REQUIRED ACCESSORIES**:

• A-BK3S: Pole Mount Adapter & 59" Non Tool Stainless Belt (Min Pole Dia. 4")

## DESCRIPTION:

- · Housing is made from durable ABS plastic
- Capsule dome is made from polycarbonate
- 24V AC heater and blower to maintain operating environment (-4°F ~ 104°F)
- IPX4 or IP66 selectable IP rating

## **OPTIONAL ACCESSORIES**

- A-CM100: Ceiling Mount Narrow
- A-RCP5T: 5" Tinted Capsule
- A-RCP7T: 7" Tinted Capsule

## REQUIRED ACCESSORIES when using the VB-C50iR /& VC-C50iR

- A-VC50BRK: Adapter Bracket (only for the VC-C50iR)
- A-PS2412S: 24V AC 12V DC Converter (for non-PoE cameras)

## Common Wall Mount Dome Configurations with Canon Cameras

### DISCLAIMER:

- 1. All domes are compatible with all Canon cameras unless specified.
- 2. All required accessories for domes will be stated.
- 3. Optional accessories are listed for your convience but are not required.
- 4. For more technical support please contact Michael Kearns 516-328-4632 or Deighton Fern 516-327-2217.




#### **CORNER MOUNTED**

MODEL ITEM CODE

\_ ITEM CODE

5" A-ODW5C(0W) (1381V094) / 7" A-ODW7C(OW) (1381V094)



### REQUIRED ACCESSORIES:

• A-CM3: Corner Mount Adapter

### DESCRIPTION:

- Housing is made from durable ABS plastic
- Capsule dome is made from polycarbonate
- 24V AC heater and blower to maintain operating environment (-4°F ~ 104°F)
- IPX4 or IP66 selectable IP rating

#### **OPTIONAL ACCESSORIES**

- A-CM100: Ceiling Mount Narrow
- A-RCP5T: 5" Tinted Capsule
- A-RCP7T: 7" Tinted Capsule

## REQUIRED ACCESSORIES when using the VB-C50iR /& VC-C50iR

- A-VC50BRK: Adapter Bracket (only for the VC-C50iR)
- A-PS2412S: 24V AC 12V DC Converter (for non-PoE cameras)

## HIGH HEAT ENVIRONMENT


MODEL

ITEM CODE

MODEL

ITEM CODE

5" A-ODW5SCS(0W) (1381V096) / 7" A-ODW7CS(OW) (1381V099)



## DESCRIPTION:

- Housing is made from durable ABS plastic
- Capsule dome is made from polycarbonate
- 24V AC heater and blower to maintain operating environment (-4°F ~ 104°F)
- IPX4 or IP66 selectable IP rating