Higher Resolution + Panoramic Field of View = Greater ROI

An area typically requiring multiple PTZ cameras or multiple fixed cameras can be covered with a single panoramic camera. It delivers comprehensive coverage with forensic detail - all without the need for an operator or control software. A highly costefficient solution, SurroundVideo® panoramic cameras virtually obsolete the need and related expense of PTZ cameras.


For applications that require critical detail like license plate recognition, combine the panoramic camera with single sensor megapixel cameras at entrance and exit




Compliant H.264 Compression

- Compliant implementation of H.264 allows full frame rates and full resolution without sacrificing image quality
- H.264 and MJPEG dual compression support with simultaneous streaming
- Decreases the CPU load both at the client (decompression) side and the server/storage side
- Lower bandwidth and storage relative to MJPEG
- Bit rate control to maintain desired bandwidth and storage size
- Real Time Streaming Protocol (RTSP) allows for compatibility with media players such as Apple QuickTime®, VLC and others

H.264 Decompression (example)





2MP with live video in **MJPEG** 2MP with live video in **H.264**


Privacy Mask





Allows the ability to select multiple regions of an arbitrary shape and block the video. It is supported by both HTTP and TFTP protocols, and features an on-board web interface.

Extended Motion Detection





Offers a higher granularity grid of 1,024 distinct motion detection zones in contrast to the 64 zones in previous versions.

Product Comparison

Model	Sensor	Resolution	Max Frame Rate @ 1/4 Resolution	Max Frame Rate @ Full Resolution	Minimum Illumination	H.264	MJPEG	Day/Night	IP66	Vandal Resistant	Heater/Blower Option
AV8185DN	4x2MP	6400x1200	22 fps	6 fps	Color: 0.2 Lux Day/Night: 0 Lux, IR Sensitive	•	•	•	•	•	•
AV8365DN	4x2MP	6400x1200	22 fps	6 fps	Color: 0.2 Lux Day/Night: 0 Lux, IR Sensitive	•	•	•	•	•	•
AV8185C0	4x2MP	6400x1200	22 fps	6 fps	Color: 0.2 Lux	•	•		•	•	•
AV8365C0	4x2MP	6400x1200	22 fps	6 fps	Color: 0.2 Lux	•	•		•	•	•
AV20185DN	4x5MP	10240x1920	11 fps	3.5 fps	Color: 0.3 Lux / 0.15 Lux (binned) Day/Night: 0 Lux, IR Sensitive	•	•	•	•	•	•
AV20365DN	4x5MP	10240x1920	11 fps	3.5 fps	Color: 0.3 Lux / 0.15 Lux (binned) Day/Night: 0 Lux, IR Sensitive	•	•	•	•	•	•
AV20185C0	4x5MP	10240x1920	11 fps	3.5 fps	Color: 0.3 Lux / 0.15 Lux (binned)	•	•		•	•	•
AV20365C0	4x5MP	10240x1920	11 fps	3.5 fps	Color: 0.3 Lux / 0.15 Lux (binned)	•	•		•	•	•

Configurations



In Ceiling Mount (shown with AV8365DN)



(shown with AV8185DN)

Accessories



SV-FMA

Flush Mount Adapter

SV-EBA

Electrical Box Adapter





MD-PMA Pole Mount Adapter



SV-WMT

Wall Mount

Junction Box Adapter



MD-CRMA



Corner Mount Adapter

Enhanced Low Light Performance





The latest additions to the SurroundVideo® family are the new Day/Night panoramic cameras which provide comprehensive field of view and excellent forensic detail in low light. The cameras' Day/Night switchers simultaneously transition for enhanced low light or night time performance based on the least illuminated sensor. For extreme low light environments, IR illumination can be added.







180° and 360° Coverage with Exceptional Resolution - SurroundVideo®

H.264 SurroundVideo® Day/Night series megapixel cameras provide an all-in-one solution for wide area video surveillance. Available in 180° and 360° panoramic configurations, SurroundVideo® cameras feature 8 and 20 megapixel panoramic dual encoder (H.264 and MJPEG) cameras housed in a vandal resistant IP66 dome. A single SurroundVideo® panoramic camera can replace multiple conventional cameras with the ability to zoom into multiple regions of interest. Their return on investment is easily measured any way you view it.

Highlighted Features:

- 8 and 20 megapixel with 180° and 360° panoramic configurations
- All-in-one vandal resistant H.264/MJPEG Day/Night solution
- Easily adjustable 2-axis gimbal
- +/- 10° mechanical sensor tilt adjustment (AV8365DN)
- Privacy masking for multiple regions
- Extended motion detection grid
- Superior low light performance
- 2 megapixel resolution (1600 x 1200) per sensor 6400 x 1200 total
- 5 megapixel resolution (2560 x 1920) per sensor 10240 x 1920 total
- IP66 weatherproof standard, IK10 impact resistance
- Various mounting options (surface, wall, pendant, in-ceiling)

Corporate Headquarters

Arecont Vision 425 East Colorado Street, 7th Floor Glendale, CA 91205 +1 (818) 937-0700 www.arecontvision.com



North America:

avsales@arecontvision.com

Latin America:

latam.sales@arecontvision.com

Asia Pacific:

Asia Pacific: apac.sales@arecontvision.com

Australia / New Zealand: anz.sales@arecontvision.com

China:

china.sales@arecontvision.com

Malaysia, Indonesia, Vietnam, Philippines, Singapore, Thailand: seasia.sales@arecontvision.com

Taiwan, Korea, Japan, Hong Kong, Mongolia: eastasia.sales@arecontvision.com

Europe:

Europe: europe.sales@arecontvision.com

Belgium, Netherlands, Luxemburg:

benelux.sales@arecontvision.com

Denmark, Finland, Iceland, Norway, Sweden: nordic.sales@arecontvision.com

Eastern Europe:

easterneurope.sales@arecontvision.com

France:

france.sales@arecontvision.com Germany, Austria, Switzerland: dach.sales@arecontvision.com

italy.sales@arecontvision.com

Russia:

russia.sales@arecontvision.com

Spain and Portugal: iberia.sales@arecontvision.com

United Kingdom: uk.sales@arecontvision.com

| Middle East / Africa :

israel.sales@arecontvision.com

Middle East / North Africa: mena.sales@arecontvision.com Central & South Africa: africa.sales@arecontvision.com



Arecont Vision is the leading manufacturer of highperformance megapixel IP cameras and associated software. All Arecont Vision products are made in the USA.



megapixel technology... beyond imagination www.arecontvision.com • 1-877-CAMERA-8



SurroundVideo® Megapixel IP Cameras



