



ADC824UL and ADC1624UL

CAMERA AND ACCESSORY POWER SUPPLIES



SPECIFICATIONS

Model Numbers

ADC824ULPower Supply, 8 Outputs, 120 VAC to 24 VAC
ADC1624ULPower Supply, 16 Outputs, 120 VAC to 24 VAC

Operational

Indicator LEDsPower on
PowerOn/off switch

Electrical

Input Voltage115 VAC @ 50/60 Hz
Input Current9A (ADC824UL), 2.9A (ADC1624UL)

Mechanical

Wall Mounting OptionsConcrete, wood, and sheet rock
Dimensions (H x W x D)
ADC824UL203 x 184 x 89 mm (8 x 7.25 x 3.5 in)
ADC1624UL343 x 330 x 83 mm (13.5 x 13.0 x 3.25 in)

Environmental

EnvironmentIndoor
Operating Temperature0° to 50° C (32° to 122° F)
Storage Temperature-40° to 70° C (-40° to 158° F)
Relative Humidity0 to 95% RH (non-condensing)

Regulatory

SafetyUL2044

The ADC824UL and ADC1624UL camera and accessory power supplies are designed for powering CCTV cameras and other video accessories. They provide 24 VAC power via eight (ADC824UL) or sixteen (ADC1624UL) fused outputs. The ADC824UL provides a total of 3.5 amps continuous supply current, and the ADC1624UL provides a total of 7 amps of continuous supply current.

Features

- Input 115 VAC @ 50/60 Hz
- 24 VAC output
- Eight individually fuse protected, power limited outputs, with 3.5 amps (85 VA) total supply current (ADC824UL)
- Sixteen individually fuse protected, power limited outputs, with 7 amps (170 VA) total supply current (ADC1624UL)
- UL 2044 listed
- Output, main and inline fuses rated at 3.5 amps/250 VAC
- Built-in surge protection
- AC power LED indicator, with on/off switch
- Unit maintains camera synchronization
- Easy to install in seven simple steps

Product specifications and availability subject to change without notice.
Certain product names mentioned herein may be trade names and/or registered trademarks of other companies.