



ADSPOT

SINGLE POSITION OUTDOOR POWER SUPPLY

SPECIFICATIONS

Model Number

ADSPOT 240 VAC (field changeable to 120 VAC)
Transformer jumpers are field changeable to support either 120 VAC or 240 VAC

ADSPOT is used with any American Dynamics dome or fixed camera

Electrical

Power Source 100-120 VAC or 200-240 VAC @ 50/60 Hz
Operational Limits 90-135 VAC or 180-265 VAC @ 50/60 Hz
Input Current 1.0A/0.5A
Output 24 VAC, 2.5A max.
UL Listed Class 2
Certified Limited Power Source

Mechanical

Dimensions (H x W x D) 175 x 125 x 75 mm
(6.9 x 4.9 x 3.0 in)
Weight 3.7 kg (8.2 lbs)
Enclosure Material Impact-resistant polycarbonate
Color Light gray
Wall Mounting Options Concrete, wood or sheet rock
Mounting Area (H x W) 281 x 200 mm
(11.1 x 7.9 in)
Cover Fasteners Four captive screws
Cable Access Knockouts Eight 21 mm or 15.5 mm
(0.83 in or 0.61 in)
Four 29 mm or 23 mm
(1.14 in or 0.91 in)

Environmental

Weatherproof Standard NEMA 4, IP66
Operating Temperature -40° to 50° C (-40° to 122° F)
Storage Temperature -40° to 50° C (-40° to 122° F)
Humidity 0% to 95% RH (non condensing)

Regulatory

Safety UL 60950
CSA C22.2 No. 60950
EN60950
IEC 60950



This weather-tight box provides Class 2 LPS power to the SpeedDome® Ultra and SpeedDome Optima outdoor camera housings. It is designed for use in the harshest of outdoor environments.

Features

- Supports both 120 VAC and 230 VAC
- Weatherproof design: NEMA 4 and IP66 rated
- Small, compact design
- Euro-style terminal blocks make for quick and simple installation

Product specifications and availability subject to change without notice.
Certain product names mentioned herein may be trade names and/or registered trademarks of other companies.