

Overview



This Altronix ALTV1224C4 AC/DC Dual Output Power Supply is designed to provide both 12VDC and 24VAC outputs where a combination of both AC and DC outputs are required.

Specifications

Input:

- 115VAC 50/60 Hz, 1.52 amp.

Output:

- Four (4) individually fused outputs.
 - Two (2) fuse protected outputs @ 12VDC.
 - Two (2) fuse protected outputs @ 24VAC.
- 6 amp total output current.
 - 2 amp supply current @ 12VDC.
 - 4 amp supply current @ 24VAC.
- DC output fuses are rated @ 1 amp.
- AC output fuses are rated @ 3.5 amp.
- Filtered and electronically regulated outputs (DC outputs).
- Surge suppression (AC outputs).

Electrical:

- Operating temperature: -20° C to 49° C ambient.

Electrical (cont'd):

- BTU/Hr.:
 - 12VDC: 9 BTU/Hr.
 - 24VAC: 36 BTU/Hr.
- System AC input VA requirement: 174.8VA.

Mechanical:

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.): 13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)
- Product weight (approx.): 14.5 lbs. (6.58 kg.).
- Shipping weight (approx.): 15.4 lbs. (6.99 kg.).

Features:

- AC/DC power LED indicators.
- Power ON/OFF switch.
- Unit maintains camera synchronization.
- Ease of installation saves time & eliminates costly labor.

Enclosure Dimensions (H x W x D) (approximate):

13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

