



Overview

- These Altronix AC Wall Mount CCTV Power Supplies provide 24VAC or 28VAC distributed via sixteen (16) fuse or PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV2416600

- Sixteen (16) fuse protected outputs.
- Outputs are rated @ 3.5 amp.

ALTV2416600CB

- Sixteen (16) PTC protected outputs.
- Outputs are rated @ 2.5 amp.

Specifications

- Input 115VAC, 50/60Hz, 5.4 amp.
- 24VAC @ 28 amp (700VA) or 28VAC @ 25 amp (700VA) supply current.
- Main fuse rated @ 15 amp/32V.
- Illuminated power disconnect circuit breaker with manual reset.
- Surge suppression.
- AC power LEDs.
- Spare fuse(s) provided (all models w/primary and/or secondary fuses).
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.
- Product weight:
 - ALTV2416600: 24.2 lbs.
 - ALTV2416600CB: 24.3 lbs.
- Shipping weight:
 - ALTV2416600: 25.1 lbs.
 - ALTV2416600CB: 25.2 lbs.

Agency Approvals



Enclosure Dimensions

13"H x 13.5"W x 3.5"D

