



ALTV2416ULX, ALTV2416ULCBX **UL Listed AC CCTV Power Supply**

Rev. DSALTV2416ULX - A24F

Overview



- These Altronix AC Wall Mount CCTV Power Supplies provide 24VAC or 28VAC distributed via sixteen (16) fuse or Class 2 Rated PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV2416ULX

- Sixteen (16) fuse protected outputs.
- Outputs are rated @ 3.5 amp.

ALTV2416ULX3

ALTV2416ULX w/3-wire Line Cord.

ALTV2416ULCBX

- Sixteen (16) Class 2 Rated PTC protected outputs.
- Outputs are rated @ 2.5 amp.

ALTV2416ULCBX3

ALTV2416ULCBX w/3-wire Line Cord.

Specifications

- Input 115VAC 50/60Hz, 1.8 amp.
- 24VAC @ 7 amp (170VA) or 28VAC @ 6 amp (170VA) supply current.
- Main fuse rated @ 5 amp/250V.
- Power ON/OFF switch.
- Surge suppression.
- AC power LEDs.
- Spare fuses provided (all models w/primary and/or secondary fuses).
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.
- Product weight:
 - ALTV2416ULX: 12.6 lbs.
 - ALTV2416ULX3: 12.9 lbs.
 - ALTV2416ULCBX: 13.5 lbs.
 - ALTV2416ULCBX3: 13.8 lbs.
- Shipping weight:
 - ALTV2416ULX: 13.6 lbs.
 - ALTV2416ULX3: 13.9 lbs.
 - ALTV2416ULCBX: 14.5 lbs.
 - ALTV2416ULCBX3: 14.8 lbs.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



Canadian Standard Association



European Conformity

Enclosure Dimensions

13"H x 13.5"W x 3.5"D

