



ALTV248300UL3

Overview

ALTV248300UL3 provides 24VAC or 28VAC distributed via Eight (8) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories. Factory installed 3-wire line cord.

Specifications***Input:***

- 115VAC, 50/60Hz, 2.7 amp.

Output:

- Eight (8) fuse protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current
(1.563 amp per device, 3.5 amp max.)
or 28VAC @ 10 amp (280VA) supply current
(1.25 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 153.55 BTU/Hr.
 - 28VAC: 143.31 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 310.5VA.

Features:

- Secondary fuse rated @ 15 amp/32V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).
- Factory installed 3-wire line cord.

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
12" x 7.5" x 4.5" (304.8mm x 190.5mm x 114.3mm)
- Product weight (approx.): 11.1 lbs (5.1 kg).
- Shipping weight (approx.): 12.1 lbs (5.5 kg).

Agency Approvals

UL Listed for Commercial CCTV Equipment
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,
Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D approximate):
12" x 7.5" x 4.5" (304.8mm x 190.5mm x 114.3mm)

