



ALTV615DC48ULM, ALTV615DC48UCBM **UL Listed DC CCTV Power Supply**

Rev. DSALTV615DC48ULM - B23F

Overview



- These Altronix DC Wall Mount CCTV Power Supplies provide 6VDC to 15VDC distributed via eight (8) Class 2 Rated fuse or PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV615DC48ULM

- Eight (8) Class 2 Rated fused protected power limited outputs.
- Outputs are rated @ 3.5 amp.

ALTV615DC48ULM3

- ALTV615DC48ULM w/factory installed 3-wire line cord.

ALTV615DC48UCBM

- Eight (8) Class 2 Rated PTC protected power limited outputs.
- Outputs are rated @ 2.5 amp.

ALTV615DC48UCBM3

- ALTV615DC48UCBM w/factory installed 3-wire line cord.

Specifications

- Input 115VAC 50/60Hz, .9 amp.
- 6VDC to 15VDC adjustable @ 4 amp total supply current.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.
- Power ON/OFF switch.
- AC and DC power LEDs.
- Spare fuses provided (on fuse protected models).
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

- Product weight:
 - ALTV615DC48ULM: 7.6 lbs.
 - ALTV615DC48ULM3: 7.9 lbs.
 - ALTV615DC48UCBM: 7.6 lbs.
 - ALTV615DC48UCBM3: 7.9 lbs.
- Shipping weight:
 - ALTV615DC48ULM: 8.2 lbs.
 - ALTV615DC48ULM3: 8.5 lbs.
 - ALTV615DC48UCBM: 8.2 lbs.
 - ALTV615DC48UCBM3: 8.5 lbs.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions

8.5"H x 7.5"W x 3.75"D

