



AM192-series Entrance Panel

IL318 Specification Sheet

Tek-ENTRY® Apartment Entry System • Rev. 11 - 12/2013

Features

- Mounts on fully-enclosed back box with knockouts
- Modular design
- Hands-free loud-speaking
- Weather-resistant speaker
- Individually replaceable name holders (black flame retardant polycarbonate plastic)
- Self-wiping push button switches
- Slim-line surface-mount option
- Simple installation

Description

The AM192 Series Entrance Panel is a modular series for use with TekTone® apartment intercom stations.

Panels are equipped with a voice-frequency response speaker and can accommodate up to 18 push buttons per panel. For more than 18 apartments, the AM192 is used in conjunction with the AM190-series push button panels.

Pressing the button corresponding to the desired name and apartment number causes a buzzing at the apartment station. The resident may then converse with the caller. Controlled entry is permitted by push button operation of the electric door release, if desired. AM192 Panels with 4 to 10 buttons are available with postal option.

Specifications

Dimensions:	Height:	16.5"	(413 mm)
	Width:	4" each panel	(100 mm)
Push buttons:	Individually replaceable type with self-wiping contacts.		
Speaker:	2.5" (64 mm) voice frequency response.		
Construction:	Modular extruded, anodized aluminum panel with high-impact grill.		
Mounting:	OF190-series frame and OH190-series housing for flush mounting. For surface mounting, use OF190-series Frame.		



AM192-series Entrance Panel

Required Components

IR-series Apartment Intercom Stations
OF190-series Frame
OH190-series Housing
PK543A Apartment Intercom Amplifier
SS102A or SS106 Transformer

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3

TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)