ANT-5814dp

Manufactured from the highest quality materials superior electrical to ensure performance, mechanical durability and longevity from the harsh elements of weather. Meet your application demands by choosing antenna to increase your signal strength and improve video quality.

ADVANTAGES

- Ideal for permanent, long range outdoor equipment mounted applications
- "Plug & Play" and ready to install
- Improve video quality and signal strength
- Dramatically increase transmission range
- All-Weather construction
- Low Profile Design
- Two Year Limited Warranty



SPECIFICATIONS

| FREQUENCY RANGE | 5250 - 5900 GHz |
|-------------------------|--|
| ANTENNA GAIN | 14 dBi |
| VSWR (RETURN LOSS) | <1.5:1 |
| POLARIZATION | Vertical - Linear |
| H-PLANE BEAMWIDTH | 32 Degrees |
| E-PLANE BEAMWIDTH | 32 Degrees |
| IMPEDANCE | 50 Ohms |
| ANTENNA INPUT CONNECTOR | N – Female |
| CONSTRUCTION | All-Weather UV Protected |
| WIND LOADING RATING | 100 MPH |
| DIMENSIONS | 4.6" x 4.8" x 1.26" |
| WEIGHT | 139g or 4.9 oz |
| MOUNTING BRACKETS | Included – Universal Pole Mounting Bracket |
| INCLUDES | 6 Feet x 0.5" Low loss Microwave Cable – SMA-Male / N-Male |

KIT INCLUDES

- 14 dBi ALL WEATHER ANTENNA
- 6' LOW LOSS MICROWAVE CABLE
- UNIVERSAL POLE MOUNTING BRACKET
- TWO YEAR LIMITED WARRANTY







US Office: 1711 Cudaback Avenue, Niagara Falls, NY USA 14303 **Canadian Office:** 1016C Sutton Drive, Unit 6, Burlington, ON Canada L7L 6B8

Toll Free: 1.888.379.2666 Tel: 905.336.9665 Fax: 905.336.9662