



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: B122-000

HDMI Signal Extender (1080p @ 24Hz) (HDMI F/F)

Highlights



- Extend a 1080p (24Hz) HDMI signal up to 150 ft. from the source
- When extending a 1080p (24Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD
- 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable
- Supports DTS-HD, Dolby True HD and 7.1 Channel Surround Sound Audio
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

Tripp Lite's B122-000 HDMI Signal Extender increases the distance a 1080p (24Hz) signal can be transmitted beyond the recommended 16 ft. (5 m.). It supports video resolutions up to 1080p, and a maximum distance of 150 ft. from the source. Use P568-Series HDMI cables in most applications. When extending a 1080p (24Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD. (Lengths over 100 ft. are available from Tripp Lite as a custom order) 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable. Simply connect the longer cable between the source and the B122-000, and the shorter cable (16 ft. or less) between the adapter and the monitor. Software or drivers are not required. HDCP compliant. Compatible with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Package Includes

- B122-000 HDMI Signal Extender
- External Power Supply (Input: 100-240V, 50/60Hz, 0.5A Output: 5V, 0.5A)
- Owner's Manual

Features

- Extend a 1080p (24Hz) HDMI signal up to 150 ft. from the source
- Use P568-Series HDMI cables in most applications
- When extending a 1080p (24Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD. (Lengths over 100 ft. are available from Tripp Lite as a custom order)
- 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable
- Supports DTS-HD, Dolby True HD and 7.1 Channel Surround Sound Audio
- HDCP compliant
- No software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
Display Style	Signal Booster
CONNECTIONS	

Connector A	 HDMI (FEMALE)
Connector B	 HDMI (FEMALE)
Number of Connectors	2
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

Related Items

Required Products

Related Model	Description	Qty.
P568-006	6-ft. HDMI Gold Digital Video Cable (HDMI M/M)	1
P568-010	10-ft. HDMI Gold Digital Video Cable (HDMI M/M)	1
P568-016	16-ft. HDMI Gold Digital Video Cable (HDMI M/M)	1
P568-025	25-ft. High Speed v1.3 HDMI Digital Video Gold Cable (HDMI M/M)	1
P568-050	50-ft. High Speed v1.3 HDMI Digital Video Gold Cable (HDMI M/M)	1
P568-100-HD	100-ft. 24AWG High Definition High Speed HDMI Digital Video Gold Cable (HDMI M/M)	1

Optional Products

Related Model	Description	Qty.
B122-000-60	HDMI Signal Extender (1080p @ 60Hz), HDMI F/F	1
B123-001	1-ft. HDMI Active Signal Extender Cable (HDMI M/F)	1
B123-001-60	1-ft. HDMI Active Signal Extender Cable (HDMI M/F)	1
B125-150	HDMI over Dual Cat5 Extender	1
B125-101-60	HDMI over Dual Cat6 60Hz Extender Kit	1
B126-1A1	HDMI Over Cat5 Active Extender Kit	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.triplite.com/en/products/model.cfm?txtModelID=3503.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.