



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@triplite.com

Model #: B123-001

1-ft. HDMI Active Signal Extender Cable (HDMI M/F)

Highlights



- Extend a 1080p (24Hz) HDMI signal up to 150 ft. from the source
- Use P568-Series HDMI cables in most applications
- When extending a 1080p (24Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD
- 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

Tripp Lite's B123-001 HDMI Signal Extender increases the distance a 1080p (24Hz) signal can be transmitted beyond the recommended 16 ft. (5 m.). It supports video resolutions up to 1080p, and a maximum distance of 150 ft. from the source. Use P568-Series HDMI cables in most applications. When extending a 1080p (24Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD. (Lengths over 100 ft. are available from Tripp Lite as a custom order) 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable. Simply connect the longer cable between the source and the B123-001, and then connect the built-in cable to the monitor. Software or drivers are not required. HDCP compliant. Compatible with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Applications

- When an HDTV display is located a long distance from the video source.

Package Includes



- HDMI Active Extender Cable, M/F, 1 ft.

Features

- Extend a 1080p (24Hz) HDMI signal up to 150 ft. from the source
- Use P568-Series HDMI cables in most applications
- When extending a 1080p (24Hz) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD. (Lengths over 100 ft. are available from Tripp Lite as a custom order)
- 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable
- HDCP compliant
- No software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
Display Style	Signal Booster
INPUT	
Cable Length (ft.)	1

Cable Length (m)	0.30
CONNECTIONS	
Connector A	 HDMI (MALE)
Connector B	 HDMI (FEMALE)
Number of Connectors	2
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

Related Items

Required Products

Product Type	Related Model	Description	Qty.
Audio/Video Cables	P568-025	25-ft. High Speed v1.3 HDMI Digital Video Gold Cable (HDMI M/M)	1
Audio/Video Cables	P568-100-HD	100-ft. 24AWG High Definition High Speed HDMI Digital Video Gold Cable (HDMI M/M)	1
Video Cables & Adapters	P568-050	50-ft. HDMI Digital Video Gold Cable (HDMI M/M)	1

Optional Products

Product Type	Related Model	Description	Qty.
Extenders/Signal Boosters	B122-000	HDMI Signal Extender (24Hz) (HDMI F/F)	1
Extenders/Signal Boosters	B122-000-60	HDMI Signal Extender (1080p @ 60Hz), HDMI F/F	1
Extenders/Signal Boosters	B125-101-60	HDMI over Dual Cat6 60Hz Extender Kit	1
Extenders/Signal Boosters	B125-150	HDMI over Dual Cat5 Extender	1
Extenders/Signal Boosters	B126-1A1	HDMI Over Cat5 Active Extender Kit	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3739.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.