

5 Megapixel Day & Night Vandal Dome Network Camera

VD-501Af


HDTV 1080p/720p • Cost Effective




- Megapixel High Resolution Outdoor Vandal Dome Camera
- HDTV Quality (Full HD 1080p @ 25fps Streaming)
- Cost Effective/ Full Features Camera
- Easy Installation Dome Type Camera, Suitable for Project
- Build In IR Leds, effective up to 10 m
- MPEG-4, MJPEG and H.264 Triple Codec Compression
- **Intelligent Multi-Profile Sensor Management®** for Different Environments
- Removable IR-cut Filter / Auto Light Sensor for Day and Night
- 1 DI/DO for External Alarm and Sensor Device
- Two-way Audio
- IK10 Vandal Proof and IP67 Weather Proof Outdoor Enclosure
- Power over Ethernet / DC 12V Power Input



Photo Indication & Dimension Diagram



- | | |
|--|---|
| 1 LEDs | 5 Tilt Screw |
| 2 RJ45 Connector
(For Ethernet and PoE) | 6 Reset Button |
| 3 Conduit Plug and Hole | 7 Terminal Block (for Audio in/out, DIDO) |
| 4 Fixed Lens | 8 Terminal Block (for Power DC12V, 1A) |



Camera

Hardware System	CPU: 533 MHz Flash: 32M RAM: 256M DDR
Image Sensor	Sensor Type : 1/2.5" CMOS Sensor Sensor Resolution : 2592 x 1944 pixel
Minimum Illumination	0 lux (IR ON, B/W) 2 lux (F1.6, Color) S/N ratio: 38.1dB
IR Illuminators	Built -in IR Illuminators, effective up to 10 meters IR LED: 12pcs IR wavelength: 850nm
Lens	Lens Type: Board Lens Focal Length: f= 4mm F No.: 1.6 View Angle: (H): 90°/ (V): 67°/ (D): 112°
Day & Night ICR	Triggered by Light sensor, Scheduling, Digital Input

Video

Compression Streaming	H.264 / MPEG4 / MJPEG Simultaneous multiple streams
Video Setting	Multi-Profile Image Management: Day/ Night/ Sunset/ User 1/ User 2 Auto Exposure Control Manual Exposure Control: 1/20000~1/5s Manual Gain Control: 1X ~ 32X Manual White Balance Control: 2000K~7000K
Image Resolution	5M : 2592x1944 @ 9fps (5M supports MJPEG only) 4M : 2304x1728 @ 14fps 3M : 2048x1536 @ 18fps 2M (1080p Full HD) : 1920x1080 @ 25fps 1M (720p HDTV) : 1280x720@ 25fps

Events and Alarm Management

Events	Motion Detection/ Schedule/ Audio Detection/ Digital Input
Alarm	Stream/Snapshot to FTP/Email/ Samba/SD-Card/HTTP/Email Notification/ Digital Output

Work Best With

Camera Accessories Options



L-WM-01
Camera Bracket



POE16U
High Power PoE Injector

Audio

Audio Streaming	2-way Audio Support
Audio Compression	G.711, AMR (8 kHz, Mono, PCM)

Audio Input/ Output	Line In/ Out
----------------------------	--------------

General

Communication	Ethernet : one 10/100Mbps RJ-45 Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, RTP, RTSP, RTCP, IPv6
Power Input/ Operating Temperature	PoE 802.3 af/ DC12V 1A : -20°C ~ 50°C (-4°F ~122°F)
Max. Power Consumption	PoE 802.3 af: 8 watts DC 12V 1A: 6 watts
Environment	Water Proof: IP67 Operating Humidity : 10% ~ 80%
Dimension	113.75 (D) mm X 144.25(H) mm
Weight	900g/ 1.99 lb
Housing	Weather-proof (IP67) Vandal-proof (IK10)
Certification	FCC, CE, IK10
Viewing System Requirements	OS: Microsoft Windows 7/Vista/XP/2000 Browser: Mozilla Firefox, Internet Explorer 7/8 or above, Safari, Google Chrome Cell Phone: 3GPP player Real Player: 10.5 or above Quick Time: 6.6 or above VLC
Warranty	Limited one-year warranty

Network Equipment Options



DWRT-600N
Dual Band Wireless Router



PS-588I
8-port 10/100M PoE Fast Ethernet Switch