

## C-19



An excellent and affordable 19" display for home and office environments where quality, reliability and price are important considerations.

---

The valuable C-19 delivers the high image clarity and outstanding display performance that is well suited for the demands of modern office and home applications. Featuring 60,000:1 dynamic contrast ratio and built-in speakers, the slim modern design and convenient VESA compatible wall mounts make the C-19 a perfect value choice for home and office environments.

---

- > Slim and sleek design
- > Economical and durable concern
- > Fast 3ms response time
- > Crisp 60,000:1 dynamic contrast ratio
- > Built-in speakers
- > Auto-adjustment for optimal viewing
- > Kensington® security socket
- > VESA standard wall mount
- > WEEE, RoHS, REACH certified

# C-19

## Specifications

## C-19

|                      |                             |                                                                              |
|----------------------|-----------------------------|------------------------------------------------------------------------------|
| Panel                | Panel Type                  | TFT LCD                                                                      |
|                      | Panel Size                  | 19.0" (482 mm)                                                               |
|                      | Max. Resolution             | SXGA 1280 x 1024                                                             |
|                      | Pixel Pitch                 | 0.294 mm                                                                     |
|                      | Brightness                  | 250cd/m2 (Typical)                                                           |
|                      | Contrast Ratio              | 60,000:1 (DCR)                                                               |
|                      | Surface Treatments          | Hard Coating (3H),<br>Anti-glare treatment                                   |
|                      | Viewing Angle (H/V)         | 170°/160° (Typical)                                                          |
|                      | Display Colour              | 16.7M                                                                        |
|                      | Response Time               | 3ms (GTG)                                                                    |
| Frequency (H/V)      |                             | H: 30 kHz - 83 kHz<br>V: 55 Hz - 75 Hz                                       |
| Input                | Analogue                    | 15-Pin D-Sub                                                                 |
|                      | Digital                     | 24-Pin DVI-D                                                                 |
| Audio                | Audio In                    | 3.5mm Audio Line-in                                                          |
|                      | Speaker                     | 1W x 2                                                                       |
| Power                | AC-DC Adaptor               | Internal                                                                     |
|                      | Power Consumption           | AC 100 - 240 V, 50 - 60 Hz<br>< 28 W (On)<br>< 1 W (Stand-by)<br>< 1 W (Off) |
| Plug & Play          | VESA                        | DCC 2B                                                                       |
| Operating Conditions | Temperature                 | 0 °C ~ 40 °C                                                                 |
|                      | Humidity                    | 10% ~ 85%                                                                    |
| Storage Conditions   | Temperature                 | -25 °C ~ 55 °C                                                               |
|                      | Humidity                    | 5% ~ 85%                                                                     |
| Mounting             | VESA FPMPI                  | Yes (100 mm)                                                                 |
| Tilt                 | Tilt                        | -5° ~ +20°                                                                   |
| Dimensions           | Product (W x H x D)         | 410 x 412 x 210 mm<br>(16.1" x 16.2" x 8.3")                                 |
|                      | Packaging (W x H x D)       | 470 x 451 x 124 mm<br>(18.5" x 17.8" x 4.9")                                 |
| Weight               | Product Weight              | 4.2 kg (9.2 lbs)                                                             |
|                      | Packaged Product Weight     | 5.6 kg (12.3 lbs)                                                            |
| Regulation Approval  | Certifications & Compliance | FCC, CB, CE, GOST-R, WEEE, RoHS, REACH                                       |
| Accessories          | Supplied                    | CD ROM (user manual), 15-Pin D-Sub cable, audio cable, AC power cord         |



Sleek design with anti-glare display panel for superior viewing comfort



VESA standard wall mount allows for secure mounting almost anywhere



Built-in speakers provide easy access to multimedia applications