

The new CCR-900 Video Receiver is easier and more reliable to use. It offers rock-solid frequency stability by automatically locking onto you 900MHz VideoComm transmitter without manual adjusting or tuning.

## FEATURES

- 3 User selectable channels – No Tuning
- Convenient signal strength indicator
- Power On/Off Switch with LED indicator
- Convenient Terminal Block connectors for various power supply input options
- One year limited warranty



SPECIFICATION	DETAILS
Frequency (3 Channels Available)	906 MHz, 916 MHz, or 924 MHz
Frequency Selection	Switchable – no tuning – Fixed
Frequency Stability	Micro Processor Controlled
Removable Antenna Included	6" Omnidirectional Rubber Duck
Antenna Connector	TNC Female
Video Compatibility	NTSC (PAL format see CCR-900P)
Video Output/Connector	75 Ohms – 1 Volt P-P / BNC Female
Audio Output/Connector	600 Ohms – 1 Volt P-P / RCA Female
Temperature Range	-20°F to 150°F, NOT Weatherproof
Reverse Polarity Protected	Yes
Power Supply	Terminal Block Input 6.4 to 24 Volts DC
Current Consumption	200mA @ 6.4 Volts DC 70mA @ 24 Volts DC
Dimensions	5.37" x 4.25" x 1.44"
FCC/IC Approved	Yes