

EasyView™ Lite Series

High Resolution, 550 TV Lines, Indoor Dome Camera

CD-H2N • CD-H39N

NTSC



CD-H2N



CD-H39N



KEY FEATURES

- 1/3" CCD Sensor
- 550 TV Lines
- 2.9mm Fixed Lens, or 3.8mm~9.5mm, DC Auto Iris Lens
- 0.1 Lux
- 12VDC or 12VDC/24VAC Dual Voltage

LENS OPTION

- 2.9mm Fixed Lens - CD-H2N (12VDC)
- 3.8~9.5mm, DC Auto Iris Lens - CD-H39N (12VDC/24VAC Dual Voltage)

CONSTRUCTION

- 3" Polycarbonate Bubble
- 3-Axis Gimbal
- Ivory or Black Plastic Housing (Optional)
- Compact Size

AVAILABLE MODELS

- CD-H2N-I (Ivory Housing) - 2.9mm Fixed Lens
- CD-H2N-B (Black Housing) - 2.9mm Fixed Lens
- CD-H39N-I (Ivory Housing) - 3.8mm~9.5mm, DC Auto Iris Lens
- CD-H39N-B (Black Housing) - 3.8mm~9.5mm, DC Auto Iris Lens

TECHNICAL SPECIFICATIONS


Technical Specifications	CD-H2N	CD-H39N
Video Format	NTSC/PAL	
Image Sensor	1/3" CCD	
Horizontal Resolution	550 TV Lines	
Day/Night Functionality	No	
Lens Type	Fixed 2.9mm	Vari-focal 3.8mm-9.5mm
Angle of View	120°	95.5°(W) ~ 37.3°(T)
Sync System	Internal	
Effective Pixels	768(H) x 494(V)	
Scanning System	525 Lines, 2:1 Interlaced	
Electronic Shutter	1/60 ~ 1/100,000 sec.	1/60 sec.
Main Video Output	1.0 Vp-p Composite, 75 ohm	
Service Monitor Output	1.0 Vp-p Composite, 75 ohm	
Minimum Illumination	0.1 Lux	
S/N Ratio	More than 48dB (AGC Off)	
General Information	CD-H2N	CD-H39N
Operating Temperature	23°F ~ 113°F	
Operating Humidity	Within 90% RH	
Power Consumption	500 mA	
Input Voltage	12VDC	12VDC/24VAC Dual Voltage

*specifications are subject to change without any prior notice.


3-AXIS GIMBAL, SIMPLY MOUNT AND POINT

All EasyView™ Lite dome camera gimbal has the ability to rotate, tilt, and pan for easy camera placement. Simply mount the camera to the ceiling, wall, or under the eaves on the exterior of building or a house and point the camera to the area you want to surveillance.


- 1 Rotation 355°
- 2 Tilting 90°
- 3 Panning 355°



1 Rotation 355°



2 Tilting 90°



3 Panning 355°

DIMENSIONS

Unit: Inches (mm)

