

NUVICO EasyView™

Indoor Color Dome Cameras

CD-WD Series / High Resolution • WDR • Day/Night

Patent
Pending



Flush Housing with Surface Mount Plate



Flush Mount Housing



Wall Mount

Key Features

- 1/3" CMOS Sensor
- High Resolution - 480 TV Lines
- Wide Dynamic Range(WDR)
- Day/Night Function with ICR
- 0.1 Lux(Color), 0.03 Lux(B/W)
- Separate Camera Control Board
 - OSD Menu
 - Service Monitor Output
- 12VDC/24VAC Dual Voltage

Lens Options

- 2.6~6mm, DC Auto Iris
- 3.8~9.5mm, DC Auto Iris
- 9~22mm, DC Auto Iris

Construction

- 4" Polycarbonate Bubble
- 3-Axis Gimbal
- Flush Mount Housing w/ Surface Mount Plate in a single package
- Ivory or Black Plastic Housing Options
- Aluminum Wall Mount (Option)
- Compact Size

3-Axis Gimbal

Cover every angle !



Pan



Tilt



Horizontal Rotation



Tilted View with 2-Axis Bracket



Perfect View with 3-Axis Gimbal

W D R

See through the light !



Conventional BLC



W D R

Day/Night

See in the dark !



Color Mode



Clear B/W Mode

NUVICO INC.

53 Smith Street, Englewood, NJ 07631 USA
Phone 201-541-1605 Toll Free 866-523-1700 Fax 201-541-1620
sales@nuvico.com www.nuvico.com

NUVICO reserves the right to alter product offers and specification at any time without notice.
NUVICO EasyView and the NUVICO logo are registered trademarks of NUVICO.
© Copyright 2006, NUVICO. All rights reserved.

NUVICO®

Connecting Video Anywhere™

NUVICO EasyView™

Indoor Color Dome Cameras

CD-WD Series / High Resolution • WDR • Day/Night

Available Models

CD-WD266N/P-AI

2.6~6mm Vari-focal Lens, 12VDC/24VAC, Ivory Housing

CD-WD266N/P-AB

2.6~6mm Vari-focal Lens, 12VDC/24VAC, Black Housing

CD-WD3895N/P-AI

3.8~9.5mm Vari-focal Lens, 12VDC/24VAC, Ivory Housing

CD-WD3895N/P-AB

3.8~9.5mm Vari-focal Lens, 12VDC/24VAC, Black Housing

CD-WD922N/P-AI

9~22mm Vari-focal Lens, 12VDC/24VAC, Ivory Housing

CD-WD922N/P-AB

9~22mm Vari-focal Lens, 12VDC/24VAC, Black Housing

Specifications

Item	CD-WD Series	
Video Formats	NTSC	PAL
Image Sensor	1/3" CMOS	
Sync System	Internal	
Scanning system	525 Lines, Interlaced	625 Lines, Interlaced
Electronic Shutter	1/60 ~ 1/100,000	1/50 ~ 1/100,000
Main Video Output	1.0 Vp-p Composite, 75 ohm	
Service Monitor Output	1.0 Vp-p Composite, 75 ohm	
Horizontal Resolution	480 TV Lines	
Min. Illumination	0.1 Lux(Color), 0.03 Lux(B/W)	
S/N Ratio	48dB	
Dynamic Range	120dB(max), 95dB(typical)	
AGC Control	0~34dB	
Day/Night Function	ICR	
Lens Options (DC Auto Iris)	Vari-focal: 2.6~6mm, 3.8~9.5mm, 9~22mm	
Camera Control & Setup	OSD Menu	
Operating Temperature	0°C ~ +45°C	
Operating Humidity	Within 90% RH	
Power Consumption	1Amp	
Power Requirement	12VDC/24VAC Dual Voltage	

Specifications are subject to change without any prior notice.

Accessories

CV-WM-I

Wall Mount for EasyView Domes - Ivory

CV-WM-B

Wall Mount for EasyView Domes - Black

CA-SMC30

Service Monitor Cable for EasyView Domes

Easy Camera Setup



Camera Control Board is conveniently located at the base of Dome Housing. Service Monitor Output, DC Level Button and Dip Switches are easily accessible for quick camera setup.

Easy Gimbal Adjustment



Traditional Dome Insert has been fully integrated into the Gimbal for complete camera concealment. Uniquely designed Gimbal mechanism yields maximum lens rotation & placement (85° Tilt, 355° Pan), in quick and simple steps.


Easy Housing Installation




Either flush mounted or surface mounted, EasyView Dome Cameras have a number of pre-drilled mounting holes that accommodate various electrical junction boxes, making installation easy and less time consuming. Optional Wall Mount provides additional flexibility.

Dimensions (UNIT: mm)


Flush Mount



Surface Mount



Top View



NUVICO INC.

53 Smith Street, Englewood, NJ 07631 USA

Phone 201-541-1605 Toll Free 866-523-1700 Fax 201-541-1620

sales@nuvico.com www.nuvico.com

NUVICO reserves the right to alter product offers and specification at any time without notice. NUVICO EasyView and the NUVICO logo are registered trademarks of NUVICO.

© Copyright 2006, NUVICO. All rights reserved.

NUVICO®

Connecting Video Anywhere™