



- SONY 1/3" CCD (Super HAD)
- 600 TVL Resolution
- 2.8 ~ 10.5mm (F1.2) Lens w/ True D/N Cut Filter
- S5 Digital Signal Processor
- Digital Noise Reduction (DNR)
- Sense Up Feature for Optimal Night Image
- Digital Image Stabilization (DIS)
- Back Light Compensation (BLC)
- High Light Compensation (HLC)
- OSD Menu Control (Built-in Joystick or CE-REMOTE)
- 3-Axis Adjustment
- DC12V / AC24V

[illegible]

CE-VXWBB	Wall Mount Bracket (in Black)
CE-VXPC	3/4" Pendant Mount Cap
CE-VXRB	Black Rubber Vandal X Dome Cover
CE-VXRW	White Rubber Vandal X Dome Cover
CE-REMOTE	
- Plugs directly into Camera	
- Adjusts OSD Functions	
- Test Monitor Connection	

Camera	CE-VX40B
Image Sensor	1/3 Inch SONY (Super HAD) CCD
Resolution	600 TV Lines
Effective Pixels	768 (H) x 494 (V)
Scanning System	2:1 Interlace
S/N Ratio	52dB (AGC Off, Weight ON)
Sync System	Internal / Line Lock
Scanning Frequency	15.734 KHz (H), 59.94 Hz (V)
Minimum Illumination	0.05 Lux / F1.2 (Color), 0.0001 Lux w/Sense-Up at x256
Shutter Speed	1/60 ~ 1/100,000 sec.
Dynamic Range	62dB (Max.)
Lens	2.8 ~ 10.5mm (F1.2) w/True D/N Filter
Video Output	1.0 Vp-p, 75Ω
Power Consumption	Max. 110mA (AC24V), Max. 220mA (DC12V)
Power Requirement	DC12V / AC24V
Operating Temperature	-20°F ~ 122°F
Weather Rating	IP 68
Dimensions	5.74" (Dia.) x 4.13" (H)
Weight	2.75 lbs.
OSD Menu	Control with OSD Joystick or CE-REMOTE
Lens	DC Video
Exposure	Brightness / Shutter / AGC / Sens-Up / Return
White Balance Control	ATW / Manual / AWC Set / Outdoor / Indoor
SSDR	OFF / ON
Backlight	OFF / BLC / HLC
DNR3	OFF / ON
Day/Night	Auto / Color / B&W / Extern
Special	Image Adj., Monitor, Cam Title, Sync, Motion Det., Privacy, Comm. Adj., Language, Return
Exit	Save / Not Save / Reset

