



ONVIF
Compliant

H.264 Megapixel Outdoor IP Mini Domes

GANZ
PiXeIPro

Features:

- Optimized for HD
- 1080p HD Resolution
- 1/2.8" CMOS Sensor
- 2.1mm, 4.3 or 6.0mm Lens
- PoE (802.3af Class 2)
- Motion Triggered Alarm
- Dual Streaming Video
- Service Monitor Output
- Digital Day/Night
- DPC (Defective Pixel Correction)
- IP66 Rated for all weather conditions



Integrated with:



Check our website for updates on additional software partners

Specifications

Models		ZN-MD221M	ZN-MD243M	ZN-MD260M
Camera	Image Sensor	1/2.8" Sony IMX-036 CMOS Sensor		
	Max. Resolution	1920 x 1080		
	Effective Pixels	2096 (H) x 1561 (V)		
	Effective Image Size	5.24mm (H) x 3.90mm (V), 6.53mm (Diagonal)		
	White Balance	ATW / Manual (Preset)		
	Electronic Zoom	2 ~ 10x (Client Software)		
	AGC	Yes		
	BLC (Back Light Compensation)	Yes		
	Iris	No		
	Shutter Speed	1/4, 1/10, 1/12.5, 1/15, 1/20, 1/25, 1/30, 1/50, 1/60, 1/100, 1/120, 1/240, 1/480, 1/960, 1/1024, 1/2000s		
	Slow Shutter	2x		
	Lens	2.1mm, fixed	4.3mm, fixed	6.0mm, fixed
	Day/Night Performance	Digital Day & Night		
	S/N ratio	50 dB or more		
	Min. Illumination	Color: 0.63 lux (F3.5, 50IRE)		
Analog	Video Signal	NTSC/PAL selectable		
	Monitor Output	Composite Output (BNC), 75 ohm 1Vpp		
	Scanning Frequency	NTSC: (H) 15.734 kHz, (V) 59.94 Hz PAL: (H) 15.625 kHz, (V) 50 Hz		
Network	Network	10BASE-T, 100BASE-TX, RJ45		
	Image Compression	H.264 : Main Profile, Base/High Profile@V2.0 MJPEG / Image quality: 75 Steps (Q value)		
	Resolution	1920 x 1080 (Full HD), 1280 x 1024 (SXGA),		
		1024x768 (XGA), 1280 x 720 (720p)		
		640 x 480 (VGA), 320 x 240 (QVGA)		
	Protocol	704x480 (4CIF), 352x240 (CIF)		
		IPv4, HTTP, SMTP, UPnP, DNS,		
		RTSP, DDNS, RTP, TCP, UDP, RTCP, DHCP, ARP		
	Frame Rate	IGMP, ICMP, NTP		
		1 fps ~ 30 fps		
		Internet Explorer 7.0 or above, Firefox, Chrome, Smart Phone		
	Web Browser	Password Protection		
	Security	HTML based API		
Power	SDK (API)	User set 4 ROI (Region of Interest)		
	VMD (Video Motion Detection)	10 Step Sensitivity		
	Alarm Trigger	VMD		
	Power Source	PoE (IEEE 802.3af compliant)		
	Power Consumption	110mA @ DC48V, Max 3W		
	Temperature	14°F~122°F (-10°C ~ 50°C)		
	Ambient Humidity	Less than 90%, Non-condensing		
	Materials	Aluminum Diecasting		
	Weight	0.8lbs. (360g)		
	Dimensions	4.3"ø x 2.7" H (110mm ø x 67.5mm H)		
Additional	Certifications/IP Rating	IP66, CE, FCC, WEEE, InVIF		

Setup and recording software included. All specifications are subject to change without notice.