

**speco technologies™**

## Color or B/W Clock Camera



**CVC-585RC**  
(Color Version)

**CVC-285RC**  
(B/W Version)

| Features                                  | Benefits                                          |
|-------------------------------------------|---------------------------------------------------|
| Stylish Design .....                      | Discreet surveillance of sensitive areas          |
| High Resolution/Low Light Operation ..... | Good performance in a variety of conditions       |
| Fully Assembled .....                     | Just hang on the wall. Nothing to build or adjust |

### Specifications

|                             | CVC-285RC (B/W Version)                    | CVC-585RC (Color Version)            |
|-----------------------------|--------------------------------------------|--------------------------------------|
| Dimensions .....            | 1.5"L x 11"W x 11"H .....                  | 1.5"L x 11"W x 11"H                  |
| Electronic Shutter .....    | 1/60 - 1/100,000 seconds .....             | 1/60 - 1/100,000 seconds             |
| Housing .....               | Functional clock, wood frame .....         | Functional clock, wood frame         |
| Humidity .....              | Within 95% RH .....                        | Within 95% RH                        |
| Image Device .....          | 1/3" B/W CCD image sensor .....            | 1/3" Color CCD image sensor          |
| Lens .....                  | 3.6mm wide angle lens .....                | 3.6mm wide angle lens                |
| Minimum Illumination .....  | 0.02 Lux .....                             | 1 Lux                                |
| Number of Pixels .....      | 512 Horizontal x 492 Vertical .....        | 512 Horizontal x 492 Vertical        |
| Output .....                | Video-BNC, Power- DC jack .....            | Video-BNC, Power- DC jack            |
| Resolution .....            | 420 Lines .....                            | 350 Lines                            |
| Scanning Frequency .....    | 15.75 kHz Horizontal, 60 Hz Vertical ..... | 15.75 kHz Horizontal, 60 Hz Vertical |
| Scanning System .....       | EIA standard 525 line .....                | EIA standard 525 line                |
|                             | 60 fields/second                           | 60 fields/second                     |
| Video Output .....          | BNC .....                                  | BNC                                  |
| Video Output .....          | 1.0 Vp-p, 75 ohm .....                     | 1.0 Vp-p, 75 ohm                     |
| Video S/N Ratio .....       | Greater than 48 dB .....                   | Greater than 50 dB                   |
| Power Supply .....          | Regulated 12V DC power supply .....        | Regulated 12V DC power supply        |
|                             | included (UL and CSA listed),              | included (UL and CSA listed),        |
|                             | battery (AA) for quartz clock              | battery (AA) for quartz clock        |
| Operating Temperature ..... | 14°F to 122°F .....                        | 14°F to 122°F                        |

#### Package Includes:

|                         |                   |              |
|-------------------------|-------------------|--------------|
| Clock Camera            | Battery for Clock | Instructions |
| Power Supply for Camera | Warranty          |              |

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880