

Color or B/W Angle Mount Camera



CVC95AM B/W

CVC695AM Color

Features

Our B/W and Color CCD angle mount weather resistant cameras are encased in 18 gauge tamper-resistant stainless steel housings. The B/W version has a 0.02 lux low light sensitivity and the color version has a 1.0 lux low light sensitivity with 420 lines of resolution. They feature 3.6mm wide-angle lenses that view at a downward angle of 38 degrees, with BNC video output. A tamperproof screw for vandal resistant mounting and 12V DC power supply are included.

Specifications

	CVC95AM	CVC695AM
Resolution	420 lines	420 lines
Image Device	1/3" B/W CCD image sensor	1/4" color CCD image sensor
Electronic Shutter	Auto 1/60 -1/100,000 second	Auto 1/60 -1/100,000 second
Lens	3.6 mm wide angle lens, Hor. 72°, Vert. 53°	3.6 mm wide angle lens, Hor. 72°, Vert. 53°
Minimum Illumination	0.02 lux	1.0 lux
Video Output Level	1.0 Vp.p, 75 ohm	1.0 Vp.p, 75 ohm
Video S/N Ratio	Greater than 50 dB	Greater than 50 dB
Output	Video - BNC, Power -DC jack	Video - BNC, Power- DC jack
Operating Temperature	14° F to 122° F	14° F to 122° F
Humidity	Within 95% RH	Within 95% RH
Power Consumption	150 mA	210mA
Power Supply	Regulated 12 V DC power supply included (UL and CSA listed)	Regulated 12 V DC power supply included (UL and CSA listed)
Housing	18 gauge stainless steel	18 gauge stainless steel
Scanning Frequency	Horizontal 15.75 kHz vertical 60 Hz	Horizontal 15.75 kHz vertical 60 Hz
Dimensions	2.5" L x 2.25" W x 2.75" H	2.5" L x 2.25" W x 2.75" H
Weight	6.8 oz.	6.8 oz.

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880