

D24PS 24 Channel DVR with Digital Deterrent™
D32PS 32 Channel DVR with Digital Deterrent™

D24PS500	D24PS4TB	D32PS500	D32PS4TB
D24PS1TB	D24PS6TB	D32PS1TB	D32PS6TB
D24PS2TB		D32PS2TB	

Features

Optimized for full HD surveillance

Expanded video display options - HDMI support

Storage expansion via eSATA and iSCSI

D24PS: 8 analog channels + 16 IP channels

D32PS: 16 analog channels + 16 IP channels

Monitoring


- Up to 5 monitors connectable simultaneously
- 16 Ch display for every monitor including spot monitor
- Full HD (1920 x 1080p) resolution support
- Various screen formats for Full HD and standard monitors
- On-Live Playback (Triplex)
- Data archiving support
- User Access: up to 10 concurrent users

Record / Search

- Various recording modes: Continuous, Motion, Alarm, Pre/Post-Event, Text-In, Panic
- Easy record scheduling
- Various searching modes: Date/Time, Calendar, Time Bar, Event, Motion, Alarm, Text-In
- Disk mirroring, data archiving support
- Various actions (PTZ preset, record cameras, alarm, save image) configurable

External Device

- External hard drives attachable via eSATA port
- iSCSI support
- Remote keyboard support
- Various PTZ protocol support (60+)
- Recording rate up to 480 fps
- Free Speco DDNS service for use with dynamic IP addresses
- MAC® software provides live view and playback*
- POS/ATM support with text overlay and searchable database
- Simultaneous live view or playback while continuing to record, network transfer
- Text message alerts of system activity and status
- Remote monitoring, recording, playback, change system settings and camera control via network and/or Internet
- Real time live display
- IR Remote control included - individually control up to 16 DVRs
- Multiple analytics such as museum search and advanced motion detection
- EZ setup, EZ network, EZ record, EZ search
- USB 2.0 port for video clip exporting



Storage from 500GB up to 6TB

*For the latest mobile apps
and CMS software go to:
www.specotech.com/DVRApps*



- Easy software upgrade via Network or USB Flash drive
- User Access: up to 10 concurrent users
- Configurable per channel normal and event recording frame rate & picture quality or globally via EZ record
- Full system monitoring
- Free Central Management System (Speco Central) software allows viewing of multiple DVRs on a PC
- Email notification of alarm events
- Per channel built-in PTZ camera protocol including Pelco D
- Automatic camera detection (Plug & Play)
- Digital Zoom in live mode and playback
- Covert camera operation provides enhanced security and administrator control
- Playback while watching live on same monitor
 - Up to 30 minutes pre-alarm recording
 - Up to 15 minutes post-alarm recording
- Hard drive status monitoring
- Remote upgrade
- USB mouse supported (not included)
- Multiple language on-screen menus
- Password to secure installation with configurable user authentication levels
- 2 way audio
- DVR supports static IP, DHCP, PPPoE and DDNS
- Power Consumption: AC100-240 V - 50/60Hz, 2.0 - 1.0A
- Operating Temperature: 41° F - 104° F
- Dimensions: 16.9" (W) x 3.46" (H) x 15.7" (D)
- Weight: 17.6 lbs.
- Rack mountable
- 3 year warranty

Free smartphone apps available

iPhone and Android are trademarks of Apple & Google respectively.
Blackberry is registered to RIM.



EZ Set-Up Wizards!

One click wizard guides you to set up essentials of the system in a logical and easy to understand sequence.

- Date/Time • Recording method • Recording video quality • Network

Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 7/19/12

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880
www.specotech.com

Technical Specifications: PS Hybrid DVR with Set-Up Wizards



Model Name	D24PS	D32PS
Video Inputs	8 BNC	16 BNC
Video Outputs	Primary: 1 HDMI, 1 VGA (HD), 1 BNC (SD)	Primary: 1 HDMI, 1 VGA (HD), 1 BNC (SD)
	Secondary: 1 VGA (SD), 1 BNC (SD)	Secondary: 1 VGA (SD), 1 BNC (SD)
	Spot: 1 BNC (8CH)	Spot: 1 BNC (16CH)
Looping Outputs	8 BNC	16 BNC
Display Resolution	HD: 1920 x 1080, SD: 720 x 480	
RECORD & PLAYBACK		
Compression	H.264	
Recording Rate	240 fps @ CIF / 240 fps @ 2CIF / 120 fps @ D1	480 fps @ CIF / 240 fps @ 2CIF / 120 fps @ D1
Playback Rate	240 fps @ CIF	480 fps @ CIF
Recording Mode	Time-Lapse, Event, Pre-Event (up to 30 min), Text-In, Panic	
Search Mode	Date/Time, Record Table, Calendar, Event, Motion, Museum, Text-In	
SYSTEM		
Operating System	Embedded Linux	
Storage	Max. 3 HDD + eSATA	
Data Export	USB (HDD, FlashDrive), SATA DVD_RW	
Data Backup	Archiving, Mirroring	
NETWORK		
Connection	2 x Gigabit Ethernet	
Protocols	Manual, ADSL, DHCP, DVRNS	
Remote Software	Speco Central, Speco Remote (Internal, External)	
Max Transmission Rate	120 fps @ CIF	
INTERFACE		
Audio In / Out	RCA 4 / 1 + 1 HDMI	RCA 4 / 1 + 1 HDMI
Alarm In / Out /	16 / 4	
Serial Interface	RS232, RS485	
External Interface	2 x USB 2.0, eSATA	
User Interface	Front Buttons, Mouse, IR Remote Control, Remote Keyboard (Jog/Shuttle)	
OTHER		
Dimensions (W x H x D)	16.9" (W) x 3.46" (H) x 15.7" (D)	
Operating Temperature	41° F - 104° F	
Operating Humidity	0 - 90%	
Power	AC100 - 240 V - 50/60 Hz, 2.0 ~ 1.0A	
Approvals	FCC, UL, CE, CB, KCC, KC, PSE	
HYBRID		
Max Channels	16ch x 2MP	
Supporting Products	ONVIF, ONSIP	
Mega-Pixel Camera Support	Up to 2MP (max 16CH x 2MP under 70 ips @ 2MP capacity)	
Display Rate	CIF: 480ips (NTSC or progressive)	
	2CIF: 240ips (NTSC or progressive)	
	4CIF: 120ips (NTSC or progressive)	
	1MP: 48ips (Progressive) (1HD = 2.5 x 4CIF)	
	2MP: 24ips (Progressive) (1HD = 5 x 4CIF)	
Playback Rate	CIF: 480ips (NTSC or progressive)	
	2CIF: 240ips (NTSC or progressive)	
	4CIF: 120ips (NTSC or progressive)	
	1MP: 48ips (Progressive) (1HD = 2.5 x 4CIF)	
	2MP: 24ips (Progressive) (1HD = 5 x 4CIF)	
Recording Rate	CIF: 140ips (NTSC or progressive)	
	2CIF: 130ips (NTSC or progressive)	
	4CIF: 110ips (NTSC or progressive)	
	1.3MP/720p: 110ips (Progressive)	
	1080p: 70ips (Progressive)	

Please note that specifications and unit exterior design are subject to change without notification.

For more information contact Speco Technologies 200 New Highway, Amityville, NY 11701
Toll Free: 1-800-645-5516 Fax: 631-957-9142 or 631-957-3880 Website: www.specotech.com

7/19/12