DIGIMERGE | Right for Business





DBB13TL-PK4

The DBB13TL-PK4 camera bundle is the perfect value-driven choice for residential, retail or small commercial applications. Each camera features 18 IR LED's that are invisible to the human eye, making nighttime monitoring more practical and effective. The mechanical IR cut filter ensures proper color rendering during the day while fully taking advantage of available infrared light during the night. The DBB13TL-PK4, the new leader in value.

Features:

- True Day/Night with mechanical IR cut filter ensures best in class image reproduction
- Day / night mode: picture automatically switches camera to B&W delivering better clarity in low light conditions
- 18 Covert IR LEDs produce effective night vision range of 40ft (12m)
- IR LEDs don't glow red for covert nighttime operation
- Weatherproof design ideal for outdoor and indoor applications (IP66)
- Versatile stand allows for ceiling or wall mounting
- 12V DC operation, 4-in-1 power adapter included

IR Illumination Range & Day/Night Model:



 18 IR LEDs provides effective night vision range of 40ft / 12m (under ideal conditions. Objects at or beyond may be partially or completely obscured, depending on the camera application)







LOW LIGHT CONDITION


 Picture automatically switches camera to B&W delivering better clarity in low light conditions

Specifications:

opcomodions.	
Image Sensor Type:	1/4" Color Image Sensor
Video Format:	NTSC
Horizontal Resolution:	420 TV Lines
Scan System:	NTSC: 525 Lines 2:1 interlace
Sync System:	Internal
S/N Ratio:	More than 48dB
Iris:	AES
AES Shutter Speed:	1/30 ~ 1/62,500 Sec.
Mini Illumination:	0.6 LUX without IR LED, 0 LUX with IR LED
Video Output:	Composite 1.0 Vpp @ 75 ohm
Lens/Focal Length/Type:	3.6mm Fixed
Lens/ Lens Mount:	Board Type
Aperture:	F1.8
FOV (Diagonal):	64 degrees
Termination:	BNC
IR LED/Qty/LED Type (nm)/Night Vision Range:	18pcs IR LED / 940nm / 12m / 40 Ft
Power Requirement:	12V DC
Power Consumption:	170mA
Operating Temp Range:	-4°~122° F / -20° ~ 50° C
Unit Weight:	0.3kg / 0.6 lbs
Unit Dimensions: (W x D x H)	66 x 107 x 132mm / 2.6 x 4.2 x 5.2" incl. Stand
Environmental Rating:	IP 66
Built In Microphone:	No

IR illumination range up to 40ft (12M) under ideal conditions. Objects at or beyond this range may be
partially or completely obscured, depending on the camera application.

Dimension:



Product Information:

UPC:	8-41430-00610-7
Package Dimensions: (W x D x H)	315 x 140 x 295mm/ 12.4 x 5.5 x 11.6"
Package Cube:	0.013cbm / 0.459cbf
Package Weight:	1.9kg / 4.2lbs
Includes:	4 x Cameras 4 x Flex stands 1 x 4-in-1 12V DC power adapter

