Box Fixed: Day/Night | 540 TVL



HIGH RESOLUTION IMAGE CAPTURE

MODEL: CAM/BDN5/A

FEATURES

- Day & Night mode: Color converts to B/W in low light
- 1/3" Sony Super HAD CCD
- Ultra sensitivity minimum illumination of 0.002 lux (Sensitivity Up color mode)
- Selectable BLC zone
- Privacy masking / Mirror function / Motion detection
- Full control via the OSD menu key on the rear of the camera
- AGC adjustment
- Dual power operation 12v DC / 24v AC
- Easy to install and configure
- 3 Year Advanced Replacement Warranty









SPECIFICATION


		CAM/BDN5/A (NTSC)
Camera Features	Resolution	540 TVL (Color)
	Image Sensor	1/3" Sony Super HAD CCD
	Minimum Illumination	0.3 lux (Color), 0.002 lux (sens-up)
	Total Pixels	811(H) x 508(V)
	Scanning System	2 : 1 interlace
	Scanning Frequency (H)	15.73Khz
	Scanning Frequency (V)	59.9Hz
	Electronic Shutter	1/60 ~ 1/120,000 sec
	Sync System	Internal / Line lock
	Signal to Noise Ratio	50dB (AGC off)
	Video Output Level	1.0Vp-p (75Ω, composite)
	Day/Night	Auto / Color / B/W
Function Options	AGC/BLC/Flickerless	Off / Low / Middle / High
	Display title	Off / On
	Sharpness	Off / On (0 ~ 31)
	Mirror	Off / On
	Privacy Zone	Off / On (4 point)
	DNR	Off / Low / Middle / High
	Motion Detection	Off / On (4 point)
	Preset	Default / Save / End
Power Supply	Power Source	12v DC / 24v AC ± 10%
	Power Consumption	4.0 Watts
Mechanical	Power Input	2-Pin terminal block
	Video Output	BNC Connector
	Auto Iris Output	4-Pin mini din jack (standard connection)
	Lens Mount	C/CS mount (selected through back focus)
	Mounting Hole	1/4"-20 UNC (top or bottom)
	Dimensions (HxWxD)	2.2" x 2.6" x 4.7" (56mm x 66mm x 120mm)
Environmental	Operating Temperature	14° ~ 122°F (-10° ~ 50°C)
	Operating Humidity	0 ~ 96% (non-condensing)
	Weight	8.8oz (250g)
Warranty		3 Year Advanced Replacement





PRODUCT CODES*	
BOX FIXED: DAY/NIGHT 540 TVL NOTE: Lens not included	CAM/BDN5/A
2010 EXTERNAL HOUSING W/ BRACKET AND HEATER 2015 EXTERNAL HOUSING W/ BRACKET AND HEATER 2015 WIPER UNIT	DM/2010-606 DM/2015-606 DM/94035

^{*} SEE OUR WEBSITE FOR FULL ACCESSORIES LISTING



PLEASE CHECK THE WEBSITE OR YOUR LOCAL REPRESENTATIVE FOR PRODUCT ORDERING INFORMATION AND OTHER DEVELOPMENTS

www.dedicatedmicrosinc.com

Dedicated Micros USA 14434 Albemarle Point Place, Suite 100, Chantilly, Virginia 20151 USA Toll Free: 800 864-7539 Tel: +1 703 904-7738 Fax: +1 703 904-7743

Dedicated Micros Canada 5580 Explorer Drive, Suite 501, Mississauga, Ontario L4W 4Y1 Tel: +1 905 602-6222 Fax: +1 905 602-6221

The manufacturer reserves the right to change the specification without notice. All trademarks are courtesy of registered owners.

The DM logo is a trademark of Dedicated Microcomputers Group Ltd. NetVu Connected is a trademark of the AD group.

