

H.264 Network DVR

DR-1 Series 4, 8, and 16 Channels Available



IR remote control included for easy programming and playback.



Features:

- ▶ High resolution recording: Up to 720x480 D1.
- ▶ VGA output (up to 1280x1024 resolution).
- ▶ HDMI output (up to 1920x1080p).
- ▶ Allows simultaneous live view or playback while still continuing to record, network transfer, and back up data.
- ▶ H.264 video compression records twice as much data as DVRs that use MPEG or MJPEG without sacrificing video quality.
- ▶ Easily connect to DVR through the internet or a local intranet via IE 6 or above for remote viewing, recording, and dome control.
- ▶ Remote access via PC, MAC, or Java based smart phones such as the iPhone®, Android™, Windows Mobile®, phones using the Symbian OS™, and BlackBerry®.
- ▶ Per channel recording priority programmable for schedule, alarm, motion, or continuous.
- ▶ Dual stream support for simultaneous access from a PC, MAC, and/or a cell phone at low bandwidth.
- ▶ Free CMS software included for remote playback, along with recording and backup to an offsite location.
- ▶ Free DDNS server for use with Dynamic IP addresses.
- ▶ Event notification, along with optional video file attachment.
- ▶ Twin SATA controller for expandable HDD storage up to 4TB.
- ▶ Dedicated audio channel for each video channel.
- ▶ Two USB 2.0 ports for backup of recorded files or quick export of recorded video.
- ▶ RS-485 control protocols for most PTZ cameras
- ▶ Rack mount or stackable.
- ▶ Optional rack-mounting brackets available.
- ▶ EZ Copy: Simple one-button video export (.DRV or .AVI).
- ▶ Supports internal SATA or external USB DVD/RW for easy backup and video export.
- ▶ Network hardware supports 10/100 Mbps.
- ▶ On-screen menu with 24 built-in languages.
- ▶ 3-Year warranty (including HDD).

Ordering Information:

4 Channels

DR-104Q	120PPS, No HDD
DR-104-500Q	120PPS, 500GB
DR-104-1.0TQ	120PPS, 1TB
DR-104-2.0TQ	120PPS, 2TB

8 Channels

DR-108Q	240PPS, No HDD
DR-108-500Q	240PPS, 500GB
DR-108-1.0TQ	240PPS, 1TB
DR-108-2.0TQ	240PPS, 2TB

16 Channels

DR-116Q	480PPS, No HDD
DR-116-500Q	480PPS, 500GB
DR-116-1.0TQ	480PPS, 1TB
DR-116-2.0TQ	480PPS, 2TB

SECO-LARM

16842 Millikan Avenue
Irvine, CA 92606

Tel: 1-949-261-2999

1-800-662-0800

Fax: 1-949-261-7326

Web: www.seco-larm.com

Email: info@seco-larm.com




Copyright © 2011
SECO-LARM U.S.A., Inc.
All rights reserved

H.264 Network DVR



Dimensions:



Specifications:

			DR-104Q*	DR-108Q*	DR-116Q*	
Video	Operating system		Embedded Linux			
	Inputs		BNCx4, 1.0Vp-p, 75Ω	BNCx8, 1.0Vp-p, 75Ω	BNCx16, 1.0Vp-p, 75Ω	
	Outputs	Main monitor	BNCx1, 1.0Vp-p, 75Ω			
		Call monitor	N/A	BNCx1, 1.0Vp-p, 75Ω		
	HDMI output		1024x768, 1280x1024, 1920x1080p			
	VGA output		800x600, 1024x768, 1280x1024 pixels			
Audio	Input		RCAx4, Line-in	D-Sub, Line-in		
	Output	Main audio	RCAx1, Line-out			
		Call audio	N/A	RCAx1, Line-out		
	Data rate		8kb/s Per channel			
Recording & Storage	Compression method		H.264			
	Recording modes		Continuous, schedule, alarm, motion detection			
	Pre-alarm		Yes			
	Recording resolution & rate	NTSC	720x480	Max. 60PPS	Max. 60PPS	Max. 120PPS
			720x240	Max. 120PPS	Max. 120PPS	Max. 240PPS
			360x240	Max. 120PPS	Max. 240PPS	Max. 480PPS
		PAL	720x576	Max. 50PPS	Max. 50PPS	Max. 100PPS
			720x288	Max. 100PPS	Max. 100PPS	Max. 200PPS
			360x288	Max. 100PPS	Max. 200PPS	Max. 400PPS
	Recording quality		8 Presets levels, adjustable			
	Image size		1kB to 22kb/Picture			
	Storage mode		Linear/Circular			
	Data lifetime		Yes (Programmable)			
	Built-in storage interface		2x SATA (4TB max.)			
Export		USB 2.0 Port – Supports flash drive or external USB HDD				
Alarm	Alarm input		x4 via, D-Sub (TTL)	x8 via, D-Sub (TTL)	x16 via, D-Sub (TTL)	
	Alarm relay output		x1, D-Sub, 1.0A@30VDC			
	Alarm detection		NO/NC, Programmable			
	Motion detection		16x12 Grid array, sensitivity, trigger level adjustable			
	Video loss detection		Programmable			
Connectivity	Network connectivity		RJ-45, 10/100Mbps Ethernet, static IP, DHCP, PPPoE, and DDNS			
	Remote control software		Mac®, Java™, CMS, IE 6/7/8			
	Remote operation		Monitoring, playback, recording, system setup, dome camera control, archiving			
	Mobile viewing		iPhone®, Android™, Window Mobile®, Symbian™, BlackBerry®			
	RS-485		D-Sub			
	IR Remote		Yes			
	Dome camera control protocol		Pelco P, Pelco D, AD422, Fastrax 2, Panasonic, GE, DSCP, JVC			
	USB		2x USB 2.0 (Exporting, USB Mouse)			
General	Dimensions (WxHxD)		11 ³ / ₄ " x 2 ¹ / ₈ " x 14" (300 x 54 x 356mm)			
	Weight		Approximately 10-lb (4.5kg)			
	Operating temperature		32°~104° F (0°~40° C)			
	Relative humidity		10%~90% Non-condensing			
	Power Adapter		AC 100~240V, 50-60Hz, 60W adapter (included)			

*Each model is available with or without a hard drive. (500GB, 1TB, or 2TB)

SECO-LARM

16842 Millikan Avenue
Irvine, CA 92606

Tel: 1-949-261-2999

1-800-662-0800

Fax: 1-949-261-7326

Web: www.seco-larm.com

Email: info@seco-larm.com



Copyright © 2011
SECO-LARM U.S.A., Inc.
All rights reserved